



Controller Configuration

Current Configuration:

Custom

Available Configurations:

- 69NT40-511-14
- 69NT40-511-15
- 69NT40-511-16**
- 69NT40-511-17
- 69NT40-511-18
- 69NT40-511-19
- 69NT40-511-200
- 69NT40-511-201
- 69NT40-511-21
- 69NT40-511-22
- 69NT40-511-23
- 69NT40-511-24
- 69NT40-511-25
- 69NT40-511-26
- 69NT40-511-27

Selectable Variables:

Variable	Value
Dehumidification	OFF
Discharge Press Sensor	OUT
Suction Press Sensor	OUT
Economy Mode	STD
Defrost Interval Timer	NO SAVE
Advanced Pretrip	AUTO 2
Pretrip Results	DATA
Suction Temp Sensor	OUT
Bulb Mode	NORMAL
Arctic Mode	OUT
Probe Check Logic	STANDARD
Snap Freeze	NO SNAP
Temperature Unit Display	BOTH AVAIL
Electronic Chart Recorder	RTS
Autofresh Enable	OUT

Fixed Variables:

Variable	Value
Evaporator Fan	2 SPEED
Number of Probes	FOUR
Probe Calibration	OUT
Condenser Fan Speed	SINGLE
Unit Size	40 FOOT
Motor Phase	1 PHASE
Refrigerant	134a
Compressor speed	SINGLE
Defrost "Off" Selection	NO OFF
Quench Valve	TXV
Unloader	OUT
Condenser Press Control	IN
Discharge Temp Sensor	OUT
DataCorder	ON
Heater Tune	OLD

Save Option

69NT40-511-16

Save

Modify Selected Variable

OFF

Send

Close