

KIWI

***instructions
for
installation***

Document number: QSM000048E

Revision: PRELIMINARY

Date of first issue: 10.July.03

Date of latest issue: 10.July.03

COSTAN®

F3000

COSTAN TECHNICAL DOCUMENTATION PRODUCT: KWI DOC. no. QSM000048E CHAP. No. 1 CHAPTER: CONTENTS	CHAPTER REVISION STATUS						SIGNED AS IN CONFORMITY WITH APPROVED ORIGINAL	SHEET: 1/1
	ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.		DATE of 1st ISSUE: 10.July.2003
	A			D			ISSUED BY MKT	
	B			E				
C			F					


CHAP. No.	CHAPTER	NUMBER OF PAGES	REVISION STATUS
1	CONTENTS	1	“_”
2	SECTIONS	1	“_”
3	ELECTRICAL, WATER AND REFRIGERATING CONNECTIONS	3	“_”
4	POSITION OF PROBES	1	“_”
5	REQUIRED HEAT EXTRACTION RATE	1	“_”
6	ELECTRICAL INPUT	1	“_”
7	FEATURES OF EXPANSION VALVE	2	“_”
7.1	SETTINGS FOR CONTROLLER EKC201	1	“_”
8	WIRING DIAGRAMS	13	“_”
9	CABINET MULTIPLEXING AND FINISHING	7	“_”

KEY

- “_” First issue
- A, B, C..... Chapter revision index
- AA, AB, AC.. General revision index of document

COSTAN TECHNICAL DOCUMENTATION PRODUCT: KIWI DOC. no. QSM000048E CHAP. No. 2 CHAPTER: SECTIONS	CHAPTER REVISION STATUS						SIGNED AS IN CONFORMITY WITH APPROVED ORIGINAL PAGE: 2/2 DATE of 1st ISSUE: 10.July.2003 ISSUED BY MKT
	ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.	
	A			D			
	B			E			
				F			

KIWI SECTIONS




AVAILABLE LENGTHS Linear cabinets: 188 - 250 - 375 cm

COSTAN TECHNICAL DOCUMENTATION PRODUCT: KIWI DOC. no. QSM000048E CHAP. No. 3 CHAPTER: CONNECTIONS	CHAPTER REVISION STATUS						SIGNED AS IN CONFORMITY WITH APPROVED ORIGINAL	PAGE: 1/3
	ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.		DATE of 1st ISSUE: 10.July.2003
	A			D				
	B			E				
	C			F			ISSUED BY MKT	

KIWI

ELECTRICAL, WATER, REFRIGERATING CONNECTIONS

WATER AND REFRIGERATING CONNECTIONS SECTION






 WATER OUTLET

 FREON CONNECTION




COSTAN TECHNICAL DOCUMENTATION PRODUCT: KWI DOC. no. QSM000048E CHAP. No. 3 CHAPTER: CONNECTIONS	CHAPTER REVISION STATUS						SIGNED AS IN CONFORMITY WITH APPROVED ORIGINAL	PAGE: 2/3
	ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.		DATE of 1st ISSUE: 10.July.2003
	A			D			ISSUED BY MKT	
	B			E				
C			F					

CONNECTIONS - GROUND PLAN




COSTAN TECHNICAL DOCUMENTATION PRODUCT: KIWI DOC. no. QSM000048E CHAP. No. 3 CHAPTER: CONNECTIONS	CHAPTER REVISION STATUS						SIGNED AS IN CONFORMITY WITH APPROVED ORIGINAL	PAGE: 3/3
	ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.		DATE of 1st ISSUE: 10.July.2003
	A			D			ISSUED BY MKT	
	B			E				
C			F					

KIWI POSITION OF FEET



COSTAN TECHNICAL DOCUMENTATION PRODUCT: KIWI DOC. no. QSM000048E CHAP. No. 4 CHAPTER: POSITION OF PROBES	CHAPTER REVISION STATUS						SIGNED AS IN CONFORMITY WITH APPROVED ORIGINAL DATE of 1st ISSUE: 10.July.2003 ISSUED BY MKT	SHEET: 1/1
	ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.		
	A			D				
	B			E				
	C			F				

KIWI position of probes, thermal-expansion valve, remote thermostat



- ① air discharge probe
- ② air return probe
- ③ thermal expansion valve
- ④ remote thermostat
- ⑤ way-in of evaporator piping
- ⑥ way-out of evaporator piping

COSTAN TECHNICAL DOCUMENTATION PRODUCT: KIWI DOC. no. QSM000048E CHAP No. 6 CHAPTER: ELECTRICAL INPUT	CHAPTER REVISION STATUS						SIGNED AS IN CONFORMITY WITH APPROVED ORIGINAL	PAGE: 1/1
	ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.		DATE of 1st ISSUE: 10.July.2003
	A			D				ISSUED BY MKT
	B			E				
			C			F		

ELECTRICAL DETAILS

Power voltage: 230 V single-phase 50 hz

Wattage: W (Watt)

Amperage: A (Ampere)

Optional motor for night blinds: 160W - 0,8A

(1) Lighting (per row of lamps - standard ferromagnetic ballast)

(2) Standard power-factor-improved (compensated) lighting: $0,9 < \cos \Phi < 1$

KIWI

	L	STANDARD									OPTION					
		Fans			Heaters			Canopy lighting (1)			Defrost heaters			Shelf lighting (1)		
		NB	W	A	NB	W	A	NB	W	A(2)	NB	W	A	NB	W	A(2)
H2000	188	2	76	0,46				2	92	0,42	1	1280	5,6	2	92	0,42
H2200	250	2	76	0,46				2	92	0,42	1	1700	7,4	2	92	0,42
	375	3	114	0,69				3	138	0,63	1	2550	11,1	3	138	0,63

COSTAN TECHNICAL DOCUMENTATION PRODUCT: KIWI DOC. no. QSM000048E CHAP. No. 7 CHAPTER: THERMAL-EXPANSION VALVE	CHAPTER REVISION STATUS						SIGNED AS IN CONFORMITY WITH APPROVED ORIGINAL	PAGE: 1/2
	ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.		DATE of 1st ISSUE: 10.July.2003
	A			D				ISSUED BY MKT
	B			E				
	C			F				

FEATURES OF THERMAL-EXPANSION VALVE

FEATURES OF THE DANFOSS THERMAL-EXPANSION VALVE RANGE N - WITHOUT MOP - WITH ADAPTOR TO SOLDER

Selection rules:

- lab-tested effective heat extraction rate and evaporating temperature at 25 °C 60% RH, class 3 ;
- correspondent condensing temperature at + 35 °C;
- subcooling: 4 K.

KIWI

		R404A	
M	L	Type	Orifice
KIWI 2000	125	TS2	03
	188	TES2	03
	219		04
	250		04
	281		04
	375		05
KIWI 2200	125	TS2	03
	188	TES2	03
	219		04
	250		04
	281		04
	375		06

Refrigerating details refer to thermal-expansion valves adjusted for 5 K overheating.

COSTAN TECHNICAL DOCUMENTATION PRODUCT: KIWI DOC. no. QSM000048E CHAP. No. 7 CHAPTER: THERMAL-EXPANSION VALVE	CHAPTER REVISION STATUS						SIGNED AS IN CONFORMITY WITH APPROVED ORIGINAL PAGE: 2/2 DATE of 1st ISSUE: 10.July.2003 ISSUED BY MKT
	ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.	
	A			D			
	B			E			
	C			F			

FEATURES OF THE DANFOSS THERMAL-EXPANSION VALVE

Selection rules:

- lab-tested effective heat extraction rate and evaporating temperature at 25 °C 60% RH class 3 ;
- correspondent condensing temperature at + 35 °C;
- subcooling: 4 K.C
- considering overcapacity to be 25% and the maximum valve's opening to be between 50 and 75% as recommended by DANFOSS.

KIWI

		R404A	
M	L	Type	Orifice
KIWI 2000	125	AKV 10	4
	188		5
	219		6
	250		6
	281		6
	375		7
KIWI 2200	125		5
	188		5
	219		6
	250		6
	281		6
	375		7

Refrigerating details refer to thermal-expansion valves adjusted for 5 K overheating.

COSTAN TECHNICAL DOCUMENTATION	CHAPTER REVISION STATUS						SIGNED AS IN CONFORMITY WITH APPROVED ORIGINAL	PAGE: 1/1
	ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.		DATE of 1st ISSUE:
	A			D				10.July.2003
	B			E				ISSUED BY
PRODUCT: KWI				F			MKT	
DOC. no. QSM000048E	CHAP. No. 7.1							
CHAPTER: SETTINGS OF CONTROLLER EK201								

SETTINGS FOR CONTROLLER DANFOSS AKC201					Factory default settings
Parameter function		Danfoss controller parameters	Danfoss controller Min. value	Danfoss controller Max. value	KIWI
1.	Cut-out T° for S4 / Sout *	Out	-50°C	50°C	-2
2.	Cut-out T° for S3 / Sin *	In	-50°C	50°C	2
Thermostat parameters					
1.	Temperature unit (°C/°F)	r05	°C	°F	°C
2.	S4/Sout differential (r07= cut-in T° * - Sout cut-out signal)	r07	0.1 K	20 K	1
3.	S3/Sin differential (r08= cut-in T° * - Sin cut-out signal)	r08	0.1 K	20 K	1
4.	Correction of signal from S4/Sout	r09	-20.0 K	20.0 K	0
5.	Correction of signal from S3/Sin	r10	-20.0 K	20.0 K	0
Alarm parameters					
1.	Timing of temperature alarm *	A03	0	90 mn	10
2.	Upper limit exceeded S4/Sout (A05 = threshold * Sout cut-out T°)	A05	0 K	50 K	6
3.	Bottom limit of S4/Sout exceeded	A06	-50 K	0 K	-50
4.	Upper limit of S3/Sin exceeded (A07 = threshold * cut-out T° of Sin)	A07	0 K	50 K	50
5.	Lower limit of S3/Sin exceeded	A08	-50 K	0 K	-50
6.	S3/Sin alarm delay with night covers on	A09	-50 K	50 K	0
VEM Parameters					
1.	Min. operation time	c01	0 mn	15 mn	0
2.	Gap between two starts	c02	0 mn	15 mn	0
3.	Cut-in frequency in case of probe failure	c03	0%	100%	100
Defrost parameters					
1.	Compressor On under defrosting	d01	No	Yes	No
2.	Defrost end T° * (probe selection automatic according to d10)	d02	0	25 °C	10
3.	Interval between 2 defrosts (d03=24 / n° of defrosts per day*)	d03	OFF	48 h	4
4.	Safety time *	d04	0	180 mn	45
5.	Delay of defrost start signal on startup	d05	0	60 mn	0
6.	Drip time	d06	0	20 mn	0
7.	Fan start delay after defrost	d07	0	20 mn	0
8.	Fan start temperature (>25°=OFF)	d08	-25	26°C	OFF
9.	Fan operation under defrosting (yes/no)	d09	No	Yes	Yes
10.	Defrost probe	d10	OUT	DEF	OUT
11.	Alarm delay on defrost end *	d11	0	200 mn	35
12.	Display timing after defrost end	d12	0	30 mn	0
13.	Defrost start	d13	No	Yes	No
Clock parameters					
1.	1. Defrost start, hour	t01	OFF	23 h	Value to be defined at the time of installation for controllers Danfoss model S or S/C only
2.	1. Defrost start, minutes	t11	0	59 mn	
3.	2. Defrost start, hour	t02	OFF	23 h	
4.	2. Defrost start, minutes	t12	0	59 mn	
5.	3. Defrost start, hour	t03	OFF	23 h	
6.	3. Defrost start, minutes	t13	0	59 mn	
7.	4. Defrost start, hour	t04	OFF	23 h	
8.	4. Defrost start, minutes	t14	0	59 mn	
9.	5. Defrost start, hour	t05	OFF	23 h	
10.	5. Defrost start, minutes	t15	0	59 mn	
11.	6. Defrost start, hour	t06	OFF	23 h	
12.	6. Defrost start, minutes	t16	0	59 mn	
13.	Adjustment of hour	t07	0	23 h	
14.	Adjustment of minutes	t08	0	59 mn	
Ventilation parameters					
1.	Fans off when compressors are off	F01	No	Yes	No
2.	Fan stop time	F02	0	15 mn	0
Other parameters					
1.	Outlet timing on startup	o01	0	600 sec	0
2.	Digital input signals	o02	OFF	5	Values to be defined at the time of installation
3.	Network address (from 0 to 60)	o03	0	990	
4.	LON service connector	o04	OFF	100	
5.	Access code	o05	OFF	100	
6.	Type of probe used (Pt/PTC)	o06	Pt	PTC	Value to be defined at the time of installation for controllers Danfoss model S or S/C only
7.	Max. wait time after synchronised defrosts with slave cabinets	o13	OFF	2	
8.	Selection of regulation probe	o14	Aut	Out	Out
9.	Temperature display scale	o15	No	Yes	Yes
10.	Max. wait time after synchronised defrost	o16	1	30 mn	30
11.	Selection of display probe signal	o17	Aut	In	In
12.	Output manual control	o18	OFF	5	OFF

* Parameters to be adapted to the climatic class of foodstuffs

** Preset with night blind option

COSTAN TECHNICAL DOCUMENTATION PRODUCT: KWI DOC. no. QSM000048E CHAP. No. 8 CHAPTER: WIRING DIAGRAMS	CHAPTER REVISION STATUS						SIGNED AS IN CONFORMITY WITH APPROVED ORIGINAL PAGE: 1/13 DATE of 1st ISSUE: 10.July.2003 ISSUED BY MKT
	ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.	
	A			D			
	B			E			
	C			F			

WIRING DIAGRAMS

KEY TO ALL DIAGRAMS


- Q1 Circuit breaker
- Q2 Lighting cutoff switch
- Q3 Cutoff switch
- K1 Lighting contactor
- XA 1st air curtain fans
- XB Electric defrost (optional)
- XC Demist heater - 2nd air curtain fans
- XD Lighting
- XE Regulation
- XF VEM
- XG Lighting switch
- XH Relay 24V to control lighting (optional)
- XJ Relay to control 2nd air curtain
- XM FTB connection

ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.
A			D		
B			E		
C			F		

WIRING DIAGRAM SRTS 1
 (Security-operation terminal-board for 1 cabinet)

* Depending on equipment


- ❶ Lights remote control signal 24V AC
- ❷ Power supply 400V AC
- ❸ Defrost-start signal (250)
- ❹ Alarm dead contact (99-99)
- ❺ Thermostat signal (77-78)



ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.
A			D		
B			E		
C			F		

WIRING DIAGRAM FTB
 (End terminal-board)

* Depending on equipment




ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.
A			D		
B			E		
C			F		


WIRING DIAGRAM
 (Customised for SRTS-FTB)

★ Depending on equipment


1 Lights remote control relay




2 Lights switch



3 Lights remote control relay + Lights switch




4 Fans-stop relay




When this relay is provided along with night blinds (either electrical or manual), disconnect shunt K113-K114 on 1.B4/K1, 2.B4/K1 or 3.B4/K1

5 Motor-driven night blind relay



ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.
A			D		
B			E		
C			F		

WIRING DIAGRAMS READING PRINCIPLE




ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.
A			D		
B			E		
C			F		

WIRING DIAGRAM: TERMINAL BOARD OF CABINET

★ Depending on equipment

- | | |
|---|--|
| <p>1 Lights power supply</p> <p>2 Power supply of night blinds
 47: Up
 45: Down</p> <p>3 Power supply of demist heater and/or second air curtain</p> <p>4 Power supply of defrost heater</p> | <p>5 Power supply of fans + controller</p> <p>6 Solenoid valve</p> <p>7 Alarm dead contact</p> <p>8 Defrost-start signal</p> |
|---|--|




ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.
A			D		
B			E		
C			F		


WIRING DIAGRAM (FANS/DEFROST/NIGHT BLINDS)

★ Depending on equipment


1 1st air curtain fans




2 Electric defrost




3 Night blinds



4 2nd air curtain fans



5 Plug



ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.
A			D		
B			E		
C			F		

WIRING DIAGRAM (LIGHTING)


* Depending on equipment

1

Lighting with ferromagnetic ballast

*

0.E7 /XD
 1.E7 /XD
 2.E7 /XD
 3.E7 /XD
 4.E7 /XD




2

Lighting with electronic ballast

*

0.E7 /XD
 1.E7 /XD
 2.E7 /XD
 3.E7 /XD
 4.E7 /XD



ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.
A			D		
B			E		
C			F		


WIRING DIAGRAM (DISPLAY/THERMOSTAT)

★ Depending on equipment

9
8
7
6
5
4
3
2
1


1 EKC101

- 0.E1 /XE
- 1.E1 /XE
- 2.E1 /XE
- 3.E1 /XE
- 4.E1 /XE




2 EKA151

- 0.E1 /XE
- 1.E1 /XE
- 2.E1 /XE
- 3.E1 /XE
- 4.E1 /XE



3 PLUG

- 0.E1 /XE
- 1.E1 /XE
- 2.E1 /XE
- 3.E1 /XE
- 4.E1 /XE



ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.
A			D		
B			E		
C			F		

WIRING DIAGRAM (EKC201)

★ Depending on equipment

9

8

7

6

5

4


3

2

1

1 EKC201


★



★ Echelon
 ★ RTC

2 EKC201
 for timer

★



★ Echelon


ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.
A			D		
B			E		
C			F		

DATE of 1st ISSUE: 10.July.2003
ISSUED BY MKT


WIRING DIAGRAM (AC-DC SOLENOID/DEFROST RELAY/TIMER)

Depending on equipment


1 AC SOLENOID




2 DC SOLENOID



3 DEFROST START RELAY



4 TIMER




ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.
A			D		
B			E		
C			F		

WIRING DIAGRAM SRTS 3
 (Security-operation terminal board for 3 cabinets)

★ Depending on equipment

- 1** Lights remote control signal 24V AC
- 3** Defrost-start signal (250)
- 5** Thermostat signal (77-78)
- 2** Power supply 400V AC
- 4** Alarm dead contact (99-99)



Sheet: 1


- 11.C2 /D
- 10.C1 /C
- 10.C7 /B
- 12.B4 /E
- 12.B6 /E
- 11.C6 /D
- 10.C3 /C
- 10.C9 /A
- 12.B8 /E
- 13.B4 /E
- ★
- 10.C5 /C
- ★
- 13.B8 /E
- 16.B2 /E
- ★
- ★
- 16.B6 /E
- 17.B2 /E

ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.
A			D		
B			E		
C			F		

WIRING DIAGRAM SRTS 2
 (Security-operation terminal board for 2 cabinets)

* Depending on equipment


- 1** Lights remote control signal 24V AC
- 2** Power supply 400V AC
- 3** Defrost-start signal (250)
- 4** Alarm dead contact (99-99)
- 5** Thermostat signal (77-78)



COSTAN TECHNICAL DOCUMENTATION PRODUCT: KWI DOC. no. QSM000048E CHAP. No. 9 CHAPTER: MULTIPLEXING AND FINISHING CABINETS	CHAPTER REVISION STATUS						SIGNED AS IN CONFORMITY WITH APPROVED ORIGINAL	PAGE: 1/7
	ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.		DATE of 1st ISSUE: 10.July.2003
	A			D			ISSUED BY MKT	
	B			E				
C			F					

MULTIPLEXING AND FINISHING CABINETS

CAUTION: the horizontal strengthening bar must be removed just before fastening the cabinet to the floor.



REMOVE THE TROLLEYS



Move the trolleys out of the cabinet and unpack them.



COSTAN TECHNICAL DOCUMENTATION PRODUCT: KWI DOC. no. QSM000048E CHAP. No.9 CHAPTER: MULTIPLEXING AND FINISHING CABINETS	CHAPTER REVISION STATUS						SIGNED AS IN CONFORMITY WITH APPROVED ORIGINAL PAGE: 2/7 DATE of 1st ISSUE: 10.July.2003 ISSUED BY MKT
	ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.	
	A			D			
	B			E			
	C			F			

UNPACK THE CABINET

Unpack the cabinet and lift it as little as necessary to remove the wood slides after having unscrewed them.



LEVEL THE CABINETS

To level the cabinets, adjust side and rear middle feet using the appropriate key. Check levelness both crosswise and lengthwise using a spirit level.




COSTAN TECHNICAL DOCUMENTATION PRODUCT: KWI DOC. no. QSM000048E CHAP. No.9 CHAPTER: MULTIPLEXING AND FINISHING CABINETS	CHAPTER REVISION STATUS						SIGNED AS IN CONFORMITY WITH APPROVED ORIGINAL	PAGE: 3/7
	ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.		DATE of 1st ISSUE: 10.July.2003
	A			D				
	B			E				
	C			F			ISSUED BY MKT	

SECURE REAR PLINTHS

Fasten pre-assembled rear plinths onto the cabinets to be coupled using self-tapping screws as shown on the drawing.


IMPORTANT: do not forget to carry out this action, otherwise the cabinet will not perform properly.



WHEN LATERAL ENDS ARE NOT PROVIDED: couple the cabinets as described below.

APPLY SPONGE RUBBER

Apply sponge rubber onto one of the two cabinets to be coupled, as shown in the figure.




Apply it all along, on the bottom part and on the small plastic profile in contact with the honeycomb deflector.


COSTAN TECHNICAL DOCUMENTATION PRODUCT: KWI DOC. no. QSM000048E CHAP. No. 9 CHAPTER: MULTIPLEXING AND FINISHING CABINETS	CHAPTER REVISION STATUS						SIGNED AS IN CONFORMITY WITH APPROVED ORIGINAL	PAGE: 4/7
	ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.		DATE of 1st ISSUE: 10.July.2003
	A			D			ISSUED BY MKT	
	B			E				
C			F					

BRING THE CABINETS TOGETHER AND FASTEN THEM

Bring the cabinets alongside each other and check their levelness using a spirit level. Secure the cabinets down at the bottom using three screws HM6x40 as shown in the picture.




Fasten the cabinets to one another at the top using two screws M8x90 as shown in picture.



COSTAN TECHNICAL DOCUMENTATION PRODUCT: KWI DOC. no. QSM000048E CHAP. No.9 CHAPTER: MULTIPLEXING AND FINISHING CABINETS	CHAPTER REVISION STATUS						SIGNED AS IN CONFORMITY WITH APPROVED ORIGINAL	PAGE: 5/7
	ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.		DATE of 1st ISSUE: 10.July.2003
	A			D				
	B			E				
	C			F			ISSUED BY MKT	



WHEN LATERAL ENDS ARE PROVIDED: press the lower plinth in place as shown in the picture.

IMPORTANT: do not forget to carry out this action, otherwise the cabinet will not perform properly.





FOR CABINETS EITHER WITH OR WITHOUT LATERAL ENDS: complete installation as described below.

REMOVE THE STRINGER



Unscrew and remove the front stringer and relevant supports.



Remove side strengtheners.

COSTAN TECHNICAL DOCUMENTATION PRODUCT: KWI DOC. no. QSM000048E CHAP. No. 9 CHAPTER: MULTIPLEXING AND FINISHING CABINETS	CHAPTER REVISION STATUS						SIGNED AS IN CONFORMITY WITH APPROVED ORIGINAL PAGE: 6/7 DATE of 1st ISSUE: 10.July.2003 ISSUED BY MKT
	ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.	
	A			D			
	B			E			
	C			F			

PLACE BOTTOM STEEL COVERS

Install bottom steel covers as shown in the picture.





ANCHOR THE CABINET TO THE FLOOR

These cabinets must be anchored to the floor; after that, install foot covers and secure them using the slots provided to the purpose. Proceed as follows:



Place fastening plates and mark the position of the holes on the floor.



Drill holes Ø 14 on the floor.



Install foot covers and fasten them in the holes provided.

COSTAN TECHNICAL DOCUMENTATION PRODUCT: KWI DOC. no. QSM000048E CHAP. No.9 CHAPTER: MULTIPLEXING AND FINISHING CABINETS	CHAPTER REVISION STATUS						SIGNED AS IN CONFORMITY WITH APPROVED ORIGINAL	PAGE: 7/7
	ORD.	DATE	FORW. DOC.	ORD.	DATE	FORW. DOC.		DATE of 1st ISSUE: 10.July.2003
	A			D				
	B			E				
	C			F			ISSUED BY MKT	

Secure fastening plates onto the floor using the two screws previously removed from the stringer. Fasten the cabinet to the floor using rawlplugs M10 for concrete.



LOWER REAR PLINTHS

Slightly unscrew the bolts securing the rear plinths to the support, lower the plinths until they rest on the floor and then fasten the bolts back again.

IMPORTANT: do not forget to carry out this step, otherwise the cabinet will not be able to operate properly.

