
INDEX

A

- abnormal operations, centrifugal pumps, 2.376
- aboveground discharge pumps, 2.99
- abrasive wear, 5.16, 5.18
 - composite pumps, 5.50
 - packings, 2.192
 - particulates, 5.20
 - rotary pumps, 3.137
 - slurry pumps, 9.364
 - water supply systems, 9.9
- absolute viscosities, 8.32
- AC adjustable-voltage drives, 6.110–6.111
- AC electric motors, 6.3
- acceleration, electric motors, 6.23–6.24
- accelerators, solutions, 9.115
- accelerometers, 2.422
- accessories, fire protection systems, 9.70
- accumulators, 9.464
- accuracy in testing pumps, 13.8
- acid sulfite pulping process, 9.160
- acidic solutions, 9.114
- acoustic filters, displacement pumps, 3.68
- acoustic treatments, gas turbines, 6.93
- acoustic velocities, displacement pump piping systems, 3.64–3.65
- active magnetic bearings, 2.282
- actuators, control valves, 7.23, 7.26
- adhesive wear, 5.14–5.15
- adjustable blade propeller turbines, 6.79
- adjustable rigid couplings, 6.176
- adjustable vanes, centrifugal pumps, 2.367
- adjustable-frequency drives
 - frequency inverters, 6.118
 - solid state adjustable-frequency inverters, 6.119–6.120

- adjustable-speed belt drives, 6.167
 - applications, 6.173
 - control systems, 6.173
 - gear reduction, 6.169
 - input speed, 6.168
 - operations, 6.170
 - output torque, 6.172
 - ratings, 6.172
 - service factoring, 6.172
 - speed control, 6.169
 - V belts, 6.170
- aerated solutions, 9.114
- affinity laws
 - rotary pumps, 3.132
 - turbines, 6.84
- agricultural pumps
 - transfer systems, 9.441–9.442
 - water usage, 9.5
- air admission, centrifugal pumps, 2.367
- air chambers, waterhammer
 - prevention, 8.101–8.103
- air cleaners, engines, 6.69
- air conditioning chilled water
 - marine pumps, 9.236
- air conditioning pumps, 9.257
- air intake systems, engines, 6.68
- air leakage, stuffing boxes, 2.192
- air lift eductors, 4.47
- air motor starters, engines, 6.71
- air siphons, 4.47
- air ventilation, hot water
 - pumps, 9.254
- air-cooled eddy current couplings,
 - enclosures, 6.105
- air-separating tanks, 2.465
- airborne noise, 8.117–8.122
- aircraft fuel pumps, 9.409–9.411
 - altitude climb performance, 9.415–9.416
 - boost pumps, 9.412–9.414, 9.418
 - constant altitude
 - performance, 9.416
 - contaminated fuels, 9.429
 - gear stage cyclic durability, 9.428
 - gear stage volumetric
 - performance, 9.428
 - low lubricity fuels, 9.429
 - main fuel pump, 9.416–9.417, 9.420–9.427
 - motor speeds, 9.414
 - performance, 9.414
 - pressure rise, 9.414–9.415
 - types of fuel, 9.415
 - vapor lock, 9.419
- aircraft refueling cryogenic pumps, 9.401
- aircraft-derivative split shaft gas turbines, 6.91
- alignment
 - engines, 6.74
 - gear reducers, 6.160
 - mechanical performance impact, 2.412–2.417
 - pumps, 12.3–12.4, 12.7
- alignment issues, screw pumps, 3.120
- alkaline solution chemical pumps, 9.114, 9.117
- alkalinity, water supply systems, 9.9
- alloys, corrosion factors, 5.7
- alternators, multipump control systems, 7.7
- altitude climb performance, aircraft fuel pumps, 9.415–9.416
- amnifold pumps, piping, 10.29
- amplitude, vibration analysis, 2.419–2.424
- angular contact bearings, 2.151–2.152
- angular misalignment, 2.228
- annual inspections, 12.17
- annular siphons, 4.44
- antifriction bearings
 - power pumps, 3.34
 - vibration, 2.434
- AODPs (air-operated diaphragm pumps)
 - applications, 3.95
 - ball valves, 3.92
 - check valves, 3.93
 - flap valves, 3.92
 - limitations, 3.97
 - pumping dry powders, 3.97

- API Standard 682, 2.215
- applications
 - adjustable-speed belt drives, 6.173
 - canned motor pumps, 2.318
 - eddy current couplings, 6.106
 - eductors, 4.30
 - flexible couplings, 6.181–6.182
 - food/beverage pumps, 9.188
 - gas turbines, 6.94–6.96
 - hydraulic water pumps, 6.193
 - jet pumps, 4.20
 - rigid couplings, 6.176
- approach channels, intake
 - design, 10.46
- ARC valves (Automatic Recirculation Control), 2.444
- Archimedeian screw, 1.2
- area ratio, L/JL pumps, 4.12, 4.16
- artificial lift, oil well pumps, 9.377
- ash handling pumps, 9.111
- atmospheric gases, cryogenic pumps, 9.400
- Austenitic iron casings, 5.29
- Austenitic stainless steel
 - casings, 5.29
 - impellers, 5.27
 - stress corrosion cracking, 5.7
- automatic controls, mining pumps, 9.211
- automatic packings, 2.183
- auxiliary bearings. *See* catcher bearings.
- auxiliary circulating pumps, steam turbogenerators, 9.228
- auxiliary condensate pumps, steam turbogenerators, 9.228
- auxiliary services, standby pumps, 12.16
- auxiliary starters, engines, 6.71
- average daily demand, water supply systems, 9.5
- axial clearances, wearing rings, 2.121
- axial lengths, centrifugal pumps, 2.29
- axial magnet forces, sealless magnetic drive pumps, 2.304
- axial thrust, 2.401
 - axial-flow impellers, 2.127
 - boiler circulating pumps, 2.127
 - centrifugal pumps, 2.53–2.54
 - double-suction impellers, 2.124
 - high-energy pumps, recirculation response, 2.79
 - hydraulic balancing devices, 2.129
 - impellers, 2.124–2.125
 - multistage pumps, 2.128
 - overhung impellers, 2.126
 - radial impellers, 2.127
 - semiopen impellers, 2.127
 - single-stage pumps, 2.124
 - single-suction impellers, 2.126–2.128
 - vertical pumps, 2.171–2.172
- axial unbalances, 2.125
- axial unloading, ball bearings, 2.152
- axial-flow impellers, 2.113, 2.127
- axially split casings, 2.102
 - interstage passages, 2.108
 - throat bushings, 2.141
- axially split pumps, 2.99

B

- babbitted bearings, 2.149
- babbits, 2.273
- backflow
 - high-energy pump cavitation, 2.86
 - preventers, 2.143
- backup systems, magnetic bearings, 2.279
- backward curved blades, centrifugal pumps, 2.331
- balance
 - couplings, 6.182
 - seals, 2.200–2.201, 2.211
- balanced piston valves, duplex steam pumps, 3.44
- balancing drum/disk units, hydraulic balancing devices, 2.129–2.131

- ball bearings, 2.149
 - angular contact, 2.151
 - double-row angular contact, 2.152
 - electric motors, 6.17
 - lubrication, 2.153
 - sealed, 2.150
 - self-aligning, 2.151
 - single-row angular contact, 2.151
 - single-row deep-groove, 2.151
- ball thrust bearings, 2.150
- ball valves
 - AODPs, 3.92
 - control valves, 7.16
- ballast pumps, 9.234
- bar racks, head losses, 8.73
- barrier fluid, 2.216
- baseplates, 2.156
 - drain pockets, 2.156
 - vibration, 2.435
- beam pumping units, 9.386
- bearing cases, single-stage steam turbines, 6.41
- bearings, 2.149
 - ball bearings, 2.150
 - canned motor pumps, 2.316
 - environment control, 2.321
 - critical mass, 2.270–2.271
 - cross coupling, 2.267
 - defective, 2.406
 - electric motors, 6.17–6.18
 - gears, lubrication, 6.161
 - heat balancing, 2.263–2.266
 - hydrokinetic drives, 6.129
 - inboard, 2.149
 - line, 2.149
 - lubrication, 2.152
 - magnetic. *See* magnetic bearings.
 - outboard, 2.149
 - pedestal, 2.149
 - propulsion marine pumps, 9.219
 - rolling element, 2.149
 - rotor whirl, 2.266
 - sealless magnetic drive pumps, 2.308–2.310
 - self-aligning, 2.149
 - sewage systems, 9.42
 - slurry pumps, 9.357
 - spring and damping coefficients, 2.268
 - squeeze film effect, 2.252
 - stability, 2.270–2.273
 - stability analyses, 2.268
 - static radial load damage, 2.403
 - static thrust, 2.401
 - thrust, 2.149
 - vertical dry-pit pumps, 2.160
 - viscosity, 2.258
- bedplates, 2.155
 - composite pumps, 5.61
 - drain surfaces, 2.157
- below-ground discharge pumps, 2.99
- bends in pipes, resistance coefficients, 8.65
- BEP (Best Efficiency Point), 2.327, 2.437
- Bernoulli constant, 2.15
- BEs (operating Basis Earthquakes), seismic nuclear pumps, 9.304
- beverage pumps, 9.187–9.188
 - positive displacement, 9.190
 - rotodynamic, 9.189
 - seals, 9.193
 - types, 9.189–9.190, 9.193
- Bhp (brake horsepower), power pumps, 3.4
- bid requisitions. *See* RFQs.
- bidders lists, RFQs, 11.20–11.22
- bilge pumps, 9.232
- biologically-induced corrosion, 5.10
- black liquor, paper mill pumps, 9.163–9.164
- blades
 - centrifugal pumps, 2.33
 - determining number, 2.36–2.38
 - determining shape, 2.39–2.40
 - inlet, 2.34
 - outlet, 2.34–2.35
 - high-energy pumps, vane combinations, 2.76–2.77
- bleach liquors, paper mill pumps, 9.164
- bleaching pulp, 9.160

- blockages, centrifugal pumps, 2.61
- blow tanks, paper mill pumps, 9.163
- boiler circulating pumps, 2.127, 9.108–9.109
- boiler feed pumps
 - cavitation, 9.92, 9.94
 - constant speed control systems, 7.11–7.13
 - drivers, 9.90
 - efficiencies, 9.94–9.95
 - reduced flow operation, 9.90
 - steam power plants, 9.77
 - capacities, 9.78
 - load reduction, 9.79–9.81
 - NPSH, 9.78–9.79
 - working pressures, 9.87
- boiler injectors, 4.48
- boiler-feed water condensate, 5.35
- booster pumps
 - aircraft fuel systems, 9.412–9.414, 9.418
 - steam power plants, 9.84
 - water treatment plants, 9.19
- Boron injection recirculation pumps, PWR plants, 9.280
- bottom-suction pumps, 2.106
- boundary blockages, centrifugal pumps, 2.61
- boundary layer theory, fluid mechanics, 2.249
- Bourdon gages, measuring head, 13.35
- brake horsepower (bhp)
 - gas turbines, 6.96
 - steam pumps, 3.58
- branch-line pumping systems
 - closed loop, 8.83–8.84
 - flow control, 8.88
 - open-ended systems, 8.84, 8.86
 - total head, 8.90
- Brayton cycle, gas turbines, 6.89
- breakaway torque
 - centrifugal pumps, 2.360
 - power pumps, 3.8
 - sealless magnetic drive pumps, 2.303
- brine pumps, 9.259
- bronze
 - casings, 5.29
 - impellers, 5.26
 - wear rings, 5.31
- brushless DC motors, 6.10–6.12
- brushless synchronous motors, 6.7
- buffer fluids, 2.216
- building water pressure control systems, 7.14
- butterfly control valves, 7.16
- BWR plants (boiling water reactor), 9.279
 - closed cooling water pumps, 9.284
 - control rod drive pumps, 9.284
 - fuel pool cooling pumps, 9.285
 - high-pressure core spray pumps, 9.285
 - jet pumps, 9.283
 - low-pressure core spray pumps, 9.285
 - main coolant pumps, 9.287, 9.290
 - reactor core isolation cooling pumps, 9.285
 - reactor water cleanup pumps, 9.284
 - recirculation pumps, 9.283
 - RHR pumps, 9.285
 - standby liquid control systems, 9.285
- bypass control and regulation
 - centrifugal pumps, 2.367
 - condensate pumps, 9.102
 - displacement pumps, 3.78
- bypass flow, 2.439
- bypass orifices, 8.87
- bypass systems
 - controls, 2.450
 - fixed orifices, 2.448
 - low flow protection, 2.441–2.444
 - orifice issues, 2.448
 - PRVs, 2.448
 - pumps in parallel, 2.450
 - variable orifices, 2.448

C

- cage control valves, 7.16–7.17
- calculated wear factors, 5.31
- calibration, metering pumps, 9.317
- canned motor pumps, 2.315
 - applications, 2.318
 - bearings, 2.316
 - environment control, 2.321
 - diagnostics, 2.322
 - filter assembly, 2.318
 - flow path, 2.318
 - installing, 2.321
 - intakes, 10.26
 - internal clearances, 2.318
 - pressure temperature
 - profiles, 2.321
 - recirculation fluid, 2.321
 - rotors, 2.316–2.318
 - secondary containment, 2.318
 - stator liners, 2.318
 - stators, 2.315
 - thrust balance, 2.319–2.321
 - vertical condensate pumps, 9.97
- cantilever shaft pumps, 2.168
- capacities
 - drainage pumps, 9.48
 - hydrodynamic drives, 6.135
 - hydrokinetic drives, 6.134
 - hydroviscous drives, 6.136
 - irrigation pumps, 9.48
 - metering pumps, 9.317
 - paper mill pumps, 9.175
 - power pumps, 3.4
 - rotary pumps, 3.139–3.140
 - screw pumps, 3.115
 - vane pumps, 3.140
 - water supply systems, 9.6
 - well pumps, 9.22
- capacity planning
 - electronic pumps, 3.88
 - sewage pumps, 9.37
- carbon pumps, 5.53
- carbon slurry pumps, water
 - treatment plants, 9.17
- carbon steel shafts, 5.30
- carburizing gears, 6.150
- cargo marine pumps,
 - 9.237–9.238, 9.241
- casing cover rings, leakage
 - joints, 2.118
- casing housing, rotary pumps, 3.124
- casing rings
 - leakage joints, 2.118
 - restricting movement, 2.123
- casing sealing glands, single-stage
 - steam turbines, 6.41
- casing tongues, centrifugal pumps,
 - reducing size, 2.347
- casings, 2.102
 - feet location, 2.110
 - handholes, 2.107
 - hydrokinetic drives, 6.129
 - hydrostatic tests, 2.111
 - materials of construction,
 - 5.28–5.29
 - mechanical features, 2.107
 - multistage pumps, 2.107, 2.110
 - single-stage steam turbines, 6.41
 - slurry pumps, 9.357
- cast cylinders, power pumps, 3.22
- cast iron
 - casings, 5.28
 - flanges, 2.110
 - impellers, 5.27
 - wear rings, 5.32
- catcher bearings, 2.279, 2.284
- cavitation, 2.224, 2.248,
 - 2.397–2.398, 2.448
 - boiler feed pumps, 9.92–9.94
 - centrifugal pumps, 2.347,
 - 2.356–2.357
 - control valves, 7.23
 - high-energy pumps
 - backflow, 2.86
 - erosion effects, 2.71, 2.88
 - instabilities, 2.87
 - pressure pulsations, 2.87
 - LJL pumps, 4.11, 4.17
 - noise sources, 8.111–8.113
 - resistance, 5.13
 - rotary pumps, 3.135

- testing pumps, 13.10
- turbines, 6.83
- cavitation erosion, 5.11
- cavitation limited flow ratios, L_{JL}
 - pumps, 4.15, 4.19
- cellar drainers, volute pumps, 2.169
- centerline footings, 2.110
- centerline pump support, 2.157
- centipoises, 8.33
- centralized multi-pump priming systems, 2.459
- centrifugal pumps, 2.3, 2.21
 - abnormal operations, 2.376
 - adjustable vanes, 2.367
 - air admission, 2.367
 - aircraft fuel, 9.411
 - axial lengths, 2.29
 - blades, 2.33–2.34
 - determining number, 2.36–2.38
 - determining shape, 2.39–2.40
 - boundary blockages, 2.61
 - breakaway torque, 2.360
 - bypass orifices, 8.87
 - bypass regulation, 2.367
 - casing tongues, reducing size, 2.347
- cavitation, 2.347
 - reducing damage, 2.356
 - resistant materials, 2.357
- chemical, 9.120
- collectors, 2.41
- component efficiencies, 2.11–2.12
- defective bearings, 2.406
- designing, 2.27, 2.406
- diffusion assessments, 2.66
- discharge
 - recirculation, 2.370
 - throttling, 2.366
- drainage. *See* drainage pumps.
- drivers, torque characteristics, 2.359–2.360
- dynamic instability, 2.56
- efficiencies, 2.60–2.61, 2.329, 2.382–2.383
 - increasing impeller speed, 2.334
- electromagnetic effects, 2.27
- emulsions, 2.27
- energy transfer, 2.9
- entrained air, 2.358
- entrained gases, 2.26
- Euler's Pump Equation, 2.13
- exit radius, 2.30
- extended Bernoulli equation, 2.15
- first law of thermodynamics, 2.9
- flow rate, 2.327, 2.351
 - regulation, 2.365
- head, 2.328
- heat of compression, 2.11
- high specific speed, 2.364
- hubs, profiles, 2.31, 2.33, 2.62
- hydraulic efficiency, 2.334
- hydraulic geometry, 2.21
- impellers, 2.29
 - blades, 2.64
 - diffusion effects, 2.15
 - eyes, 2.29
 - inlets, 2.58–2.59
 - outlets, 2.59
 - reducing diameter, 2.338–2.339
 - reversed installation, 2.382
- incorrect driver rotation, 2.382
- inducers, 2.358
- inlets
 - blades, 2.34
 - velocity diagrams, 2.64
- internal static pressure
 - distribution, 2.16
- irrigation. *See* irrigation pumps.
- L_{JL} pump interaction, 4.19
- losses, 2.11
- low specific speed, 2.361–2.362
- marine cargo, 9.237
- mechanical issues
 - critical speed, 2.409
 - efficiency, 2.334
 - mechanical performance, 2.405–2.406
- medium specific speed, 2.364
- mixed-flow impellers, reducing diameter, 2.339
- moments of forces, 2.13
- Moody-Stauffer formula, 2.383

- NPSH, 2.16–2.17, 2.25,
2.349–2.351, 2.355
 - operating, 12.13–12.14
 - outlets
 - blades, 2.34–2.35
 - velocity diagrams, 2.64
 - overfiling vanes, 2.343
 - parallel operation, 2.367–2.368
 - performance, 2.24, 2.334
 - axial thrust, 2.53–2.54
 - backward-curved blades, 2.331
 - CFD, 2.51–2.52
 - characteristic curves, 2.18, 2.46
 - estimates, 2.69
 - forward-curved blades, 2.332
 - mechanical efficiency, 2.50
 - non-recirculating flows, 2.46
 - non-viscous flows, 2.329–2.330
 - radial blades, 2.332
 - stability, 2.56
 - viscous flow, 2.331
 - volumetric efficiency, 2.50
 - pipeline applications, 9.142
 - pitting, 2.347
 - power output, 2.329
 - primers, 2.359
 - Q3D analysis, 2.48
 - radial thrust, 2.372
 - recirculation, 2.369–2.370
 - recirculating flow, 2.19
 - return passages, 2.45
 - rotary pump comparisons, 3.130
 - rotative speed, 2.27
 - Rütschi formula, 2.384
 - scaling, 2.19
 - second law of
 - thermodynamics, 2.10
 - shrouds, profiles, 2.31–2.33, 2.62
 - similitude, 2.20
 - sizing, 2.28–2.29
 - effect on efficiency, 2.24
 - slurry effects, 2.26
 - speeds, rotor shape, 2.23
 - starting, 12.14
 - static instability, 2.56
 - static pressure
 - increases, 2.16
 - losses, 2.14
 - static stability, 2.56
 - stopping, 12.14
 - subscript designations, 2.8
 - suction nozzles, 2.58
 - suction recirculation, 2.370
 - suction throttling, 2.366
 - suction-specific speed, 2.352
 - temperature rise, 2.372
 - Thoma cavitation parameter, 2.352
 - total dynamic head, 2.10
 - transient operations, 2.379–2.381
 - transient power failures, 2.376
 - troubleshooting, 12.20–12.23
 - turbine applications, 2.385–2.387
 - underfiling vanes, 2.343
 - units, 2.327
 - vane tips
 - clearance, 2.337
 - reducing size, 2.342
 - vaned diffusers, 2.43–2.44
 - velocity diagrams, 2.13
 - velocity triangles, 2.19
 - vibration, 2.382
 - viscosity, 2.25
 - volumetric efficiency, 2.334
 - volute, 2.41–2.43, 2.67
 - wearing rings, clearance, 2.336
- centrifugal slurry pumps,
9.351–9.352, 9.358
- casings, 9.357
 - efficiencies, 9.360–9.361
 - hydraulic design, 9.353
 - impellers, 9.357
 - liners, 9.365
 - particle impact wear, 9.364
 - seals, 9.357
 - shells, 9.365
 - sliding abrasion wear, 9.364
 - solids effects, 9.360
 - wear, 9.353, 9.363–9.365
- centrifugal/displacement systems,
flow control, 3.78, 3.81
- ceramic pumps, 5.53
- CFD (computational fluid dynamics),
centrifugal pumps, 2.46,
2.51–2.52
- chamber design, seals, 2.220
- charging pumps, 9.280

- check valves
 - AODPs, 3.93
 - sealing liquids, 2.143
 - waterhammer, 8.98, 8.102
- chemical pulping, 9.160
- chemical pumps
 - alkaline solutions, 9.117
 - casting integrity, 9.121
 - chlorine, 9.117
 - corrosion, 9.118
 - gaskets, 9.121
 - hydrochloric acid, 9.117
 - maintenance, 9.122
 - materials of construction, 9.115–9.116, 9.121
 - nitric acid, 9.117
 - nonmetallic, 9.124
 - organic acids/compounds, 9.117–9.118
 - packings, 9.122
 - phosphoric acid, 9.117
 - pigments, 9.116
 - power end, 9.122
 - salt solutions, 9.118
 - sealless, 9.124
 - seals, 9.122–9.123
 - shafts, 9.123
 - sulfuric acid, 9.116
 - types, 9.120
 - weldments, 9.121
- chemical resistance, composite pumps, 5.51
- chemical transfer systems. *See* transfer systems.
- chilled water pumps, PWR plants, 9.283
- chlorine
 - chemical pumps, 9.117
 - composite pump applications, 5.54
 - corrosion, 5.38
 - paper mill pumps, 9.165
- chrome plating, shafts, 5.30
- Cipoletti weirs, 13.19, 13.22
- circuits, hot water pumps, 9.255
- city water cooling systems, engines, 6.66
- clamshell markings, 5.24
- classes of nuclear pumps, 9.294
- classification of pumps, 1.2–1.3
- clearances
 - centrifugal pumps, 2.336–2.337
 - magnetic bearing rotors, 2.282
 - wearing rings, 2.123–2.124
- clockwise rotation, 2.107
- closed cooling water pumps, BWR plants, 9.284
- closed cooling electric motors, 6.20
- closed couplings, sealless magnetic drive pumps, 2.305
- closed cycles, steam power plants, 9.75
- closed impellers, 2.115
- closed loop branch-line pumping systems, 8.83–8.84
- closed-cycle gas turbines, 6.90
- closed-loop controls, 7.3
- coagulant feed pumps, water treatment plants, 9.16
- coatings, 5.7, 5.44
- codes, fire protection systems, 9.60
- coefficient of friction
 - packings, 2.187
 - seals, 2.202
- cold alignment of pump and driver, 2.413
- collectors, centrifugal pumps, 2.41
- Colmonoy-wear rings, 5.32
- combined cycle gas turbines, 6.90
- combined displacement/centrifugal systems
 - flow control, 3.78
 - parallel operation, 3.81
 - suction boost, 3.81
- commercial purchase recommendations, 11.29
- commercial terms, RFQs, 11.9
- commercial water usage, 9.5
- complex slurry flows, 9.338–9.339
- component cooling water pumps, 9.280
- component efficiencies, centrifugal pumps, 2.11–2.12
- composite pumps
 - abrasives, 5.50
 - bedplates, 5.61
 - chemical resistance, 5.51

- chlorine applications, 5.54
- dye applications, 5.57
- ethylene uses, 5.57
- ferric chloride uses, 5.57
- industrial uses, 5.58
- insulation properties, 5.50
- lined housings, 5.53
- materials of construction, 5.60
- mechanical properties,
 - 5.49–5.50, 5.54
- operating temperatures, 5.50
- propylene uses, 5.57
- standards, 5.60
- sulfuric acid applications, 5.57
- thermoplastic, 5.51
- thermoset, 5.52
- UV exposure, 5.50
- compound pressure gages, 12.12
- compressible flow, jet pumps, 4.8
- compression packings,
 - 2.183–2.184, 2.187
- computer-based pump systems
 - design, 11.33
- computer-based purchase proposals,
 - 11.30–11.31
- concentrated sludge/scum pumps,
 - 9.34–9.35
- concentration cell corrosion,
 - chemical pumps, 9.118
- concentrations, solutions,
 - 9.113–9.114
- condensate injection water,
 - requirements, 2.241
- condensate pumps, 9.96
 - bypass control, 9.102
 - discharge throttling, 9.102
 - flow regulation, 9.100
 - marine plants, 9.220–9.223
 - seal cages, 9.99
- condenser circulating pumps, 9.104
 - performance, 9.105
 - system hydraulics, 9.108
- condenser exhausting pumps, 9.223
- conduction rings, sealless magnetic drive pumps, 2.298
- connecting rods, power pumps, 3.31
- Conrad-type bearings, 2.151
- consistency, paper stock, 9.166
- constant altitude performance,
 - aircraft fuel pumps, 9.416
- constant differential pressure
 - propulsion marine pumps, 9.220
- constant drain temperature-controlled injection flow control systems, 2.243
- constant pressure governors,
 - propulsion marine pumps, 9.219
- constant speed control systems, 7.9
- constant speed multipump
 - water pressure booster systems, 9.454
- constant-torque loads, eddy current couplings, 6.103
- constituents of solutions, 9.113
- construction refinery pumps,
 - 9.134, 9.137
- construction liquids transfer systems, 9.444
- contact load solids, 9.322
- contact secondary controls, wound-rotor induction motors, 6.116
- contacting liquid lubricated seals,
 - 2.197–2.199, 2.215
- contacting seals, operating envelope, 2.207
- containment shell, sealless magnetic drive pumps, 2.305
- containment spray pumps, PWR plants, 9.280
- contaminated fuels, aircraft fuel pumps, 9.429
- contamination, cylindrical bearings, 2.255
- continuous bypass systems, 2.441
- continuous coil packings, 2.193
- continuous-tooth herringbone gears, 6.146
- control panels, water pressure booster systems, 9.455
- control rod drive pumps, BWR plants, 9.284
- control systems, 7.2
 - adjustable-speed belt drives, 6.173
 - alternators, 7.7

- boiler feedwater constant speed, 7.11–7.13
- building water pressure, 7.14
- bypass systems, 2.450
- closed-loop controls, 7.3
- constant speed, 7.9
- eddy current couplings, 6.105
- gas turbines, 6.94
- liquid level sensors, 7.4
- on-off constant speed, 7.9
- on-off controls, 7.3
- open-loop controls, 7.3
- pressure sensors, 7.7
- proportional controls, 7.3
- sewage systems, 9.40
- steam turbines, 6.41
- system design, 11.4
- telemetry systems, 7.9
- transducers, 7.7
- transmitters, 7.7
- valve-throttling constant speed, 7.10
- valves, 7.14–7.15
- waterhammer prevention, 8.103–8.105
- control techniques for noise, 8.113
 - airborne noise, 8.117–8.122
 - controlling noise paths, 8.115–8.116
 - source modification, 8.113–8.114
- control valves, 7.15, 7.23
 - ball valves, 7.16
 - butterfly valves, 7.16
 - cage valves, 7.16–7.17
 - cavitation, 7.23
 - flow characteristics, 7.20–7.21
 - flow coefficient, 7.22
 - gain, 7.21
 - gate valves, 7.16
 - globe valves, 7.15
 - injection flow systems, 2.245
 - multiple orifices in series, 7.18
 - positioners, 7.26
 - pressure recovery, 7.23
 - rangeability, 7.21
- controlled valve closure, waterhammer, 8.100
- controllers
 - fire protection systems, 9.61
 - fluid couplings, 6.139
- controlling noise path, noise control, 8.115–8.116
- controls. *See* control systems.
- conventional generation, pumped storage, 9.268
- conventional sewage pumps, 9.29
- conventional split-shaft gas turbines, 6.90
- coolant flow, seals, 2.204–2.205
- cooling systems, engines, 6.62–6.66
- cooling tower systems, 9.257–9.258
 - engines, 6.68
 - intakes, 10.8
 - pump pits, 10.6
- cooling water intakes, 10.5
- copper oxide corrosion, 5.4
- corrective fatigue measures, 5.25
- corrective procedures for common problems, 2.404
- corrosion, 5.37
 - alloys, 5.7
 - cavitation erosion, 5.11
 - chemical pumps, 9.118
 - seals, 9.122
 - shafts, 9.123
 - copper oxide corrosion, 5.4
 - dealloying, 5.5
 - dezincification, 5.5
 - galvanic corrosion, 5.6–5.7
 - graphite corrosion, 5.4–5.5
 - hydrocarbons, 5.38
 - intergranular, 5.10
 - microbiologically-induced, 5.10
 - rotary pumps, 3.136
 - stress corrosion cracking, 5.7
- corrosion-assisted fatigue, 5.25
- cost estimates, pumped storage, 9.275
- counterbalance, oil well pumps, 9.386
- counterclockwise rotation, 2.107
- couplings
 - balance, 6.182
 - elastomer, 6.178–6.179
 - electric motors, 6.20

flexible, 6.176
flexible diaphragm, 6.178
gear units, 6.160
limited end float, 6.182
material flexible, 6.178
mechanically flexible, 6.176–6.177
metal disk, 6.178
rigid, 6.175–6.176
rubber jaw, 6.179
spring-grid, 6.180
vertical operations, 6.182
crack arrest lines, 5.24
cracking and fatigue, 5.22–5.23
crank pin bearings, power pumps, 3.33
cranking ratios, engines, 6.71
crankshafts, power pumps, 3.28–3.29
crevice corrosion, chemical pumps, 9.118
critical damping, seismic nuclear pumps, 9.302
critical mass
 bearings, 2.270
 journal bearings, 2.271
critical sigma, turbines, 6.83
critical speed
 centrifugal pumps, 2.409
 shafts, 2.132–2.133, 6.187
cross coupling, bearings or springs, 2.267
crossheads, power pumps, 3.32
crossways, power pumps, 3.32
crude oil pipeline service, gas turbines, 6.95
cryogenic liquids, 2.227
cryogenic pumps, 9.399
 atmospheric gases, 9.400
 LNG (liquefied natural gas), 9.403–9.405
 LPG (liquefied petroleum gas), 9.404–9.405
 refueling systems, 9.401
 ship-loading, 9.405
CTIO volume (closed-to-inlet-and-outlet), rotary pumps, 3.123
current meters, 13.26
Curtis stage steam turbines, 6.46

cushion valves, duplex steam pumps, 3.44
cycle time, sewage systems, 9.38
cyclone separators, 2.142
cylinders
 engines, 6.57
 power pumps, 3.22
 liners, 3.26
cylindrical bearings, 2.254
 performance plots, 2.259
 spring and damping coefficients, 2.268
 with axial grooves, 2.255

D

daily observation of pump operations, 12.16
dam wearing rings, 2.120
damping coefficients, 2.267
Darcy-Weisbach formula, 8.33
data sheets, RFQs, 11.11
datum, horizontal/vertical shaft pumps, 2.328
DC motors, 6.3, 6.8
 PM brushless, 6.10, 6.12
 SCR power supply drives, 6.123
 shunt-wound, 6.8
 SR brushless, 6.13
dealloying, 5.5
dealuminification, 5.6
debris removal, 10.14–10.16
deep well eductors, 4.38
deep well marine cargo pumps, 9.242–9.243
deep well turbine irrigation pumps, 9.46
defective bearings, 2.406
deflection, shafts, 2.134
deformation rates, 8.32
degrees of freedom, seismic nuclear pumps, 9.302
delivery, screw pumps, 3.101, 3.115

- demand profiles, water pressure
 - booster systems, 9.457–9.460
- deposition, partially stratified slurries, 9.332
- derating power pumps, 3.9
- design/analysis computer programs, 11.33–11.34
- designing intakes, 10.42
 - approach channel, 10.46
 - Froude scaling, 10.45
 - model scale, 10.46
 - model similitude, 10.44
 - screens, 10.47
- designing magnetic bearings, 2.285
- designing pumps, 10.47
 - centrifugal, 2.27
 - faults, 2.406
 - control systems, 11.4
 - flow distribution, 10.51
 - fluid characteristics, 11.2, 11.7
 - free surface vortices, 10.49
 - gas turbine temperatures, 6.91
 - intake loss coefficient, 10.50
 - nuclear pumps, 9.293–9.294
 - operating modes, 11.3
 - power, 3.21–3.22
 - prerotation, 10.50
 - pump type selection, 11.4, 11.7
 - subsurface vortices, 10.49
 - system head curves, 11.2–11.3
- designing slurry transport systems, 9.343
 - homogeneous slurries, 9.344–9.345
 - settling slurries, 9.345
- detailed dynamic analysis, seismic nuclear pumps, 9.308
- dezincification, 5.5
- diagnostics
 - canned motor pumps, 2.322
 - displacement pumps, 3.70–3.71
 - magnetic bearings, 2.291
 - vibration symptoms, 2.425, 2.430–2.431
- dial indicators
 - pump alignment, 12.4
 - pump installs, 2.418
- diaphragm couplings, 6.178
- diaphragm pumps
 - air-operated, 3.92–3.93
 - chemical, 9.121
 - hydraulically driven, 3.89–3.91
 - mechanically driven, 3.85–3.86
 - walking beams, 3.87
- diaphragms, 2.108
- diesel engines, 6.57
 - fire protection systems, 9.60
 - fuel systems, 6.62
- diesel freshwater cooling pumps, 9.226
- diesel generators
 - fuel oil pumps, 9.229
 - jacket water circulating pumps, 9.229
 - lubricating oil pumps, 9.229
- diesel marine pumps, 9.226
- diesel seawater cooling pumps, 9.226
- diesel transfer systems, 9.443
- differential mercury gages, measuring head, 13.34
- differential pressure
 - rotary pumps, 3.145
 - water supply systems, 9.12
- differential pressure meters, 13.15
- differential pressure-controlled injection flow systems, 2.242
- differential temperature-controlled injection flow systems, 2.242
- diffusers
 - centrifugal pumps, 2.43–2.44
 - pumps, 2.97, 2.100, 2.163
- diffusion effects, centrifugal impellers, 2.15, 2.66
- digester circulating paper mill pumps, 9.181
- dilatant liquids, 8.33, 9.188
- dilute sludge pumps, 9.34
- direct acting steam pumps, 3.40, 3.53
- direct connected steam turbines, 6.39
- direct-acting pumps, throttle control, 3.75
- direct-connected exciters, synchronous motors, 6.7
- disc diaphragm pumps, 3.89

- discharge
 - drainage/irrigation systems, 9.48–9.51
 - mainfolds, power pumps, 3.27
 - pressure, 2.439
 - steam power plants, 9.85
 - recirculation, 2.370, 2.398
 - testing pumps, 13.14
- discharge head, 13.4
- discharge nozzles, 2.106
- discharge piping, 12.9
 - float mounted mining pumps, 9.202–9.203
 - profiles, waterhammer, 8.93
 - water supply systems, 9.9
- discharge stroke, reciprocating pumps, 3.38
- discharge throttling
 - centrifugal pumps, 2.366
 - condensate pumps, 9.102
- discharge valves, power pumps, 3.27
- disks, hydroviscous drives, 6.134
- displacement
 - power pumps, 3.4
 - rotary pumps, 3.138, 3.141–3.143
 - steam pumps, 3.53
- displacement pumps, 1.3
 - acoustic filters, 3.68
 - bypass control, 3.78
 - diagnostics, 3.70–3.71
 - flow control, 3.75
 - operating costs, 3.78
 - pumps in series, 3.83
 - gas-charged dampeners, 3.69
 - in-line gas dampeners, 3.69
 - inadequate NPSH, 3.63
 - isentropic bulk moduli, 3.66–3.67
 - isothermal bulk moduli, 3.67
 - piping system
 - acoustic velocities, 3.64–3.65
 - pulsation responses, 3.64
 - vibration, 3.70
 - positive pulsations, 3.64
 - pulsation control, 3.67
 - shaft failures, 3.73
 - side branch accumulators, 3.69
 - speed changer controls, 3.76
 - suction valve unloading, 3.76–3.77
 - thermal problems, 3.72
 - troubleshooting, 3.63
- displacement/centrifugal systems,
 - flow control, 3.78, 3.81
- dissolved air issues, screw pumps, 3.113
- dissolved gases, rotary pumps, 3.134
- distance shaft sleeves, 2.136
- distillation marine pumps, 9.234
- distribution pumps, water treatment plants, 9.19
- domestic water usage, 9.5
- double acting reciprocating pumps, 3.38
- double helical gears, 6.146
- double seals, 2.208
- double volute pumps, 2.101
- double-end screw pumps, 3.104
- double-ring pumps, 2.119
- double-row angular contact ball bearings, 2.152
- double-suction impellers, 2.113, 2.124
- doughnut type pumps, 2.110
- doweling, pumps/drivers, 12.8
- drain lines, injection flow systems, 2.245
- drain pockets, baseplates, 2.156
- drainage pumps, 9.45
 - capacities, 9.48
 - discharge systems, 9.49–9.51
 - multiple pumps, 9.47
 - pool-to-pool head, 9.48
 - propeller, 9.53
 - total suction head, 9.52
 - total suction lift, 9.52
 - turbines, 9.52
 - valves, 9.48
 - volute, 9.52
- drains, piping systems, 12.11
- dredge pumps, 9.321, 9.351
- drive shaft systems, 6.182–6.183
- drive-end pumps, 2.107
- driver speed controls, displacement pumps, 3.76
- drivers
 - boiler feed pumps, 9.90

- centrifugal pumps, torque
 - characteristics, 2.359–2.360
- doweling, 12.8
- fire protection systems, 9.60
- mining pumps, 9.212
- refinery pumps, 9.142
- selecting, 11.8
- sewage systems, 9.39
- steam power plants, 9.85–9.87
- water supply systems, 9.10
- dry pit pumps, 2.99
 - multipump systems, 10.11–10.12
 - sewage pumps, 9.29
- dry running, sealless magnetic
 - drive pumps, 2.310
- dry vacuum pumps, 2.458
- dual containment shells, sealless
 - magnetic drive pumps, 2.308
- dual strainers, injection flow
 - systems, 2.245
- dual-pressurized gas lubricated
 - seals, 2.223–2.224
- ductile overload zones, 5.24
- duplex stainless steel
 - casings, 5.29
 - impellers, 5.28
- duplex steam pumps, 3.40–3.44
- duty cycles, engines, 6.59
- dye applications, composite
 - pumps, 5.57
- dynamic instability, centrifugal
 - pumps, 2.56
- dynamic pumps, 1.3
- dynamic viscosities, 8.32

E

- ebullition cooling systems,
 - engines, 6.67
- eccentric straps, power pumps, 3.31
- ECCS (emergency core cooling
 - system), PWR plants, 9.280
- economic evaluation, pumped
 - storage, 9.272
- eddies, 10.24
- eddy current couplings, 6.99
 - air-cooled, 6.105
 - applications, 6.106
 - constant-torque loads, 6.103
 - control systems, 6.105
 - enclosures, 6.105
 - horizontal, 6.103
 - ratings, 6.106
 - sizes, 6.106
 - slip speed, 6.100–6.101
 - variable-torque loads, 6.101
 - vertical, 6.104
 - water-cooled, 6.105
 - weather-protected, 6.105
- eddy current losses, sealless
 - magnetic drive pumps,
 - 2.306–2.307
- eductors, 4.24–4.25
 - air lift, 4.47
 - applications, 4.30
 - deep well, 4.38
 - general purpose, 4.30–4.32
 - mixing, 4.33
 - multinozzle, 4.38
 - NPSH, 4.27
 - performance, 4.30
 - priming, 4.41
 - sand/mud, 4.36
 - solids handling, 4.37
 - spindle proportioning, 4.34
- efficiencies
 - boiler feed pumps, 9.94–9.95
 - centrifugal pumps, 2.60–2.61,
 - 2.329, 2.334, 2.382–2.383
 - eddy current couplings, 6.101
 - electric motors, 6.4, 6.25
 - fluid couplings, 6.139
 - gear reducers, 6.153
 - paper mill pumps, 9.180–9.181
 - power transmission systems, 6.197
 - single-stage steam turbines, 6.47
 - slurry pumps, 9.360–9.361
 - steam power plants, 9.94–9.95
 - steam turbines, 6.48
 - units of measure, 13.7
- efficiency formula, 13.37
- ejectors, 2.458, 4.23
- elastomer couplings, 6.178–6.179

- elastomeric vane pumps. *See* flexible liner pumps.
- electric drives, 6.109–6.111
- electric motors
 - AC, 6.3
 - acceleration, 6.23–6.24
 - adjustable-frequency drives, 6.118
 - ball bearings, 6.17
 - bearings, 6.17
 - brushless synchronous motors, 6.7
 - DC, 6.3, 6.8
 - with SCR power supply drives, 6.123
 - drainage/irrigation, 9.53
 - efficiencies, 6.4, 6.25
 - enclosures, 6.15–6.16
 - fire protection systems, 9.60
 - flanged, 6.20
 - flux vector drives, 6.121
 - frequency variations, 6.22
 - horizontal wound-rotor induction, 6.114
 - hydrodynamic bearings, 6.18
 - insulation, 6.18–6.19
 - Kraemer drives, 6.122
 - magnetic starters, 6.27
 - manual starters, 6.27
 - mining pumps, 9.212
 - motion equations, 6.23
 - performance, 6.21
 - power factors, 6.26
 - pull-in torque, 6.25
 - pump coupling methods, 6.20
 - rolling element bearings, 6.18
 - safe temperature, 6.25
 - service factor ratings, 6.25
 - sleeve bearings, 6.18
 - speeds, 6.23
 - squirrel-cage induction motors, 6.4–6.5
 - starters, 6.27–6.28
 - submersible centrifugal oil well pumps, 9.393
 - submersible pumps, 9.246
 - synchronous motors, 6.6
 - TEWAC (totally enclosed water-to-air-cooled), 6.113
 - voltage ratings, 6.22
 - wound-rotor induction, 6.111–6.113
 - wound-rotor induction motors, 6.5–6.6
- electric starters for engines, 6.71
- electromagnetic effects, centrifugal pumps, 2.27
- electronic pumps, 3.87–3.88
- elevation head
 - centrifugal pumps, 2.10
 - pumping systems, 8.6
- elliptical bearings, 2.255
- emergency pumps, fire protection systems, 9.58
- emissions, gas turbines, 6.93
- emulsions, centrifugal pumps, 2.27
- enclosures
 - eddy current couplings, 6.105
 - electric motors, 6.15–6.16
- end plates, rotary pumps, 3.124
- end suction pumps, 2.102, 9.58
- energy conversion, steam turbines, 6.46
- energy evaluations, RFQs, 11.11
- energy gradients, pumping systems, 8.12
- energy level measurements, high-energy pumps, 2.71
- energy transfer, centrifugal pumps, 2.9
- engineering guidelines, fire protection systems, 9.62
- engines
 - air cleaners, 6.69
 - air intake systems, 6.68
 - alignment, 6.74
 - cooling systems, 6.62–6.68
 - cylinders, 6.57
 - drainage/irrigation, 9.53
 - duty cycles, 6.59
 - exhaust systems, 6.60, 6.70
 - foundations, 6.73
 - fuel systems, 6.61
 - heat exchangers, 6.66
 - ignition systems, 6.72
 - maintenance, 6.60

- mufflers, 6.70
- pistons, velocities, 6.59
- pollutants, 6.60
- power ratings, 6.57–6.58
- radiators, 6.64–6.65
- speed ratings, 6.60
- starters, 6.70–6.71
- vibration isolation, 6.74
- entrained air
 - centrifugal pumps, 2.358
 - rotary pumps, 3.134
 - screw pumps, 3.113
- entrained gases, centrifugal pumps, 2.26
- environmental issues
 - canned pump bearings, 2.321
 - environmentally-assisted fatigue, 5.22
 - gas turbines, 6.91
- epicyclic gear units, 6.159
- equations
 - liquid jet pumps, 4.7
 - LJL pumps, 4.9–4.10
- equipment inspection, 12.16–12.17
- equivalent fluid slurries, 9.322
 - hydraulic gradient, 9.324
 - pressure losses, 9.323
- equivalent head, pumping systems, 8.5
- erosion, 5.17–5.20
 - cavitation, high-energy pumps, 2.88
 - corrosion, 5.37
 - chemical pumps, 9.119
 - high purity water, 5.35
 - saline water, 5.36
- ethylene uses, composite pumps, 5.57
- Euler's Pump Equation, 2.13
- evaluating bids, 11.24
- exhaust gas boiler marine pumps, 9.231
- exhaust systems, engines, 6.60, 6.70
- exit radius, centrifugal pumps, 2.30
- exit width, centrifugal pumps, 2.30
- expansion joints, piping systems, 12.10

- explosion-proof enclosures, electric motors, 6.16
- exposure limits for noise, 8.124
- extended Bernoulli equation, 2.15
- extended-shaft pumps, power losses, 6.197
- external gear pumps, 3.127
- eye of impeller. *See* impeller eye.

F

- face pressure, seals, 2.201
- face-and-rim alignment, 12.5
- failures
 - power, 12.16
 - pump motor, waterhammer, 8.95–8.96
- fast fracture zones, 5.24
- fatigue, 5.22, 5.24
 - corrective measures, 5.25
 - failures, 2.401
 - reducing via mechanical notches, 5.23
- feedback systems, magnetic bearings, 2.278–2.279
- feet, casings, 2.110
- ferric chloride uses, composite pumps, 5.57
- fertilizer pumps, 9.321, 9.442
- fiber characteristics of paper stock, 9.166
- field maintenance, 12.2
- field tests, 13.2
- filters
 - canned motor pump assemblies, 2.318
 - gas turbines, inlets, 6.94
 - injection flow systems, 2.245
- finite element method analysis, seismic nuclear pumps, 9.303
- fire marine pumps, 9.231–9.232
- fire protection systems, 9.57
 - accessories, 9.70
 - codes and regulations, 9.60
 - controllers, 9.61

- drivers, 9.60
- emergency pumps, 9.58
- engineering guidelines, 9.62
- first intervention pumps, 9.58
- jockey pumps, 9.58
- recommended design features, 9.63–9.68
- firm capacity, raw sewage pumps, 9.29
- first intervention pumps, fire protection systems, 9.58
- first law of thermodynamics, 2.9
- fish, preventing from entering intake, 10.18–10.21
- fittings, frictional losses, 8.54
- fixed blade propeller turbines, 6.79
- fixed displacement hydraulic pumps, fixed water flow, 6.195
- fixed orifices, bypass systems, 2.448
- fixed system heads, pumping systems, 8.13
- fixed water flow, hydraulic pumps, 6.195
- flame hardening gears, 6.150
- flanges, 2.110
 - motors, 6.20
 - rigid couplings, 6.175
- flap valves, AODPs, 3.92
- flash distilling marine pumps, 9.234
- flashing, 2.448, 8.113
- flat characteristic, 2.334
- flat side valves, duplex steam pumps, 3.43
- flat wearing rings, 2.119
- flexible couplings, 6.176, 6.181–6.182
- flexible diaphragm couplings, 6.178
- flexible drive shafts, 6.186
- flexible graphite packing, 2.188
- flexible impeller food/beverage pumps, 9.190
- flexible liner pumps, 3.126
- flexible pipe, bedplate issues, 2.157
- flexible shafts, 2.133
- float mounted mining pumps, 9.201–9.203
- floating packings, 2.183
- floating rings, segmented throttle bushings, 2.240–2.241
- floating shafts, 6.184
- flooded suction, units of measure, 13.3
- floor acceleration, seismic nuclear pumps, 9.303
- flow characteristics
 - complex slurries, 9.338–9.339
 - control valves, 7.20–7.21
 - fully stratified slurries, 9.335
 - inclined slurries, 9.342
 - slurries, 9.322–9.323
 - vertical slurries, 9.341
- flow coefficients, valves, 7.22, 8.56–8.58, 8.62–8.63
- flow control, 2.437
 - automatic bypass systems, 2.441–2.443
 - branch-line pumping systems, 8.88
 - combined displacement/centrifugal systems, 3.78, 3.81
 - continuous bypass systems, 2.441
 - control loop bypass systems, 2.442
 - design factors, 2.439
 - displacement pumps, 3.75, 3.78 in series, 3.83
 - sewage systems, 9.41
- flow curves, rotary pumps, 3.131
- flow cutoff, LJGL pumps, 4.8
- flow distribution, scale models, 10.51
- flow metering devices, 12.12
- flow nozzles, testing pumps, 13.16
- flow paths
 - canned motor pumps, 2.318
 - sealless magnetic drive pumps, 2.311
- flow rates, 2.327
 - centrifugal pumps, 2.351, 2.365
 - reducing to prevent cavitation, LJL pumps, 4.17
 - temperature variations, 8.77
- flow regimes, jet pumps, 4.5–4.6
- flow regulation, condensate pumps, 9.100
- flow requirements, 2.438
- flow units, hydraulic turbines, 6.80
- fluid characteristics, pump selection, 11.7

- fluid couplings, 6.127
 - controllers, 6.139
 - efficiencies, 6.139
 - hydrodynamic drives, 6.132
 - hydrokinetic drives, 6.127–6.130
 - hydrostatic drives, 6.134
 - hydroviscous drives, 6.133–6.134
 - leakoff, 6.131
 - output speed regulation, 6.136
 - scoop-trimming, 6.130–6.131
 - turndown, 6.136
- fluid drives. *See* hydrokinetic drives.
- fluid dynamics, 2.9
- fluid film bearing cavitation, 2.248
- fluid friction power losses, rotary pumps, 3.145
- fluid issues, rotary pumps, 3.135
- fluid lubricity, rotary pumps, 3.135
- fluid mechanics, boundary layer theory, 2.249
- fluid vapor pressure, screw pumps, 3.110
- fluid/structure interactions, high-energy pumps, 2.74
- flumes, 13.23–13.24
- fluoride pumps, water treatment plants, 9.17
- flush gland plates, 2.220
- flush-and-quench gland plates, 2.220
- flushes, 2.204
- flushing solids pumps, 9.374
- flux vector drives, 6.121
- flywheel effect, waterhammer, 8.94
- food pumps, 9.187–9.188
 - positive displacement, 9.190
 - rotodynamic, 9.189
 - seals, 9.193
 - types, 9.189–9.190, 9.193
- foot valves, 2.456
- forged cylinders, power pumps, 3.23
- forward curved blades, centrifugal pumps, 2.332
- foul condensate, paper mill pumps, 9.166
- foundations, 12.3, 12.8, 2.155
 - engines, 6.73
 - gear reducers, 6.160
 - grouting, 12.8
 - screw pumps, 3.120
 - vertical pumps, 2.175
- frames, power pumps, 3.28
- Francis turbines
 - power shafts, 6.80
 - runners, 6.79
 - sizes, 6.83
- Francis-vane impellers, 2.113
- Francis-vane radial impellers, 2.113
- free surface vortices, 10.39, 10.49
- freeness, paper stock, 9.166
- frequencies
 - defective bearings, 2.406
 - impeller vane passage, 2.406
 - variations, electric motors, 6.22
 - vibration analysis, 2.419–2.424
- frequency inverters, PWM, 6.118
- freshwater cooling marine pumps, 9.230
- freshwater drain collecting tank pumps, 9.223
- fretting, 5.15
- friction, 8.32
- frictional losses
 - head losses, pumping systems, 8.34, 8.39–8.48
 - journal bearings, 2.253
 - LJL pump coefficients, 4.12
 - paper mill piping, 9.170–9.173, 9.177–9.179
 - water supply systems, 9.12
- Froude scaling of intakes, 10.45
- fuel oil pumps, 9.225–9.229, 9.256
- fuel pool cooling pumps, BWR plants, 9.285
- fuel systems, engines, 6.61
- fuels
 - aircraft fuel pumps, 9.415
 - gas turbines, 6.91
- full-convolution bellows seals, 2.214
- fully stratified slurries, 9.323, 9.335
- fundamental shaft frequency
 - pressure pulsations, 8.105
- fungicide transfer systems, 9.442
- FVNR starters (full voltage nonreversing), wound-rotor induction motors, 6.111

G

- gain, control valves, 7.21
- galling resistance of alloys, 5.30–5.34
- galvanic corrosion, 5.6–5.7, 9.119
- gaps, sealless magnetic drive pumps, 2.299
- gas turbines, 6.89
 - acoustic treatments, 6.93
 - brake horsepower, 6.96
 - Brayton cycle, 6.89
 - closed-cycle, 6.90
 - combined cycle, 6.90
 - control systems, 6.94
 - design temperatures, 6.91
 - emissions, 6.93
 - environmental issues, 6.91
 - filtration inlets, 6.94
 - fuel oil marine pumps, 9.227
 - fuel sources, 6.91
 - Joule cycle, 6.89
 - lubricating oil marine pumps, 9.227
 - lubrication, 6.94
 - noise, 6.93
 - open-cycle, 6.90
 - pipeline service, 6.95
 - pump applications, 6.94–6.96
 - rolling media filters, 6.94
 - single-shaft, 6.90
 - split shaft, 6.90
 - split-shaft conventional, 6.90
 - standards, 6.91
 - starting systems, 6.94
- gas-charged dampeners, displacement pumps, 3.69
- gaseous fuel systems, engines, 6.61
- gaskets, chemical pumps, 9.121
- gasoline transfer systems, 6.61, 9.443
- gate control valves, 7.16
- gear food/beverage pumps, 9.190
- gear pumps, 3.123, 3.127
- gear reducers, 6.152
 - adjustable-speed belt drives, 6.169
 - alignment, 6.160
 - efficiencies, 6.153
 - foundations, 6.160
 - leveling, 6.160
 - power ranges, 6.153
 - ratios, 6.153
 - speeds, 6.153
- geared steam turbines, 6.39
- gears
 - carburizing, 6.150
 - continuous-tooth herringbone gears, 6.146
 - couplings, 6.160
 - double helical gears, 6.146
 - epicyclic gear units, 6.159
 - flame hardening, 6.150
 - grease lubrication, 6.161
 - helical gears, 6.144–6.146
 - hypoid–bevel gears, 6.148
 - induction hardening, 6.149
 - installing, 6.159
 - lubrication, 6.160–6.161
 - minimizing
 - dimensions, 6.150
 - noise, 6.151
 - nitriding, 6.149
 - oil seals, 6.161
 - packaged gear drives, 6.152
 - parallel-shaft gears, 6.144
 - pump drives, 6.143
 - spiral-bevel gears, 6.147
 - spur gears, 6.144
 - straight-bevel gears, 6.147
 - through hardening, 6.149
 - troubleshooting, 6.161–6.164
 - worm gears, 6.148
 - zero-bevel gears, 6.147
- general corrosion, 5.4
- general purpose eductors, 4.30–4.32
- generator motors, pumped storage, 9.262
- geothermal water, salinity, 5.37
- gerotor pumps, 3.129
- gland plates
 - seals, 2.220
 - stuffing boxes, 2.186
- globe control valves, 7.15

governors
 pumped storage systems, 9.270
 single-stage steam turbines, 6.41
 steam turbines, 6.41
 graphite corrosion, 5.4–5.5
 grease
 ball bearing lubricant, 2.153
 gear units, 6.161
 oil lubricant, 2.152
 grease seals, sewage pumps, 2.144
 green liquor, paper mill
 pumps, 9.164
 ground acceleration, seismic nuclear
 pumps, 9.303
 groundwater
 salinity, 5.37
 pumps, 9.3–9.4
 well pumps, 9.21
 groundwood pulp, 9.159
 grouting, 12.8
 guarded enclosures, electric
 motors, 6.15
 GVFs (gas void fractions), screw
 pumps, 3.118

H

half-convolution bellows seals, 2.214
 handholes, casings, 2.107
 Hazen-Williams formula, 8.34–8.36
 head
 area meters, 13.18
 capacity curves
 sewage systems, 9.39
 steam power plants, 9.85
 centrifugal pumps, 2.328
 measuring, 13.27–13.28
 Bourdon gages, 13.35
 differential mercury gages, 13.34
 mercury gages, 13.34
 water gages, 13.33
 pool-to-pool, drainage/irrigation
 pumps, 9.48

pumping systems, 8.5
 units of measure, 13.3
 head losses, 8.64
 bar racks, 8.73
 metering systems, 8.66
 perforated plates, 8.73
 pumping systems, 8.32
 pipe frictional losses, 8.34,
 8.39, 8.42–8.48
 screens, 8.70
 throttling orifices, 8.77
 wire mesh screens, 8.71
 heat balancing, bearings,
 2.263–2.266
 heat exchangers, engines, 6.66
 heat of compression, centrifugal
 pumps, 2.11
 heat recovery distillation
 pumps, 9.235
 heat removal, seals, 2.203
 heater drain pumps, 9.103–9.104
 heating jackets, rotary pumps, 3.125
 helical gears, 6.144–6.146
 herbicide transfer systems, 9.442
 heteropolar magnetic bearings,
 2.282, 2.285–2.288
 high head systems,
 waterhammer, 8.93
 high purity water, erosion
 corrosion, 5.35
 high specific speed centrifugal
 pumps, 2.364
 high viscosity uses, rotary
 pumps, 3.132
 high-energy pumps, 2.71–2.72
 blade-vane combinations,
 2.76–2.77
 cavitation
 backflow, 2.86
 erosion, 2.71, 2.88
 instabilities, 2.87
 pressure pulsations, 2.87
 energy level measurements, 2.71
 fluid/structure interactions, 2.74
 high-energy domains, 2.72
 low energy domains, 2.74

- MCSF (minimum continuous stable flow), 2.80, 2.84
- NPSH life prediction, 2.90
- pressure pulsations, 2.71
- recirculation, 2.78–2.79
- suction specific speed, 2.84–2.85
- torque per unit volume, 2.72–2.73
- high-head mining pumps, 9.208
- high-pressure core spray pumps, BWR plants, 9.285
- high-service pumps, water treatment plants, 9.19
- homogeneous slurries, transport systems, 9.344–9.345
- homopolar magnetic bearings, 2.282, 2.289–2.290
- horizontal condensate pumps, 9.96
- horizontal eddy current couplings, 6.103
- horizontal shaft pumps, standard datum, 2.328
- horizontal shafts pumps, 2.99
- turbines, 6.80
- horizontal wound-rotor induction motors, 6.114
- horizontally split casings, 2.102
- hot alignment of pump and driver, 2.414
- hot water pumps, 9.253
 - air ventilation, 9.254
 - circulation marine pumps, 9.236
 - types, 9.254–9.255
- housings
 - composite pumps, 5.53
 - hydrokinetic drives, 6.128
 - hydroviscous drives, 6.133
- hubs
 - centrifugal pumps, profiles, 2.31–2.33, 2.62
 - impellers, 2.118
- hybrid bearings, 2.257
- hydraulic balancing devices, 2.129, 2.131
 - balancing disks, 2.130
 - balancing drums, 2.129
 - predetermined thrust direction, 2.130
- hydraulic conditions, mining pumps, 9.207–9.208
- hydraulic couplings. *See* hydrokinetic drives.
- hydraulic design, slurry pumps, 9.353
- hydraulic efficiency, centrifugal pumps, 2.334
- hydraulic geometry, centrifugal pumps, 2.21
- hydraulic gradient
 - equivalent fluid slurries, 9.324
 - non-Newtonian flows, 9.325
 - non-Newtonian slurries, 9.325
- open channels, 8.41
- pumping systems, 8.12
- hydraulic horsepower, rotary pumps, 3.145
- hydraulic instabilities, 2.438
- hydraulic presses, 9.463
 - operating pressures, 9.466
- reciprocating pumps, 9.464–9.465
- hydraulic pumps, power
 - transmission systems, 6.191–6.192
- hydraulic starters, engines, 6.71
- hydraulic submersible centrifugal oil well pumps, 9.395–9.396
- hydraulic system marine pumps, 9.231
- hydraulic transients, pumped storage, 9.263–9.264
- hydraulic turbines, 6.77–6.79
 - cavitation, 6.83
 - flow units, 6.80
 - power shafts, 6.80
 - runners, 6.82
 - torque, 6.86
- hydraulic water pumps
 - applications, 6.193
 - efficiency, 6.197
 - fixed water flow, 6.195

- performance curves, 6.197
- variable water flow, 6.196
- hydraulic-motor-driven submersible pumps, 9.246
- hydraulically actuated diaphragm metering pumps, 9.315
- hydraulically actuated piston metering pumps, 9.315
- hydraulically driven diaphragm pumps, 3.89, 3.91
- hydraulics, 2.9
- hydrocarbons, corrosion, 5.38
- hydrochloric acid chemical pumps, 9.117
- hydrodynamic bearings, 2.135
 - canned motor pumps, 2.317
 - electric motors, 6.18
- hydrodynamic drives, 6.132
 - capacitance, 6.135
 - response speeds, 6.138
- hydrogen embrittlement, 5.9
- hydrokinetic drives, 6.127–6.128
 - bearings, 6.129
 - capacitance, 6.134
 - casings, 6.129
 - housing, 6.128
 - manifolds, 6.130
 - oil coolers, 6.129
 - oil pumps, 6.129
 - response speeds, 6.136
 - rotors, 6.129
 - scoop tubes, 6.129
 - shafts, 6.129
- hydrostatic drives, 6.134
- hydrostatic tests, 2.111
- hydroviscous drives
 - capacitance, 6.136
 - disks, 6.134
 - housing, 6.133
 - oil coolers, 6.134
 - oil pumps, 6.134
 - pistons, 6.134
 - response speeds, 6.138
 - rotors, 6.134
- hypoid-bevel gears, 6.148
- IGBTs (insulated gate bipolar transistors), electric drives, 6.109
- ignition systems, engines, 6.72
- imbalance loads, magnetic bearings, 2.282
- impeller rings, 2.119
 - radial pins, 2.123
 - restricting movement, 2.123
- impellers, 2.97, 2.114
 - axial flow, 2.113
 - axial thrust, 2.124–2.125
 - blades, centrifugal pumps, 2.64
 - centrifugal pumps, 2.29
 - diffusion effects, 2.15
 - increasing speed, 2.334
 - reducing diameter, 2.338–2.339
 - reversed installation, 2.382
 - closed, 2.115
 - double-suction, 2.113
 - eyes, centrifugal pumps, 2.29
 - Francis-vane, 2.113
 - Francis-vane radial, 2.113
 - hubs, 2.118
 - hydraulic unbalance, 2.433
 - inlets, centrifugal pumps, 2.58–2.59
 - inspection ports, 2.120
 - leakage joints, 2.118
 - materials of construction, 5.26–5.27
 - mixed-flow, 2.113
 - open, 2.115
 - opposed, 2.128
 - optimum diameter, 1.5
 - outlets, centrifugal pumps, 2.59
 - overhung, 2.113, 2.118
 - pump-out vanes, 2.115
 - radial vane, 2.113
 - recessed, 2.168
 - semiopen, 2.115
 - single-suction, 2.113

- slurry pumps, 9.357
- straight-vane radial, 2.113
- suction eye, 2.118
- unbalanced, 2.432
- vanes, frequency pressure pulsations, 8.106
- vertical turbine pumps, 2.165
- wearing rings, 2.118
- impulse loads, oil well pumps, 9.383
- impulse stage, steam turbines, 6.39
- impulse turbines, 6.78–6.79
 - runners, 6.79
 - sizes, 6.83
- in-line gas dampeners,
 - displacement pumps, 3.69
- inadequate NPSH, displacement pumps, 3.63
- inboard bearings, 2.149
- inboard-end pumps, 2.107
- inclined flows, slurries, 9.342
- inclined shaft turbines, 6.80
- incorrect driver rotation, centrifugal pumps, 2.382
- index tests, 13.2
- inducers, 2.113–2.114, 2.358
- induction hardening, gears, 6.149
- industrial uses, composite pumps, 5.58
- industrial water usage, 9.5
- inert gas marine pumps, 9.248
- inertial head, pumping systems, 8.22–8.24
- inhibitors, solutions, 9.115
- injection flow systems, 2.241–2.242
 - control valves, 2.245
 - drain lines, 2.245
 - dual strainers, 2.245
 - injection sources, 2.244
- injection-type shaft seals, 2.239–2.240
- injectors, 4.23
- inlet blades, centrifugal pumps, 2.34
- inlet pressure, rotary pumps, 3.134
- inlet vane, vertical turbine pumps, 2.164
- inlet velocity diagrams, centrifugal pumps, 2.64
- inlets, gas turbines, 6.94
- inner magnet encapsulation, sealless magnetic drive pumps, 2.304
- input power, rotary pumps, 3.145
- input speeds, adjustable-speed belt drives, 6.168
- insecticide transfer systems, 9.442
- inserts, slurry pumps, 5.44
- inside-mounted seals, 2.208
- inspecting equipment, 12.16–12.17
- inspection checklists, RFQs, 11.17
- inspection ports, wearing ring clearance, 2.120
- instabilities, high-energy pump cavitation, 2.87
- installing pumps
 - alignment, 12.3, 12.7
 - canned motor pumps, 2.321
 - compound pressure gages, 12.12
 - continuous coil packing, 2.193
 - dial indicators, 2.418
 - discharge piping, 12.9
 - expansion joints, 12.10
 - flow metering devices, 12.12
 - foundations, 12.3
 - gears, 6.159
 - grouting, 12.8
 - magnetic bearings, 2.291
 - relief valves, 12.11
 - rotary pumps, 3.133
 - screw pumps, 3.119
 - suction piping, 12.8
 - suction strainers, 12.10
 - surge chambers, 12.12
 - vents, 12.11
 - warm-up flow piping, 12.11
- installing seals, 2.228
- instrumentation, 12.12, 13.8
- insulation
 - composite pumps, 5.50
 - electric motors, 6.18–6.19
- intakes, 10.3
 - can pumps, 10.26

- cooling tower systems, 10.8
- cooling water, 10.5
- designing, 10.42
 - approach channel, 10.46
 - model scale, 10.46
 - screens, 10.47
- Froude scaling, 10.45
- insufficient NPSH, 10.42
- loss coefficients, scale
 - models, 10.50
- model similitude, 10.44
- once through, 10.5
- prerotation, 10.42
- preventing fish from entry, 10.18–10.21
- similarity of vortices, 10.45
- submergence levels, 10.25
- swirl, 10.42
- velocity caps, 10.18
- vortices, 10.39
- integral eddy current
 - couplings, 6.103
- integral relief valves, rotary
 - pumps, 3.125
- intergranular corrosion, 5.10, 9.119
- interior suction pressure, rotary
 - pumps, 3.144
- intermediate leakoff flow control
 - systems, 2.243–2.244
- intermeshing rings, 2.119
- internal axial velocity limits, screw
 - pumps, 3.109
- internal clearances, canned motor
 - pumps, 2.318
- internal combustion engines.
 - See* engines.
- internal gear pumps, 3.127
- internal static pressure distribution,
 - centrifugal pumps, 2.16
- internal vane pumps, 3.126
- Internet-based vendor
 - communication, 11.35
- interstage diaphragms, 2.108
- interstage passages, multistage
 - pumps, 2.108
- interstage shaft sleeves, 2.136
- irrigation pumps, 9.46
 - capacities, 9.48
 - discharge systems, 9.49–9.51
 - multiple pumps, 9.47
 - pool-to-pool head, 9.48
 - propeller, 9.53
 - total suction head, 9.52
 - total suction lift, 9.52
 - turbines, 9.52
 - valves, 9.48
 - volute, 9.52
- isentropic bulk modulus,
 - displacement pumps, 3.66–3.67
- isothermal bulk modulus,
 - displacement pumps, 3.67

J–K

- jacket water circulating pumps,
 - diesel generators, 9.229
- jet compressors, 4.23
- jet pumps, 4.23
 - applications, 4.20
 - BWR plants, 9.283
 - compressible flow case
 - solutions, 4.8
 - eductors, 4.24–4.25
 - applications, 4.30
 - NPSH, 4.27
 - performance, 4.30
 - equations, 4.7
 - flow regimes, 4.5–4.6
 - jet losses, 4.8
 - operating conditions, 4.20
 - pump efficiencies, 4.8
 - siphons, 4.43
 - See also* L_{JL} jet pumps; L_{JG} jet pumps; L_{JGL} jet pumps.
- jockey pumps, fire protection
 - systems, 9.58

Joule cycle, gas turbines, 6.89
 journal bearings
 critical mass, 2.270–2.271
 cross coupling, 2.267
 cylindrical bearings, 2.254
 with axial grooves, 2.255
 elliptical bearings, 2.255
 fluid film bearing cavitation, 2.248
 heat balancing, 2.263–2.266
 hybrid bearings, 2.257
 lobe bearings, 2.255
 lubrication, 2.248
 performance plots, 2.259–2.260
 rotor whirl, 2.266
 spring coefficients, 2.267
 stability, 2.270–2.273
 analyses, 2.268
 tilted pad bearings, 2.256
 turbulence, 2.252
 viscous drag losses, 2.253
 kinematic viscosities, 8.33
 Kingsbury-type bearings, electric
 motors, 6.18
 Kraemer drives, 6.122

L

L-type wearing rings, 2.119
 labyrinth wearing rings, 2.119
 lake water pumps, 9.259
 laminar flow, 8.32
 non-Newtonian slurries, 9.325
 scaling, 9.329
 Langelier Index, 5.4
 lantern rings, 2.186
 packing, 2.141
 rotary pumps, 3.124
 sealing liquids, 2.141
 lawn services systems, 9.444
 leaded bronze, impellers, 5.26
 leading edge lockup, 2.257
 leakage, 2.207
 compression packings, 2.187
 screw pumps, 3.101
 leakage joints
 casing cover rings, 2.118
 casing eings, 2.118
 impellers, 2.118
 radial clearance, 2.122
 relief chambers, 2.119
 suction head rings, 2.118
 leakoff fluid drives, 6.131
 length of mixing throat, L_{JL}
 pumps, 4.14
 level controls, sewage systems, 9.41
 leveling gear reducers, 6.160
 leveling pumps, 12.4, 12.7
 life cycle cost evaluations, RFQs,
 11.13, 11.15
 lifetimes of pumps, 5.3
 lift mechanisms, non-contacting gas
 lubricated seals, 2.222
 lime slurries, paper mill
 pumps, 9.164
 limited end float, couplings, 6.182
 limited storage constant speed
 multipump water booster
 systems, 9.456
 limiting stage pressure rise,
 high-energy pumps, 2.72
 line bearings, 2.149
 lined composite pumps, 5.53
 liners, slurry pumps, 5.44, 9.365
 liquid cylinders, reciprocating
 pumps, 3.37
 liquid end
 power pumps, 3.22
 reciprocating pumps, 3.37
 steam pumps, 3.47
 diameter, 3.56
 piston type, 3.47–3.48, 3.51
 plunger type, 3.53
 valves, 3.52
 liquid horsepower, rotary
 pumps, 3.145
 liquid jet pumps
 compressible flow case
 solutions, 4.8
 equations, 4.7
 flow regimes, 4.5–4.6

- jet losses, 4.8
- pump efficiencies, 4.8
- liquid level sensors, 7.4–7.6
- liquid noise sources, 8.110–8.111
- liquid rheostat controls,
 - wound-rotor induction motors, 6.112–6.113
- liquid rocket propellant pumps,
 - 9.431–9.432, 9.437
- liquid viscosity, petroleum pumps,
 - 9.150–9.154
- liquid-plunger separation, power pumps, 3.18
- liquor pumps, paper mills, 9.162
- LJG jet pumps (liquid-jet gas)
 - compressible flow, 4.8
 - flow regime, 4.6
- LJGL jet pumps (liquid-jet gas liquid)
 - compressible flow, 4.8
 - flow regime, 4.6
 - flow cutoff, 4.8
- LJL jet pumps (liquid-jet liquid)
 - area ratios, 4.16
 - cavitation, 4.11
 - limited flow ratios, 4.15, 4.19
 - centrifugal pump interaction, 4.19
 - equations, 4.9–4.10
 - flow performance, 4.15
 - flow ratios, reducing to curb cavitation, 4.17
 - flow regimes, 4.6
 - friction loss coefficients, 4.12
 - longitudinal dimensions, 4.14
 - mixing throats, 4.14
 - nozzle throats, 4.14
 - nozzle to throat area ratio, 4.12
 - operating flow ratio, 4.11
 - primary flow nozzles, 4.14
 - straight line approximation, 4.14
 - throat inlets, 4.15
- LNG cryogenic pumps (liquefied natural gas), 9.404–9.405
- load handling, magnetic bearings, 2.282
- load reduction, boiler feed pumps,
 - 9.79–9.81
- load stress, seismic nuclear pumps, 9.310
- loads, vertical pump foundations, 2.175
- lobe bearings, 2.255, 2.259
- lobe pumps, 3.123, 3.128–3.129
- lobe rotor food/beverage pumps, 9.190
- locating pumps in the field, 12.3
- locks, screw pumps, 3.101
- Lomakin effect, 2.135
- longitudinal dimensions, LJL pumps, 4.14
- losses, centrifugal pumps, 2.11
- low flow protection systems, 2.441
- low flow rates, 2.438
- low head systems,
 - waterhammer, 8.93
- low lift pumps, water treatment plants, 9.16
- low lubricity fuels, aircraft fuel pumps, 9.429
- low specific speed centrifugal pumps, 2.361–2.362
- low-energy domains, high-energy pumps, 2.74
- low-pressure core spray pumps,
 - BWR plants, 9.285
- LPG cryogenic pumps (liquefied petroleum gas), 9.150, 9.404–9.405
- lubricating oil pumps, 9.225
 - diesel generators, 9.229
 - diesel marine pumps, 9.227
 - steam turbogenerators, 9.228
 - transfer marine pumps, 9.230
- lubrication
 - bearings, 2.152
 - gas turbines, 6.94
 - gear units, 6.160–6.161
 - gears, bearings, 6.161
 - journal bearings, 2.248
 - power pumps, 3.34
 - refrigeration pumps, 9.260
 - single-stage steam turbines, 6.41

M

- magnet blocks, sealless magnetic drive pumps, 2.303
- magnetic bearings, 2.277–2.278
 - active, 2.282
 - backup systems, 2.279
 - catcher bearings, 2.279, 2.284
 - designing, 2.285
 - diagnostics, 2.291
 - feedback systems, 2.278–2.279
 - heteropolar, 2.285–2.288
 - homopolar, 2.289–2.290
 - imbalance loads, 2.282
 - installing, 2.291
 - pump operation, 2.292
 - reduced power consumption, 2.281
 - reliability, 2.281
- rotors
 - clearances, 2.282
 - dynamics, 2.281–2.283
- stators, sizing, 2.284
- transfer function, 2.283
- transient loads, 2.283
- tuning, 2.291
- unit load capabilities, 2.284
- user interfaces, 2.292
- magnetic drive pumps, 2.179, 2.297
- magnetic starters, electric
 - motors, 6.27
- main bearings, power pumps, 3.33
- main circulating pumps, marine
 - plants, 9.223
- main condensate pumps, marine
 - plants, 9.220–9.223
- main coolant pumps, BWR plants, 9.287, 9.290
- main fuel pumps, aircraft fuel
 - systems, 9.416–9.417, 9.420–9.422, 9.425, 9.427
- maintenance
 - annual inspections, 12.17
 - chemical pumps, 9.122
 - daily observation of pump operation, 12.16
 - engines, 6.60
 - metering pumps, 9.318
 - overhauls, 12.17
 - semiannual inspections, 12.16
 - site location, 12.2
 - solids pumps, 9.376
 - spare parts, 12.19
- manifolds
 - hydrokinetic drives, 6.130
 - power pumps, 3.27
- Manning formula, 8.41
- manual injection flow systems, 2.242
- manual starters, electric
 - motors, 6.27
- marine pumps, 9.215
 - air conditioning chilled water, 9.236
 - ballast pumps, 9.234
 - bilge pumps, 9.232
 - condenser exhausting pumps, 9.223
 - deep well cargo, 9.242–9.243
 - diesel, 9.226
 - electric-motor-driven submersible pumps, 9.246
 - exhaust gas boiler, 9.231
 - fire prevention, 9.231–9.232
 - flash distilling, 9.234
 - freshwater
 - cooling, 9.230
 - drain collecting tank pumps, 9.223
 - fuel oil diesel, 9.225–9.229
 - gas turbine fuel oil, 9.227
 - gas turbine lubricating oil, 9.227
 - heat recovery distillation, 9.235
 - hotwater circulation, 9.236
 - hydraulic system, 9.231
 - hydraulic-motor-driven submersible pumps, 9.246
 - inert gas, 9.248
 - liquid cargo transfer, 9.237–9.238, 9.241
 - lubricating oil diesel, 9.225–9.227
 - lubricating oil transfer, 9.230
 - main circulating pumps, 9.223
 - main condensate pumps, 9.220–9.223
 - potable water, 9.235

- propulsion, 9.216
 - bearings, 9.219
 - constant differential pressure governors, 9.220
 - constant pressure governors, 9.219
 - relief valves, 9.220
 - seals, 9.219
- reciprocating cargo, 9.248
- rotary cargo, 9.248
- sanitary uses, 9.236
- seawater service, 9.230
- sewage, 9.236
- stern-tube lubricating oil, 9.231
- tank cleaning, 9.249
- waste heat, 9.231
- Martensitic stainless steel
 - casings, 5.29
 - impellers, 5.27
 - shafts, 5.30
 - stress corrosion cracking, 5.7
 - wear rings, 5.31
- material flexible couplings, 6.178
- materials of construction, 5.3–5.4
 - casings, 5.28–5.29
 - chemical pumps, 9.115–9.116, 9.121
 - composite pumps, 5.60
 - fire pumps, 9.63–9.68
 - impellers, 5.26–5.27
 - mining pumps, 9.206
 - nuclear pumps, 9.299
 - packings, 2.187–2.188
 - pipeline pumps, 9.145–9.147
 - pump selection, 11.8
 - pumps, 5.32, 5.35
 - refinery pumps, 9.142
 - rotary pumps, 3.125
 - seals, 2.227
 - shafts, 5.29–5.30
 - slurry pumps, 5.43–5.44
 - solids pumps, 9.371
 - steam pumps, 3.45–3.47
 - water pressure booster systems, 9.461
 - wear rings, 5.30
- mating rings, contacting liquid lubricating seals, 2.199
- maximum demand, water supply systems, 9.5
- maximum speed rise, steam turbines, 6.45
- MCSF (minimum continuous stable flow), high-energy pumps, 2.80, 2.84
- measuring elements, 7.4
- measuring noise, 8.122–8.124
- mechanical efficiency
 - centrifugal pumps, 2.50, 2.334
 - power pumps, 3.6, 3.19
 - rotary pumps, 3.146
 - steam pumps, 3.57
- mechanical friction power, rotary pumps, 3.145
- mechanical load, 2.438
- mechanical noise sources, 8.110
- mechanical notches, reducing fatigue, 5.23
- mechanical performance
 - alignment, 2.412–2.417
 - centrifugal pumps, 2.405
 - critical speed, 2.409
 - defective bearings, 2.406
 - multistage boiler feed pumps, 2.410
- mechanical properties, composite pumps, 5.49–5.50, 5.54
- mechanical seals, 2.148
 - chemical pumps, 9.122
 - rotary pumps, 3.124
 - slurry pumps, 9.357
- mechanically actuated diaphragm metering pumps, 9.314
- mechanically driven diaphragms pumps, 3.85–3.87
- mechanically flexible couplings, 6.176–6.177
- medium specific speed centrifugal pumps, 2.364
- mercury gages, measuring head, 13.34
- metal disk couplings, 6.178

- metal-chain belt
 - transmissions, 6.171
- metallic construction materials for pumps, 5.3–5.4
- metallic packing, 2.188
- meter differential pressure, 8.77
- meter loss of head, 8.77
- metering pumps, 9.313
 - calibration, 9.317
 - capacity controls, 9.317
 - hydraulically actuated diaphragm type, 9.315
 - hydraulically actuated piston type, 9.315
 - maintenance, 9.318
 - mechanically actuated diaphragm type, 9.314
 - packed plunger type, 9.313
- microbiologically-induced corrosion, 5.10
- Miller number index, slurry particulate abrasiveness, 5.20
- minimizing gear dimension, 6.150
- minimizing gear noise, 6.151
- minimum flow control systems
 - automatic bypass systems, 2.441–2.443
 - continuous bypass systems, 2.441
 - control loop bypass systems, 2.442
 - design factors, 2.439
 - See also* flow control.
- minimum polished rod load, oil well pumps, 9.384
- minimum pump flow requirements, 2.438
- mining pumps
 - automatic controls, 9.211
 - drivers, 9.212
 - float mounted, 9.201–9.203
 - hydraulic conditions, 9.207–9.208
 - materials of construction, 9.206
 - NPSH, 9.198–9.199
 - pressure pulsations, 9.209
 - pumping conditions, 9.197–9.198
 - sumps, 9.209–9.210
 - system design, 9.205
 - waterhammer analysis, 9.208
- minor losses, pumping systems, 8.53
- mixed-flow impellers, 2.113
 - axial thrust, 2.127
 - centrifugal pumps, reducing diameter, 2.339
- mixing eductors, 4.33
- mixing throats, L/JL pumps, 4.14
- modal analysis, seismic nuclear pumps, 9.303
- model similitude, intake design, 10.44
- model testing, 13.2, 13.39–13.40
 - noise reduction, 8.124
 - suction pits, 10.22
- modeling intakes, 10.42–10.47
- modified Kraemer drives, 6.122
- modulating control systems, 7.2
- moments of forces, centrifugal pumps, 2.13
- Moody-Stauffer formula, centrifugal pumps, 2.383
- motion equations, electric motors, 6.23
- motor sheaves, 6.171
- motor speeds, aircraft fuel pumps, 9.414
- motor-driven pumps, 3.87
- motor-generated exciters, synchronous motors, 6.7
- motors
 - electric. *See* electric motors.
 - failures due to waterhammer, 8.95–8.96
- mounting wearing rings, 2.122
- mud eductors, 4.36
- mufflers, engines, 6.70
- multinozzle eductors, 4.38
- multiphase uses, screw pumps, 3.117
- multiple consecutive pumps, 2.107
- multiple orifice in series control valves, 7.18
- multiple origin high cycle fatigue, 5.25
- multiple pump systems, total head, 8.16

- multiple screw pumps, 3.99
- multiple seals, 2.208
- multiple spring seals, 2.211
- multiple-convolution bellows
 - seals, 2.214
- multipump systems
 - dry pit, 10.11–10.12
 - pipng, 10.30
- multistage boiler feed
 - pumps, mechanical
 - performance, 2.410
- multistage pumps, 2.99
 - axial thrust, 2.128
 - casings, 2.107, 2.110
 - interstage passages, 2.108
 - steam turbines, 6.39, 6.47

N

- Natural frequencies, seismic nuclear
 - pumps, 9.304, 9.308
- Net inlet pressure, rotary
 - pumps, 3.145
- Net plunger stroke, oil well
 - pumps, 9.385
- Newtonian liquids, 8.33
- Ni-Resist iron, casings, 5.29
- Nitric acid chemical pumps, 9.117
- Nitriding gears, 6.149
- Nitronic alloys, wear rings, 5.32
- Noise, 8.109
 - cavitation, 8.111–8.113
 - control techniques
 - airborne noise, 8.117–8.122
 - controlling noise paths, 8.115–8.116
 - source modification, 8.113–8.114
 - exposure limits, 8.124
 - flashing, 8.113
 - gas turbines, 6.93
 - gears, 6.151
 - liquid sources, 8.111
 - measuring, 8.122–8.124
 - mechanical sources, 8.110
 - rotary pumps, 3.134
 - screw pumps, 3.120
- Noise data sheets, RFQs, 11.19–11.20
- Non-asbestos packing, 2.188
- Non-contacting gas lubricated
 - cryogenic seals, 2.227
- Non-contacting gas lubricated seals, 2.198, 2.221–2.222
- Non-drive-end pumps, 2.107
- Non-Newtonian flows
 - hydraulic gradient, 9.325
 - rheograms, 9.326
 - turbulent flows, 9.327
- Non-Newtonian fluids
 - rotary pumps, 3.136
 - screw pumps, 3.113–3.114
- Non-Newtonian slurries
 - hydraulic gradient, 9.325
 - laminar flow, 9.325
- Non-recirculating flows, centrifugal
 - pumps, 2.46
- Nonaerated solutions, 9.114
- Nonclog sewage pumps, 9.29
- Nonmetallic chemical pumps, 9.124
- Nonpusher seals, 2.214
- Nonreverse ratchets, waterhammer
 - prevention, 8.102
- Nonseismic nuclear pumps, 9.301
- Nozzle rings, 2.119
- Nozzle throats, L/JL pumps, 4.14
- Nozzle to throat area ratio, L/JL
 - pumps, 4.12
- Nozzles, 2.106
- NPSH (net positive suction head), 2.16–2.17, 2.224, 3.111
 - boiler feed pumps, steam power
 - plants, 9.78–9.79
 - centrifugal pumps, 2.25, 2.349–2.351, 2.355
 - displacement pumps,
 - inadequacies, 3.63
 - eductors, 4.27
 - high-energy pumps, life
 - prediction, 2.90

- losses, 10.42
- mining pumps, 9.198–9.199
- pipng losses, 10.30
- screw pumps, 3.110–3.112
- units of measure, 13.5
- water supply systems, 9.12
- NPSHA (Net positive suction head available), 3.63, 2.397
- NPSHR (NPSH required), 2.398
- Nuclear pumps, 9.279
 - classes, 9.294
 - design issues, 9.293–9.294
 - materials of construction, 9.299
 - nonseismic, 9.301
 - SSEs (safe shutdown earthquakes), 9.301, 9.306
 - types, 9.291
 - working pressures, 9.87

O

- O rings, sleeves, 2.138
- ocean inlets, once through intakes, 10.5
- oil
 - ball bearing lubricant, 2.153
 - bearing lubricant, 2.152
 - field brines and salinity, 5.37
- oil coolers
 - hydrokinetic drives, 6.129
 - hydroviscous drives, 6.134
- oil pumps
 - hydraulic presses, 9.464
 - hydrokinetic drives, 6.129
 - hydroviscous drives, 6.134
- oil seals
 - gear units, 6.161
 - sewage pumps, 2.144
- oil well pumps
 - artificial lift, 9.377
 - counterbalance, 9.386
 - electric submersible centrifugal, 9.393

- hydraulic submersible centrifugal, 9.395–9.396
- impulse load, 9.383
- installation calculations, 9.382
- minimum polished rod load, 9.384
- net plunger stroke, 9.385
- peak polished rod load, 9.384
- peak torque, 9.384
- plungers
 - fluid weight, 9.382
 - overtravel, 9.384
- polished rod power, 9.384
- rod weights, 9.383
- subsurface hydraulic, 9.386–9.387
- subsurface progressing cavity, 9.392
- subsurface reciprocating hydraulic, 9.390–9.391
- sucker rod, 9.378
 - stretch, 9.385
- torque ratings, 9.382
- tubing shrink, 9.385
- oil-ring lubrication system, single-stage steam turbines, 6.41
- on-off control systems, 7.2–7.3, 7.9
- once through intakes, ocean inlets, 10.5
- one-dimensional model, magnetic bearing design, 2.285
- open channels, frictional head losses/hydraulic gradients, 8.41
- open cycles, steam power plants, 9.75
- open drip-proof enclosures, electric motors, 6.15
- open enclosures, electric motors, 6.15
- open ended branch-line pumping systems, 8.84–8.86
- open externally vented enclosures, electric motors, 6.15
- open impeller pumps, casings, 2.104
- open impellers, 2.115
- open pipe vented enclosures, electric motors, 6.16
- open-cycle gas turbines, 6.90
- open-loop controls, 7.3

- operating
 - centrifugal pumps, 12.13–12.14
 - costs
 - displacement pump flow control, 3.78
 - steam turbines, 6.52
 - jet pumps, 4.20
 - magnetic bearing pumps, 2.292
 - requirements
 - fluid types, 11.2
 - system head curves, 11.2–11.3
 - scale models, 10.49
 - speeds
 - rotary pumps, 3.150–3.151
 - sewage systems, 9.38
 - temperatures
 - chemical pump seals, 9.122
 - composite pumps, 5.50
 - testing pumps, 13.8–13.9
 - operating basis earthquakes, seismic
 - nuclear pumps, 9.304
 - operating envelope
 - non-contacting gas lubricated seals, 2.222
 - seals, 2.207
 - operating flow ratio, L/JL
 - pumps, 4.11
 - operating frequency, sewage systems, 9.38
 - operating pressures, hydraulic presses, 9.466
 - opposed impellers, 2.128
 - optimum geometry, pumps, 1.4
 - organic acid chemical pumps, 9.117
 - organic compound chemical pumps, 9.118
 - orifice issues, bypass systems, 2.448
 - orifice meters, 2.449, 13.17
 - origins of pumps, 1.2
 - OTI volume (open-to-inlet), rotary pumps, 3.123
 - OTO volume (open-to-outlet), rotary pumps, 3.123
 - outboard bearings, 2.149
 - outboard-end pumps, 2.107
 - outer impeller hubs, 2.118
 - outer magnet encapsulation, sealless magnetic drive pumps, 2.305
 - outlet blades, centrifugal pumps, 2.34–2.35
 - outlet discharge pressure, rotary pumps, 3.144
 - outlet pipes, suction tanks, submergence, 10.25
 - outlet velocity diagrams, centrifugal pumps, 2.64
 - output torque, adjustable-speed belt drives, 6.172
 - outside-mounted seals, 2.208
 - overall efficiency, 2.329, 3.146
 - overfilling vanes, centrifugal pumps, 2.343
 - overhauling pumps, 12.17
 - overhung impellers, 2.113, 2.118
 - axial thrust, 2.126
 - sleeves, 2.138
 - overpressure fire pumps, 9.58
 - oversizing shaft at impeller, 2.135
 - overspeed trip system
 - single-stage steam turbines, 6.41
 - steam turbines, 6.46
 - OWS (oily-water separator), 9.234
 - oxygen pumps, liquid rocket propellant pumps, 9.432
- ## P
- packaged gas turbine drivers, 6.95
 - packaged gear drives, 6.152
 - packed plunger metering pumps, 9.313
 - packing glands, 2.147
 - packing rings, 2.184
 - packing seals, 2.183
 - packings
 - abrasives, 2.192
 - air leakage, 2.192
 - chemical pumps, 9.122
 - coefficients of friction, 2.187

- compression, 2.184
- continuous coil, 2.193
- lantern rings, 2.141
- materials used, 2.187–2.188
- power pumps, 3.26
- pressure issues, 2.190–2.191
- rotary pumps, 3.124
- sleeves, 2.138
- slurry pumps, 9.357
- temperature issues, 2.192
- packless stuffing boxes, 2.239
- Pamgren-Miner cumulative damage
 - law, 5.26
- paper mill pumps, 9.159, 9.182
 - black liquor, 9.163–9.164
 - bleach liquors, 9.164
 - blow tank discharge, 9.163
 - capacities, 9.175
 - chlorine dioxide, 9.165
 - digester circulating, 9.181
 - efficiencies, 9.180–9.181
 - foul condensate, 9.166
 - green liquor, 9.164
 - lime slurries, 9.164
 - liquors, 9.162
 - pipng, 9.167
 - friction losses, 9.170–9.173, 9.177–9.179
 - slurries, 9.162
 - steaming out process, 9.181
 - stock, 9.166
 - stock pumps, 9.167
 - wash liquors, 9.165
 - water pumping, 9.161
 - white liquor, 9.162
- parallel misalignment, 2.228
- parallel operations, centrifugal
 - pumps, 2.367–2.368
- parallel pump bypass systems, 2.450
- parallel water supply systems, 9.13–9.14
- parallel-shaft gears, 6.144
- parshall flumes, 13.23–13.24
- partially stratified slurries, 9.322
 - deposition, 9.332
 - pressure gradients, 9.335–9.337
- particle impact wear, slurry
 - pumps, 9.364
- particulates, 5.19–5.20
- peak polished rod load, oil well
 - pumps, 9.384
- peak torque, oil well pumps, 9.384
- pedestal bearings, 2.149
- Pelton wheel turbines, 6.79
- perforated plates, head losses, 8.73
- performance
 - aircraft boost pumps, 9.414
 - centrifugal pumps, 2.24
 - condenser circulating
 - pumps, 9.105
 - direct acting steam pumps, 3.53
 - eductors, 4.30
 - electric motors, 6.21
 - LJL pumps, 4.15
 - pipeline pumps, 9.147
 - pumps, 5.3
 - refinery pumps, 9.141
 - rotary pumps, 3.147–3.149
 - screw pumps, 3.109
 - seals, 2.198
- performance characteristic curves
 - centrifugal pumps, 2.18, 2.46, 2.334
 - axial thrust, 2.53–2.54
 - backward curved blades, 2.331
 - CFD, 2.51–2.52
 - forward curved blades, 2.332
 - mechanical efficiency, 2.50
 - non-recirculating flows, 2.46
 - non-viscous flow, 2.329–2.330
 - radial curved blades, 2.332
 - viscous flow, 2.331
 - volumetric efficiency, 2.50
 - hydraulic water pumps, 6.197
 - journal bearings, 2.259–2.260
- performance troubleshooting, 2.397
- peristaltic food/beverage
 - pumps, 9.193
- pest control systems, 9.444
- pesticide transfer systems, 9.442
- petroleum pumps, 9.134
 - liquid viscosity, 9.150–9.154
 - transfer systems, 9.443
- See also* oil well pumps.

- pharmaceutical pumps, 9.187–9.188
- phosphoric acid chemical pumps, 9.117
- piezoelectric accelerometers, 2.422
- pigment chemical pumps, 9.116
- pilot-operated ARC valves, 2.444
- pilotless trim design ARC valves, 2.444
- pipeline pumps, 9.142–9.143
 - materials of construction, 9.145–9.147
 - performance, 9.147
- piping
 - bends, resistance coefficients, 8.65
 - discharge end, 12.9
 - displacement pumps
 - acoustic velocities, 3.64–3.65
 - pulsation responses, 3.64
 - expansion joints, 12.10
 - fitting losses, 8.53
 - friction, 8.33–8.34
 - gas turbines, 6.95
 - manifold pumps, 10.29
 - multipump systems, 10.30
 - NPSH losses, 10.30
 - paper mill pumps, 9.167
 - friction losses, 9.170–9.173, 9.177–9.179
 - screens, 10.32
 - screw pumps, 3.119
 - sewage systems, 9.41
 - strainers, 10.32
 - strains, 12.9
 - suction end, 12.8
 - suction pits, 10.28–10.29
 - surge protection, 10.31
 - vents, 12.11
 - vibration problems, 10.31
 - displacement pumps, 3.70
 - warm-up flow, 12.11
- piston food/beverage pumps, 9.193
- piston type liquid ends, steam pumps, 3.47–3.48, 3.51
- pistons
 - engines, velocities, 6.59
 - hydroviscous drives, 6.134
 - power pumps, 3.24
 - reciprocating pumps, 3.37
 - steam pumps, speeds, 3.55
- pitot static tubes, 13.18
- pitot tubes, 13.18
- pitting
 - centrifugal pumps, 2.347
 - chemical pumps, 9.118
- plain gland plates, 2.220
- plant water pumps, water treatment plants, 9.18
- plunger type liquid ends, steam pumps, 3.53
- plungers
 - oil well pumps
 - fluid weight, 9.382
 - overtravel, 9.384
 - power pumps, 3.24
 - reciprocating pumps, 3.37
- PM brushless DC motors
 - (permanent magnet), 6.10–6.12
- pneumatic ejectors, raw sewage pumps, 9.29
- poises, 8.33
- polished rod power, oil well pumps, 9.384
- pollutants, engines, 6.60
- polymer chemical pumps, 9.115–9.116
- pony rods, power pumps, 3.32
- pool-to-pool head, drainage/irrigation pumps, 9.48
- portable drainage pumps, 9.47
- positioners, control valve actuators, 7.26
- positive displacement pumps
 - acoustic filters, 3.68
 - bypass control, 3.78
 - diagnostics, 3.70–3.71
 - flow control, 3.75
 - operating costs, 3.78
 - pumps in series, 3.83
 - food/beverage, 9.190
 - gas-charged dampeners, 3.69
 - in-line gas dampeners, 3.69
 - inadequate NPSH, 3.63

- isentropic bulk moduli, 3.66–3.67
- isothermal bulk moduli, 3.67
- paper mill pumps, 9.181
- pipng system
 - acoustic velocities, 3.64–3.65
 - pulsation responses, 3.64
 - vibration, 3.70
- positive pulsations, 3.64
- power pumps, 3.3
- pulsation control, 3.67
- shaft failures, 3.73
- side branch accumulators, 3.69
- solids pumps, 9.369
- speed changer controls, 3.76
- starting/stopping, 12.15
- suction valve unloading, 3.76–3.77
- thermal problems, 3.72
- troubleshooting, 3.63
- potable water marine pumps, 9.235
- power end
 - chemical pumps, 9.122
 - power pumps, 3.16, 3.28
- power factors, electric motors, 6.26
- power failures, 12.16, 2.376
- power measurements, 13.35
- power output, centrifugal pumps, 2.329
- power pumps, 3.3
 - antifriction pin bearings, 3.34
 - applications, 3.35
 - bhp, 3.4
 - break-away torque, 3.8
 - capacitance, 3.4
 - connecting rods, 3.31
 - crank pin bearings, 3.33
 - crankshafts, 3.28–3.29
 - crossheads, 3.32
 - crossways, 3.32
 - cylinder, 3.22
 - cylinder liners, 3.26
 - derating, 3.9
 - designing, 3.21–3.22
 - displacement, 3.4
 - eccentric straps, 3.31
 - frames, 3.28
 - liquid end, 3.22
 - liquid-plunger separation, 3.18
 - lubrication, 3.34
 - main bearings, 3.33
 - manifolds, 3.27
 - mechanical efficiency, 3.6, 3.19
 - packing, 3.26
 - pistons, 3.24
 - plungers, 3.24
 - pony rod, 3.32
 - power end, 3.16, 3.28
 - pressure, 3.4
 - pull rod, 3.33
 - pulsation, 3.10
 - pumping cycles, 3.10
 - relief valves, 3.35
 - rod load, 3.17
 - sleeve bearings, 3.33
 - slip, 3.5
 - stress limits, 3.23
 - stroke rate, 3.6
 - stuffing boxes, 3.25
 - torque, 3.8
 - unbalanced reciprocating parts
 - force, 3.18
 - unbalanced rotating parts
 - force, 3.19
 - valve covers, 3.28
 - valve dynamics, 3.14
 - valve spring rates, 3.16
 - valve springs, 3.16
 - valve stiction, 3.14
 - valves, 3.12–3.13, 3.15, 3.27
 - volumetric efficiency, 3.6–3.7
 - wrist pin bearings, 3.33
 - wrist pins, 3.31
- power ranges, gear reducers, 6.153
- power ratings
 - engines, 6.57–6.58
 - screw pumps, 3.116
- power shafts
 - Francis turbines, 6.80
 - hydraulic turbines, 6.80
- power transmission systems,
 - 6.175–6.176,
 - 6.191–6.192, 6.197
- power-recovery turbines, 6.83
- pre-bid meetings, 11.24
- pre-rotation, 2.105–2.106

- predetermined thrust direction,
 - hydraulic balancing devices, 2.130
- preoperation checks, centrifugal pumps, 12.14
- prerotation, 10.42, 10.50
- pressure
 - chemical pump seals, 9.123
 - fully stratified slurry gradients, 9.335, 9.337
 - power pumps, 3.4
 - rotary pumps, 3.145
 - seal calculations, 2.200–2.201
 - screw pump capabilities, 3.103
 - water supply system
 - differential, 9.12
- pressure head, pumping systems, 8.5, 8.10
- pressure losses, equivalent fluid slurries, 9.323
- pressure lubrication system, single-stage steam turbines, 6.41
- pressure pulsations, 2.403
 - fundamental shaft frequency, 8.105
- high-energy pumps, 2.71
 - cavitation, 2.87
- impeller vane frequency, 8.106
- mining pumps, 9.209
- scroll case frequency, 8.107
- pressure recovery, control valves, 7.23
- pressure rise, aircraft fuel pumps, 9.414–9.415
- pressure sensors, 7.7
- pressure temperature profiles,
 - canned motor pumps, 2.321
- pressure transducers, 13.18
- pressure velocity, seals, 2.202
- pressure-reducing devices, 2.145
- preventing unprimed pump operation, 2.466
- primary flow nozzles, LjL pumps, 4.14
- primary rings, contacting liquid lubricating seals, 2.199
- prime movers, drainage/irrigation, 9.53
- primers
 - centrifugal pumps, 2.359
 - sewage pumps, 2.464
- priming
 - centrifugal pumps, 12.13
 - screw pumps, 3.120
- priming chambers, 2.456
- priming eductors, 4.41
- priming ejectors, 2.458
- priming inductors, 2.457
- priming tanks, 2.465
- profiles, discharge lines,
 - waterhammer, 8.93
- progressing tooth gear pumps, 3.129
- progressive cavity food/beverage pumps, 9.190
- progressive cavity pumps, 3.99
- propeller drainage pumps, 9.46, 9.53
- propeller irrigation pumps, 9.46, 9.53
- propeller turbines, 6.79, 6.83
- propellers, 2.113
- proportional control systems, 7.3
- proportioning pumps, 9.313
- propulsion marine pumps, 9.216
 - bearings, 9.219
 - constant differential pressure governors, 9.220
 - constant pressure governors, 9.219
 - relief valves, 9.220
 - seals, 9.219
- propylene uses, composite pumps, 5.57
- PRVs (Pressure Reducing Valves), 2.448
- public water usage, 9.5
- pull rods, power pumps, 3.33
- pull-in torque, electric motors, 6.25
- pulleys, 6.171
- pullout pumps, 2.167
- pulp mill pumps, 9.159
- pulping process, 9.159–9.160
- pulsation
 - displacement pumps, 3.67
 - power pumps, 3.10
 - responses, 3.64

- pump covers, rotary pumps, 3.124
- pump data sheets, RFQs, 11.11
- pump drives
 - adjustable-speed belt drives, 6.167
 - gear reduction, 6.169
 - input speed, 6.168
 - operations, 6.170
 - speed control, 6.169
 - V belts, 6.170
 - continuous-tooth herringbone gears, 6.146
 - double helical gears, 6.146
 - gears, 6.143
 - helical gears, 6.144–6.146
 - hypoid-bevel gears, 6.148
 - parallel-shaft gears, 6.144
 - spiral-bevel gears, 6.147
 - spur gears, 6.144
 - straight-bevelgears, 6.147
 - worm gears, 6.148
 - zero-bevelgears, 6.147
- pump efficiencies, jet pumps, 4.8
- pump efficiency formula, 13.37
- pump noise, 8.109
 - cavitation, 8.111–8.113
 - control techniques, 8.113
 - airborne noise, 8.117–8.122
 - controlling noise paths, 8.115–8.116
 - source modification, 8.113–8.114
- exposure limits, 8.124
- flashing, 8.113
- liquid sources, 8.111
- measuring, 8.122, 8.124
- mechanical sources, 8.110
- pump pits, cooling tower systems, 10.6
- pump power formula, 13.36
- pump turbines, pumped storage, 9.262
- pump-out vanes, 2.115, 2.126
- pumped storage systems, 9.261
 - conventional generation, 9.268
 - economic evaluation, 9.272, 9.275
 - generator motors, 9.262
 - governor times, 9.270
 - pump turbines, 9.262
 - pumping mode, 9.266
 - rotating spinning reserve, 9.269
 - surge tanks, 9.271
 - transient speeds, 9.263–9.264
- pumping chamber, rotary pumps, 3.124
- pumping conditions, mining pumps, 9.197–9.198
- pumping cycles, power pumps, 3.10
- pumping mode, pumped storage, 9.266
- pumping stations, 9.148
 - sump, 9.54
 - superstructure, 9.54
 - water. *See* water supply systems.
- pumping systems, 8.3–8.4
 - bar racks, head losses, 8.73
 - defining operation requirements
 - control systems, 11.4
 - fluid types, 11.2
 - operating modes, 11.3
 - pump type selection, 11.4, 11.7
 - system head curves, 11.2–11.3
 - deformation rates, 8.32
 - elevation head, 8.6
 - energy gradients, 8.12
 - equivalent head, 8.5
 - fluid characteristics, 11.7
 - friction, 8.32
 - frictional head losses, 8.41
 - head, 8.5
 - head losses, 8.32, 8.64
 - metering systems, 8.66
 - pipe frictional losses, 8.34, 8.39, 8.42–8.48
 - screens, 8.70
 - wire mesh screening, 8.71
 - hydraulic gradients, 8.12
 - incompressible liquids, 8.5
 - inertial head, 8.22–8.24
 - kinematic viscosities, 8.33
 - laminar flow, 8.32
 - meter differential pressure, 8.77
 - meter loss of head, 8.77
 - minor losses, 8.53

- multiple pump systems, total head, 8.16
- perforated plates, head losses, 8.73
- pipe bends, resistance coefficients, 8.65
- pipe friction, 8.33–8.34
- pressure head, 8.5, 8.10
- reverse-speed-torque, 8.20
- shear stress, 8.32
- siphon head, 8.25–8.31
- starting against check valves, 8.20
- starting against closed valves, 8.17
- starting against open valves, 8.20
- suction elbows, 8.66
- system-head curves, 8.13
- temperature variations, flow rates, 8.77
- throttling orifices, head losses, 8.77
- total head, 8.6–8.9
- turbulent flow, 8.32
- valves, flow coefficients, 8.56–8.58, 8.62–8.63
- variable static head, 8.15
- variable system resistance, 8.16
- velocity head, 8.5
- pumping time variations, water supply systems, 9.6
- pumps
 - air conditioning. *See* air conditioning pumps.
 - alignment, 12.3–12.4, 12.7
 - aircraft fuel, 9.409
 - ash handling, 9.111
 - axial thrust, 2.401
 - axially split, 2.99
 - backflow preventers, 2.143
 - bearings, 2.149
 - bedplates, 2.155
 - beverage. *See* beverage pumps.
 - boiler circulating, 9.108–9.109
 - bottom-suction, 2.106
 - brine, 9.259
 - canned motor pumps, 2.315
 - cantilever shaft, 2.168
 - casings, 2.102
 - feet locations, 2.110
 - handholes, 2.107
 - hydrostatic tests, 2.111
 - mechanical features, 2.107
 - cast-iron flanges, 2.110
 - cavitation, 2.398
 - centerline support, 2.157
 - centrifugal. *See* centrifugal pumps.
 - classification, 1.2–1.3
 - condenser circulating. *See* condenser circulating pumps.
 - control systems, 7.2
 - cyclone separators, 2.142
 - diaphragms, 3.85–3.87
 - diffusers, 2.97, 2.100, 2.163
 - direct acting throttle control, 3.75
 - disc diaphragm, 3.89
 - discharges
 - nozzles, 2.106
 - piping, 12.9
 - recirculation, 2.398
 - displacement
 - flow control, 3.75
 - in series flow control, 3.83
 - double volute, 2.101
 - double-ring, 2.119
 - doweling, 12.8
 - drainage. *See* drainage pumps.
 - drive shaft systems, 6.182–6.183
 - drive-end, 2.107
 - dry vacuum, 2.458
 - eddy current couplings, 6.99
 - electric motors. *See* electric motors.
 - electronic, 3.87–3.88
 - end suction, casings, 2.102
 - erosion, 5.19
 - field locations, 12.3
 - fire protection. *See* fire protection systems.
 - flexible liners, 3.126
 - flexible pipe, bedplate issues, 2.157
 - flow control, 2.437, 2.441–2.443
 - design factors, 2.439
 - flow requirements, 2.438
 - food. *See* food pumps.
 - foot valves, 2.456
 - foundations, 12.3, 12.8

- fretting, 5.15
- fuel oil. *See* fuel oil pumps.
- gear, 3.123, 3.127
- gerotor, 3.129
- groundwater, 9.3–9.4
- grouting, 12.8
- heater drain. *See* heater drain pumps.
- high purity water and erosion, 5.35
- horizontal-shaft, 2.99
- hot water. *See* hot water pumps.
- impellers, 2.97, 2.113–2.115
- inboard-end, 2.107
- inducers, 2.114
- intakes, 10.3
- internal vane, 3.126
- irrigation. *See* irrigation pumps.
- jet
 - compressible flow case
 - solutions, 4.8
 - equations, 4.7
 - flow regimes, 4.5–4.6
 - jet losses, 4.8
 - pump efficiencies, 4.8
- jet. *See* jet pumps.
- lake water. *See* lake water pumps.
- leveling, 12.4, 12.7
- lifetimes, 5.3
- liquid jet
 - compressible flow case
 - solutions, 4.8
 - equations, 4.7
 - flow regimes, 4.5–4.6
 - jet losses, 4.8
 - pump efficiencies, 4.8
- liquid rocket propellant, 9.432
- LJL, equations, 4.9–4.10
- lobe, 3.123, 3.128–3.129
- low flow rates, 2.438
- magnetic bearings, 2.277–2.278
- magnetic drives, 2.178
- maintenance. *See* maintenance.
- marine. *See* marine pumps.
- materials of construction,
 - 5.3–5.4, 5.32, 5.35
- metering, 9.313
- motor failure, waterhammer,
 - 8.95–8.96
- motor-driven, 3.87
- multiple screw, 3.99
- multistage, 2.99
 - casings, 2.107, 2.110
 - interstage passages, 2.108
- non-drive-end, 2.107
- nuclear, 9.279
- oil well, 9.377
- open impeller casings, 2.104
- optimum geometry, 1.4
- outboard-end, 2.107
- overhauling, 12.17
- paper/pulp. *See* paper mill pumps.
- performance troubleshooting,
 - 2.397
- pharmaceutical. *See*
 - pharmaceutical pumps.
- pipeline. *See* pipeline pumps.
- power-driven, speed control, 3.75
- pre-rotation, 2.105–2.106
- pressure pulsations, 2.403
- preventing unprimed
 - operation, 2.466
- priming, 2.455–2.458
- progressing tooth gear, 3.129
- progressive cavity, 3.99
- radial thrust, 2.100–2.101, 2.402
- radially split, 2.99
- radially split double casing, 2.110
- raw sewage, 9.29
- refinery. *See* refinery pumps.
- refrigeration, 9.259
- rigid vane, 3.126
- ring casing, 2.110
- rotary, 3.123
- rotation, 2.107
- safety shutdown systems, 2.445
- saline water and erosion, 5.36
- screw, 3.99
- screw-and-wheel, 3.128
- seal chambers, 2.139, 2.141
- sealing liquids, 2.141–2.143
- sealless. *See* sealless pumps.
- seawater. *See* seawater pumps.

- selecting, 1.5
- self-priming, 2.461–2.462
- semi-open impeller casings, 2.105
- series unit, 2.107
- sewage. *See* sewage systems.
- shafts, 2.132
 - failures, 2.401–2.403
- shutdown, waterhammer
 - prevention, 8.103
- side-suction, 2.106
- single-chamber primers, 2.456
- single-stage, 2.99
- single-volute, 2.168
- single-volute casing, 2.100
- solenoid, 3.87
- solid casings, 2.102
- specific speed, 1.4
- split casings, 2.102
- stage pieces, 2.108
- starting, waterhammer
 - prevention, 8.102
- steam heat. *See* steam heat pumps.
- stop pieces, 2.106
- straight-radial-vane
 - high-speed, 2.179
- stuffing boxes, 2.139–2.141
- submersible motor-driven
 - wet-pit, 2.177
- suction piping, 12.8
- suction recirculation, 2.398–2.400
- surface water, 9.3
- testing. *See* testing pumps.
- thrust bearings, 2.149
- tubular diaphragm, 3.91
- two-chamber primers, 2.457
- vacuum primers, 2.458
- vane, 3.123
- vertical dry-pit, 2.158–2.160
- vertical propeller, 2.166–2.167
- vertical sewage, 2.158
- vertical shaft, 2.99
- vertical single-suction, 2.160–2.162
- vertical turbine, 2.163–2.165
- vertical wet-pit, 2.163
- volute, 2.97, 2.168
- volute-casing, 2.99
- vortex pumps, 2.389
- wear, 5.13
- well. *See* well pumps.
- wet vacuum, 2.458
- purchase orders, 11.30
- purchase recommendations, 11.29
- purity of solutions, 9.115
- pusher-type seals, 2.211
- PV, pressure times velocity, 2.202
- PWM (pulse width modulation)
 - electric drives, 6.109
 - frequency inverters, 6.118
- PWR plants (pressurized water
 - reactor), 9.279
 - boron injection recirculation
 - pumps, 9.280
 - charging pumps, 9.280
 - chilled water pumps, 9.283
 - component cooling water
 - pumps, 9.280
 - containment spray pumps, 9.280
- ECCS (emergency core cooling
 - system), 9.280
- reactor coolant pumps, 9.280
- recycle evaporator feed
 - pumps, 9.283
- residual heat removal
 - pumps, 9.280
- RHR pumps (residual heat
 - removal), 9.280
- safety injection pumps, 9.280
- spent fuel pit pumps, 9.283
- spent resin sluicing pumps, 9.283

Q

- Q, rotary pumps, 3.138–3.139
- Q3D (quasi three-dimensional
 - analysis), 2.48
- qualification analysis, seismic
 - nuclear pumps, 9.308
- qualification testing, seismic nuclear
 - pumps, 9.309

quantity meters, 13.14
 quick opening slow closing
 valves, waterhammer
 prevention, 8.101

R

Rabinowitsch-Mooney technique,
 scaling laminar flow, 9.329
 radial blades, centrifugal
 pumps, 2.332
 radial clearances, leakage
 joints, 2.122
 radial impellers, axial thrust, 2.127
 radial magnet forces, sealless
 magnetic drive pumps, 2.304
 radial pins, impeller rings, 2.123
 radial thrust, 2.101, 2.402
 centrifugal pumps, 2.372
 pumps, 2.100
 radial vane impellers, 2.113
 radially split casings, 2.102
 radially split double casing
 pumps, 2.110
 radially split pumps, 2.99
 radiators, engines, 6.64–6.65
 raised-face flanges, 2.110
 rangeability, control valves, 7.21
 Ranney wells, 10.10
 ratchets, electric motors, 6.20
 rate of flow meters, 13.15
 ratings
 adjustable-speed belt drives, 6.172
 eddy current couplings, 6.106
 gas turbines, 6.91
 ratios, gear reducers, 6.153
 raw sewage pumps, 9.29
 firm capacity, 9.29
 pneumatic ejectors, 9.29
 RD-170 rocket engine, 9.439
 reaction stage, steam turbines, 6.40
 reactor coolant pumps, 9.280
 reactor core isolation cooling pumps,
 BWR plants, 9.285
 reactor feed pumps, 9.150
 reactor water cleanup pumps, BWR
 plants, 9.284
 recessed impellers, 2.168
 reciprocating cargo pumps, 9.248
 reciprocating hydraulic presses,
 9.464–9.465
 reciprocating pumps
 discharge stroke, 3.38
 double acting, 3.38
 liquid cylinders, 3.37
 liquid end, 3.37
 pistons, 3.37
 plungers, 3.37
 single-acting, 3.38
 suction stroke, 3.38
 troubleshooting, 12.24
 recirculating flow, centrifugal
 pumps, 2.19
 recirculation, 2.398, 2.400
 canned motor pumps, 2.321
 centrifugal pumps, 2.369–2.370
 discharge pumps, 2.463
 high-energy pumps, 2.78–2.79
 recirculation pumps, BWR
 plants, 9.283
 recirculation to suction pumps, 2.462
 recommended test procedures,
 13.12–13.13
 records of pump test data, 13.38
 recycle evaporator feed pumps, 9.283
 reduced flow
 bolier feed pumps, 9.90
 centrifugal pumps, 12.13
 reduced power consumption,
 magnetic bearings, 2.281
 reducing waterhammer, 8.93, 8.95
 refiner mechanical pulp, 9.159
 refinery pumps, 9.133–9.134
 construction, 9.134, 9.137
 drivers, 9.142
 materials of construction, 9.142
 performance, 9.141
 See also oil well pumps.
 refining industry, seal
 standards, 2.215
 refrigeration pumps, 9.259

- lubricating oil transfer, 9.260
- refrigerant circulation, 9.260
- refueling cryogenic pumps, 9.401
- regulation of flow, condensate pumps, 9.100
- regulation of flow rate, centrifugal pumps, 2.365
- regulations, fire protection systems, 9.60
- reliability
 - magnetic bearings, 2.281
 - sewage systems, 9.38
- relief chambers, 2.119
 - leakage joints, 2.119
 - pressure-reducing devices, 2.145
- relief valves, 12.11
 - power pumps, 3.35
 - propulsion marine pumps, 9.220
- remote monitoring, mining pumps, 9.211
- renewable shaft sleeves, 2.136
- repairing equipment, 12.17
- requisitions, see RFQs, 11.9
- residual heat removal pumps,
 - PWR plants, 9.280
- resistance coefficients, pipe bends, 8.65
- resistance to cavitation, 5.13
- resistance to wear, slurry pumps, 9.364
- response spectra, seismic nuclear pumps, 9.304
- response speeds
 - hydrodynamic drives, 6.138
 - hydrokinetic drives, 6.136
 - hydroviscous drives, 6.138
- return passages, centrifugal pumps, 2.45
- reverse-speed-torque, pumping systems, 8.20
- reversed impellers, centrifugal pumps, 2.382
- Reynolds equation, 2.249, 2.251
- RFQs (requests for quotation), 11.9
 - bidders lists, 11.20–11.22
 - commercial terms and conditions, 11.9
 - energy evaluations, 11.11
 - inspection checklists, 11.17
 - life cycle cost evaluations, 11.13–11.15
 - noise data sheets, 11.19–11.20
 - pump data sheets, 11.11
 - technical specifications, 11.9
 - technical specs, 11.10
 - testing checklists, 11.17
 - vendor data requirement forms, 11.17
- rheograms, non-Newtonian flows, 9.325–9.326
- RHR pumps (residual heat removal), 9.280, 9.285
- rigid couplings, 6.175–6.176
- rigid shafts, 2.133, 6.185–6.186
- rigid vane pumps, 3.126
- rigid water column theory, waterhammer, 8.93
- rigidity of seismic nuclear pumps, 9.308
- ring-casing pumps, 2.110
- ring-section pumps, 2.110
- rings, intermeshing, 2.119
- rising head characteristic, 2.334
- rod load, power pumps, 3.17
- rod weights, oil well pumps, 9.383
- roller bearings, slurry pumps, 9.357
- rolling element bearings, 2.149, 6.18
- rolling-media filters, gas turbines, 6.94
- rotary cargo pumps, 9.248
- rotary chemical pumps, 9.120
- rotary pumps, 3.123
 - abrasives, 3.137
 - affinity laws, 3.132
 - capacity, 3.139–3.140
 - casing housing, 3.124
 - cavitation, 3.135
 - centrifugal pump
 - comparisons, 3.130
 - corrosiveness of fluids, 3.136
 - CTIO volume (closed-to-inlet-and-outlet), 3.123
 - displacement, 3.138, 3.141–3.143
 - dissolved gases, 3.134

- dry running, 3.133
- end plates, 3.124
- entrained air, 3.134
- flow curves, 3.131
- fluid lubricity, 3.135
- heating jackets, 3.125
- high viscosity uses, 3.132
- inlet pressure, 3.134
- input power, 3.145
- installing, 3.133
- integral relief valves, 3.125
- lantern rings, 3.124
- materials of construction, 3.125
- mechanical efficiency, 3.146
- mechanical friction power, 3.145
- mechanical seals, 3.124
- noise, 3.134
- non-Newtonian fluids, 3.136
- operating speeds, 3.150–3.151
- OTI volume (open-to-inlet), 3.123
- OTO volume (open-to-outlet), 3.123
- overall efficiency, 3.146
- packings, 3.124
- performance, 3.147–3.149
- pressure issues, 3.144–3.145
- pumping chamber, 3.124
- rotating assembly, 3.124
- safety relief valves, 3.125
- seal cages, 3.124
- seal chambers, 3.124
- slip, 3.138–3.139
- speed issues, 3.143
- stators, 3.124
- suction strainers, 3.134
- temperature of fluids, 3.135
- timed, 3.124
- troubleshooting, 12.23
- untimed arrangement, 3.124
- vapor pressure, 3.138
- viscosity if fluids, 3.135
- viscous power losses, 3.145
- Volumetric efficiency, 3.146, 3.149
- rotating assembly, rotary pumps, 3.124
- rotating seals, 2.211
- rotating spinning reserve, pumped storage, 9.269
- rotating trash screens, 10.15
- rotation, 2.107
- rotative speed
 - centrifugal pumps, 2.27
 - screw pumps, 3.114
- rotodynamic beverage pumps, 9.189
- rotodynamic food pumps, 9.189
- rotor armature, canned motor pumps, 2.318
- rotor dynamics, magnetic bearings, 2.281
- rotor sleeves, canned motor pumps, 2.318
- rotor whirl, bearings, 2.266
- rotors
 - canned motor pumps, 2.316
 - centrifugal pumps, shape and speed, 2.23
 - hydrodynamic bearing effect, 2.135
 - hydrokinetic drives, 6.129
 - hydroviscous drives, 6.134
 - magnetic bearings
 - clearances, 2.282
 - dynamics, 2.283
 - single-stage steam turbines, 6.41
 - RP1 pumps
 - liquid rocket propellant pumps, 9.433
- RRS (required response spectrum), seismic nuclear pumps, 9.304
- rubber jaw couplings, 6.179
- rules, fire protection systems, 9.60
- runners
 - Francis turbines, 6.79
 - hydraulic turbines
 - running speed, 6.82
 - impulse turbines, 6.79
 - turbines, 6.79
- Rütschi formula, centrifugal pumps, 2.384

S

- safe temperatures, electric
 - motors, 6.25
- safety injection pumps, PWR
 - plants, 9.280
- safety relief valves, rotary
 - pumps, 3.125
- safety shutdown systems, 2.445
- saline water, erosion corrosion, 5.36
- salt solution chemical pumps, 9.118
- sampling pumps, water treatment
 - plants, 9.18
- sand/mud eductors, 4.36
- sanitary marine pumps, 9.236
- Saturn V booster rockets, 9.432
- scale models, 13.39–13.40
 - flow distribution, 10.51
 - free surface vortices, 10.49
 - intake loss coefficient, 10.50
 - operating, 10.49
 - prerotation, 10.50
 - subsurface vortices, 10.49
- scaling centrifugal pumps, 2.19
- scaling laminar flow, 9.329
- SCC (stress corrosion cracking),
 - stainless steel, 5.7
- scoop tubes, hydrokinetic
 - drives, 6.129
- scoop-trimming fluid drives,
 - 6.130–6.131
- SCR (silicon-controlled rectifier),
 - electric drive power
 - supplies, 6.110
- screens, 10.14, 10.16
 - head losses, 8.70
 - intake design, 10.47
 - piping, 10.32
- screw pumps, 3.99
 - advantages, 3.100
 - delivered capacity, 3.115
 - delivery, 3.101
 - dissolved air issues, 3.113
 - double-end, 3.104
 - entrained air issues, 3.113
 - foundations, 3.120
 - GVFs (gas void fractions), 3.118
 - installing, 3.119
 - internal axial velocity limits, 3.109
 - leakage, 3.101
 - locks, 3.101
 - multiphase uses, 3.117
 - noise, 3.120
 - non-Newtonian liquids,
 - 3.113–3.114
 - NPSH, 3.110–3.112
 - performance, 3.109
 - pipe sizing, 3.119
 - power ratings, 3.116
 - pressure capability, 3.103
 - priming, 3.120
 - rotative speed, 3.114
 - seals, 3.109
 - single-end, 3.104
 - slip, 3.102
 - timed rotor, 3.103, 3.106–3.107
 - untimed rotor, 3.103, 3.107–3.108
 - vapor pressure issues, 3.110
 - viscosity issues, 3.113
- screw-and-wheel pumps, 3.128
- scroll case frequency pressure
 - pulsations, 8.107
- scum pumps, 9.33–9.34
- SDFs (single degree of freedom
 - oscillators), seismic nuclear
 - pumps, 9.306
- seal cages, 2.141, 2.186
 - condensate pumps, 9.99
 - rotary pumps, 3.124
- seal chambers, 2.139, 2.141
 - chemical pumps, 9.122
 - rotary pumps, 3.124
- sealed ball bearings, 2.150
- sealing liquids, 2.141
 - check valves, 2.143
 - lantern rings, 2.141

- sealless chemical pumps, 9.124
- sealless magnetic drive pumps, 2.297
 - axial magnet forces, 2.304
 - bearings, 2.308, 2.310
 - breakaway torque, 2.303
 - closed coupling, 2.305
 - conduction rings, 2.298
 - containment shell, 2.305
 - dry running, 2.310
 - dual containment shells, 2.308
 - eddy current losses, 2.306–2.307
 - flow paths, 2.311
 - gaps, 2.299
 - inner magnet encapsulation, 2.304
 - magnet blocks, 2.303
 - outer magnet encapsulation, 2.305
 - radial magnet forces, 2.304
 - transmittal torque, 2.303
- sealless pumps, 2.179, 2.295
- seals
 - angular misalignment, 2.228
 - balance, 2.200–2.201
 - balanced, 2.211
 - chamber design, 2.220
 - chemical pumps, 9.122
 - chamber pressures, 9.123
 - temperature issues, 9.122
 - coefficient of friction, 2.202
 - contacting liquid lubricating, 2.197
 - mating rings, 2.199
 - primary rings, 2.199
 - refining industry standards, 2.215
 - coolant flow, 2.204–2.205
 - dual-pressurized gas
 - lubricated, 2.223
 - face pressure, 2.201
 - flushes, 2.204
 - food/beverage pumps, 9.193
 - full-convolution bellows, 2.214
 - gland plates, 2.220
 - half-convolution bellows, 2.214
 - heat removal, 2.203
 - inside-mounted, 2.208
 - installing, 2.228
 - leakage, 2.207
 - main coolant pumps, BWR plants, 9.290
 - materials of construction, 2.227
 - multiple, 2.208
 - multiple spring, 2.211
 - multiple-convolution bellows, 2.214
 - non-contacting gas lubricated, 2.221–2.222
 - non-contacting gas
 - lubricating, 2.198
 - nonpusher, 2.214
 - operating envelope, 2.207
 - outside-mounted, 2.208
 - parallel misalignment, 2.228
 - performance analysis, 2.198
 - pressure calculations, 2.200–2.201
 - pressure velocity, 2.202
 - propulsion marine pumps, 9.219
 - pusher-type, 2.211
 - refining industry standards, 2.215
 - rotating, 2.211
 - screw pumps, 3.109
 - sewage systems, 9.41–9.42
 - single, 2.208
 - single spring, 2.211
 - slurry pumps, 9.357
 - split pusher-type, 2.212
 - stationary, 2.211
 - tandem, 2.209
 - unbalanced, 2.211
- seawater and erosion corrosion, 5.37
- seawater pumps, 9.259
- seawater service marine pumps, 9.230
- second law of thermodynamics, 2.10
- secondary containment, canned motor pumps, 2.318
- segmented throttle bushings, floating rings, 2.240–2.241
- seismic nuclear pumps
 - critical damping, 9.302
 - degrees of freedom, 9.302
 - finite element method analysis, 9.303
 - floor acceleration, 9.303
 - ground acceleration, 9.303

- load stress, 9.310
- modal analysis, 9.303
- natural frequencies, 9.308
- natural frequency, 9.304
- operating basis earthquakes, 9.304
- qualification analysis, 9.308
- qualification testing, 9.309
- response spectra, 9.304–9.306
- SSEs, 9.306
- stress limits, 9.310
- time history analysis, 9.307
- time history of acceleration, 9.307
- TRS (test response spectrum), 9.307
- ZPA (zero period acceleration), 9.307
- selecting pumps, 1.5
- selective leaching corrosion,
 - chemical pumps, 9.119
- self-aligning ball bearings, 2.151
- self-aligning bearings, 2.149
- self-contained priming units, 2.461
- self-priming centrifugal pumps, 2.462
- self-releasing couplings, electric motors, 6.20
- semi-open impeller pumps,
 - casings, 2.105
- semiannual inspections, 12.16
- semiguarded enclosures, electric motors, 6.15
- semiopen impellers, 2.115–2.127
- sensitization, 5.10
- sensors, 7.4–7.7
- series operations, centrifugal pumps, 2.367–2.368
- series unit pumps, 2.107
- series water supply systems, 9.13–9.14
- serrated throttle bushings, 2.239–2.240
- service factor ratings
 - adjustable-speed belt drives, 6.172
 - electric motors, 6.25
- service water sewage pumps, 9.33
- settled sewage pumps, 9.32
- settling slurries
 - deposition, 9.332
 - transport systems, 9.345
- sewage marine pumps, 9.236
- sewage pump systems, 9.25
 - bearings, 9.42
 - capacity planning, 9.37
 - collection, 9.26
 - concentrated sludge/scum pumps, 9.34–9.35
 - control systems, 9.40
 - cycle time, 9.38
 - drivers, 9.39
 - grease/oil seals, 2.144
 - head-capacity curves, 9.39
 - operating frequency, 9.38
 - operating speeds, 9.38
 - pipng, 9.41
 - priming systems, 2.464
 - raw sewage pumps, 9.29
 - reliability, 9.38
 - scum pumps, 9.33–9.34
 - seals, 9.41–9.42
 - service water systems, 9.33
 - settled sewage pumps, 9.32
 - sludge pumps, 9.33–9.34
 - surge control, 9.41
 - treatment, 9.26–9.27
 - valves, 9.41
 - vertical, 2.158
 - water-sealing tanks, 2.144
- shafts, 2.132
 - chemical pumps, 9.123
 - critical speed, 6.187
 - critical speeds, 2.132–2.133
 - deflection, 2.134
 - distance sleeves, 2.136
 - drive systems, 6.182
 - spacers, 6.183
 - elongation, vertical pumps, 2.175
 - failures, 2.401, 3.73
 - flexible, 2.133
 - flexible drive, 6.186
 - floating, 6.184
 - hydrokinetic drives, 6.129
 - interstage sleeves, 2.136

- Lomakin effect, 2.135
- materials of construction,
 - 5.29–5.30
- radial load failures, 2.403
- rigid, 2.133, 6.185–6.186
- sizing, 2.135
- sleeves, 2.137
 - O rings, 2.138
 - packing, 2.138
 - renewable, 2.136
- steam turbines, orientation, 6.39
- torsional stress, 6.186
- turbines, 6.80
- shear rate, 8.32
- shear stress, 8.32
- shells, slurry pumps, 9.358, 9.365
- ship service pumps, 9.229
- ship-loading cryogenic pumps, 9.405
- shipping pumps, 12.2
- shop tests, 13.2
- shrouds, centrifugal pumps, profiles,
 - 2.31–2.33, 2.62
- shunt-wound DC motors, 6.8
- shutdown process, waterhammer
 - prevention, 8.103
- shutdown systems, 2.445
- side branch accumulators,
 - displacement pumps, 3.69
- side-suction pumps, 2.106
- sigma, turbines, 6.83
- similitude, 2.20
- simplex steam pumps, 3.40, 3.45
- simplified dynamic analysis, seismic
 - nuclear pumps, 9.308
- single seals, 2.208
- single spring seals, 2.211
- single-acting reciprocating
 - pumps, 3.38
- single-chamber primers, 2.456
- single-curvature vanes, 2.113
- single-end screw pumps, 3.104
- single-row angular contact ball
 - bearings, 2.151
- single-row deep-groove ball
 - bearings, 2.151
- single-shaft gas turbines, 6.90
- single-stage pumps, 2.99
 - axial lengths, 2.29
 - axial thrust, 2.124
- single-stage steam turbines,
 - 6.39, 6.41
 - bearing cases, 6.41
 - casing sealing glands, 6.41
 - efficiencies, 6.47
 - governors, 6.41
 - rotors, 6.41
 - steam chest, 6.41
- single-steam steam turbines,
 - overspeed trip system, 6.41
- single-suction impellers, 2.113,
 - 2.126–2.128
- single-unit adjustable-speed electric
 - drives. *See* electric drives.
- single-volute casing pumps, 2.100
- single-volute pumps, 2.168
- siphon head, pumping systems,
 - 8.25–8.31
- siphons, 4.23, 4.43
 - air, 4.47
 - annular, 4.44
 - standard, 4.44
- site maintenance, 12.2
- size effect on efficiency, centrifugal
 - pumps, 2.24
- sizing
 - centrifugal pumps, 2.28–2.29
 - eddy current couplings, 6.106
 - shafts, 2.135
- sleeve bearings, 2.149
 - electric motors, 6.18
 - power pumps, 3.33
- sleeves
 - O rings, 2.138
 - overhung impellers, 2.138
 - packing, 2.138
 - shafts, 2.136–2.137
- sliding abrasion wear, slurry
 - pumps, 9.364
- slip
 - loss, fluid couplings, 6.139
 - power pumps, 3.5
 - rotary pumps, 3.138–3.139
 - screw pumps, 3.102

- slip eddy current couplings, 6.106
- slip speed, eddy current couplings, 6.100–6.101
- sludge pumps, 9.27, 9.33–9.34
- slurries
 - complex flows, 9.338–9.339
 - equivalent fluid
 - hydraulic gradient, 9.324
 - pressure losses, 9.323
 - flow characteristics, 9.322–9.323
 - inclined flows, 9.342
 - laminar flow, scaling, 9.329
 - particulate abrasiveness, 5.20
 - vertical flows, 9.341
- slurry paper mill pumps, 9.162
- slurry pumps, 9.321–9.322, 9.351–9.352
 - casings, 9.357
 - centrifugal pumps, 2.26
 - coatings, 5.44
 - designing, 9.343–9.345
 - efficiencies, 9.360–9.361
 - hydraulic design, 9.353
 - impellers, 9.357
 - inserts, 5.44
 - liners, 5.44, 9.365
 - materials of construction, 5.43–5.44
 - particle impact wear, 9.364
 - roller bearings, 9.357
 - seals, 9.357
 - shells, 9.358, 9.365
 - sliding abrasion wear, 9.364
 - solids effects, 9.360
 - wear, 9.353, 9.363, 9.365
- smothering glands, 2.147
- solenoid pumps, 3.87
- soleplates, 2.156–2.157, 12.3
- solid casings, 2.102
- solid state adjustable-frequency
 - inverters, adjustable-frequency drives, 6.119–6.120
- solids effects, slurry pumps, 9.360
- solids handling eductors, 4.37
- solids in suspension, solutions, 9.114
 - solids pumps, 9.321, 9.351, 9.369
 - flushing, 9.374
 - maintenance, 9.376
 - materials of construction, 9.371
 - packing wear, 9.372
 - process stream pumping, 9.370
 - surge legs, 9.374, 9.376
 - valves, 9.371–9.372
 - solutions
 - accelerators, 9.115
 - acidic, 9.114
 - aeration, 9.114
 - alkalinity, 9.114
 - concentrations, 9.113–9.114
 - constituents, 9.113
 - inhibitors, 9.115
 - purity, 9.115
 - solides in suspension, 9.114
 - temperatures, 9.114
 - source modification, noise control, 8.113–8.114
 - sources of pump noise, 8.110
 - space shuttle booster pumps, 9.437
 - spacing of nozzle throat, L_{JL} pumps, 4.14
 - spare parts, 12.19
 - specific pump speeds, waterhammer, 8.94
 - specific speed, pumps, 1.4
 - speed changer controls, displacement pumps, 3.76
 - speed characteristic, turbines, 6.86
 - speed control
 - adjustable-speed belt drives, 6.169
 - centrifugal pumps, 2.21–2.23
 - electric motors, 6.23
 - engines, 6.60
 - gear reducers, 6.153
 - hydraulic turbines, runners, 6.82
 - power-driven pumps, 3.75
 - regulation, fluid couplings, 6.136
 - rotary pumps, 3.143
 - steam turbines, 6.43
 - variation, 6.45
 - speed measurements, 13.36

- speed rings, vertical dry-pit pumps, 2.162
- speed-torque curves, ac adjustable-voltage drives, 6.111
- spent fuel pit pumps, PWR plants, 9.283
- spent resin sluicing pumps, PWR plants, 9.283
- spindle proportioning eductors, 4.34
- spiral-bevel gears, 6.147
- splashproof enclosures, electric motors, 6.15
- split casings, 2.102
- split glands, 2.147
- split pusher-type seals, 2.212
- split rigid couplings, 6.175
- split-case fire pumps, 9.58
- split-shaft gas turbines, 6.90
- spring-grid couplings, 6.180
- spur gears, 6.144
- squeeze film effect, 2.252
- squirrel-cage induction motors, 6.4–6.5
- SR brushless dc motors (Switched Reluctance), 6.13
- SSEs (safe shutdown earthquakes), nuclear pumps, 9.301, 9.306
- stability, journal bearings, 2.270–2.273
- stability analyses, bearings, 2.268
- stable head characteristic, 2.334
- stage pieces, 2.108
- stainless steel
 - casings, 5.29
 - shafts, 5.30
 - wear rings, 5.31
- standard datum, shaft pumps, 2.328
- standard siphons, 4.44
- standards
 - composite pumps, 5.60
 - gas turbines, 6.91
- standby liquid control system pumps, BWR plants, 9.285
- standby pumps, auxiliary services, 12.16
- standpipe cooling systems, engines, 6.66
- starters
 - electric motors, 6.27–6.28
 - engines, 6.70–6.71
 - high specific speed centrifugal pumps, 2.364
 - low specific speed centrifugal pumps, 2.361–2.362
 - medium specific speed centrifugal pumps, 2.364
- starting
 - gas turbines, 6.94
 - pumped storage systems, 9.266
 - pumps
 - centrifugal pumps, 12.14
 - positive displacement pumps, 12.15
 - standby pumps, 12.16
 - steam turbine pumps, 12.15
 - waterhammer prevention, 8.102
- static analysis, seismic nuclear pumps, 9.308
- static excitation, synchronous motors, 6.7
- static head
 - pumping systems, 8.13
 - water supply systems, 9.12
- static instability, centrifugal pumps, 2.56
- static load failure, 2.401
- static pressure head, centrifugal pumps, 2.10
- static pressure increases, centrifugal pumps, 2.16
- static pressure losses, centrifugal pumps, 2.14
- static shaft deflection, 2.134
- static stability, centrifugal pumps, 2.56
- static thrust, 2.401
- stationary seals, 2.211
- stationary wearing rings, 2.122
- stators
 - canned motor pumps, 2.315
 - liners, 2.318
 - magnetic bearings, 2.284
 - rotary pumps, 3.124
 - windings, squirrel-cage induction motors, 6.5

- steam chest, single-stage steam turbines, 6.41
- steam consumption, steam pumps, 3.58
- steam ends, steam pumps, 3.40, 3.45, 3.57
- steam heat pumps, 9.256
- steam power plants, 9.73–9.74
 - boiler feed pumps, 9.77
 - capacities, 9.78
 - NPSH, 9.78–9.79
 - booster pumps, 9.84
 - closed cycles, 9.75
 - discharge pressures, 9.85
 - drivers, 9.85–9.87
 - efficiencies, 9.94–9.95
 - head capacity curve slope, 9.85
 - load reduction, transient conditions, 9.79–9.81
 - open cycles, 9.75
- steam pumps, 3.37
 - brake horsepower, 3.58
 - direct acting, 3.40
 - displacement, 3.53
 - duplex, 3.40
 - liquid end, 3.47
 - diameter, 3.56
 - piston type, 3.47–3.48, 3.51
 - plunger type, 3.53
 - valves, 3.52
 - materials of construction, 3.45, 3.47
 - mechanical efficiencies, 3.57
 - piston speed, 3.55
 - simplex, 3.40
 - steam consumption, 3.58
 - steam ends, 3.40, 3.45
 - diameter, 3.57
 - throttle control, 3.75
 - troubleshooting, 12.25
 - water horsepower, 3.59
- steam rates, steam turbines, 6.47
- steam turbine marine pumps, 9.216
- steam turbine pumps, 12.15
- steam turbines, 6.37–6.39
 - control systems, 6.41
 - direct connected, 6.39
 - efficiencies, 6.48
 - energy conversion, 6.46
 - geared, 6.39
 - governors, 6.41
 - impulse stage, 6.39
 - maximum speed rise, 6.45
 - multistage, 6.47
 - operating cost, 6.52
 - overspeed trip system, 6.46
 - reaction stage, 6.40
 - shaft orientation, 6.39
 - single-stage, 6.39
 - speed ranges, 6.43
 - speed variation, 6.45
 - steam rates, 6.47
 - superheat, 6.48, 6.51
- steam turbogenerators
 - auxiliary circulating pumps, 9.228
 - auxiliary condensate pumps, 9.228
 - lubricating oil pumps, 9.228
- steaming out process, paper mill pumps, 9.181
- steep characteristic, 2.334
- stellite-coated wear rings, 5.32
- step wearing rings, 2.119
- stern tube lubricating oil marine pumps, 9.231
- stock, paper mill pumps, 9.166–9.167
- stop pieces, 2.106
- stopping
 - centrifugal pumps, 12.14
 - positive displacement pumps, 12.15
 - steam turbine pumps, 12.15
 - waterhammer prevention, 8.103
- straight line approximation, L/JL pumps, 4.14
- straight-bevel gears, 6.147
- straight-radial-vane high-speed pumps, 2.178
- straight-vane radial impellers, 2.113
- strain on piping systems, 12.9
- strainers
 - piping, 10.32
 - suction end, 12.10
- stress corrosion cracking, chemical pumps, 9.119

- stress limits
 - power pumps, 3.23
 - seismic nuclear pumps, 9.310
- stroke rate, power pumps, 3.6
- structure borne noise, 8.116
- stuffing boxes, 2.139, 2.141
 - air leakage, 2.192
 - gland plates, 2.186
 - lantern rings, 2.141
 - mechanical seals, 2.148
 - packing glands, 2.147
 - packings
 - abrasives, 2.192
 - materials used, 2.187–2.188
 - power pumps, 3.25
 - pressure issues, 2.190–2.191
 - slurry pumps, 9.357
 - smothering glands, 2.147
 - temperature issues, 2.192
 - water-cooled, 2.145
- submergence, suction tank outlet pipes, 10.25
- submergence levels, intakes, 10.25
- submersible enclosures, electric motors, 6.16
- submersible motor-driven wet-pit pumps, 2.177
- submersible raw sewage pumps, 9.29
- submersible turbine irrigation pumps, 9.47
- subscript designations, centrifugal pumps, 2.8
- subsea multiphase pumps, 3.118
- subsurface hydraulic oil pumps, 9.386–9.387
- subsurface progressing cavity oil pumps, 9.392
- subsurface reciprocating hydraulic oil pumps, 9.390–9.391
- subsurface vortices, 10.40, 10.49
- sucker rod oil well pumps, 9.378
- sucker rod stretch, oil well pumps, 9.385
- suction case, vertical turbine pumps, 2.164
- suction elbows, 8.66
- suction eye, impellers, 2.118
- suction feed helicopter fuel pumps, 9.411
- suction flanges, 2.110
- suction head, units of measure, 13.3
- suction head rings, leakage joints, 2.118
- suction lift, 10.13, 13.3
- suction manifolds, power pumps, 3.27
- suction nozzles, centrifugal pumps, 2.58
- suction piping, water supply systems, 9.9, 12.8
- suction pits
 - eddies, 10.24
 - environmental issues, 10.18
 - intakes, submergence levels, 10.25
 - model tests, 10.22
 - piping, 10.28–10.29
 - vortices, 10.22–10.23
- suction recirculation, 2.370, 2.398, 2.400
- suction strainers, 3.134, 12.10
- suction stroke, reciprocating pumps, 3.38
- suction tanks, outlet pipes, submergence, 10.25
- suction throttling, centrifugal pumps, 2.366
- suction valves
 - power pumps, 3.27
 - unloading, displacement pumps, 3.76–3.77
- suction-specific speed
 - centrifugal pumps, 2.352
 - high-energy pumps, 2.84–2.85
- suggested test procedures, 13.12–13.13
- sulfide stress corrosion cracking, 5.7
- sulfuric acid applications, composite pumps, 5.57
- sulfuric acid chemical pumps, 9.116
- sump pumps, 2.163, 9.54, 9.209–9.210
- superheat, steam turbines, 6.48, 6.51
- superstructure, pumping stations, 9.54

support systems, 2.155, 2.163
 surface treatments, fatigue
 correction, 5.26
 surface wash pumps, water
 treatment plants, 9.19
 surface water pumps, 9.3
 surge chambers, 12.12
 surge control, sewage systems, 9.41
 surge legs, solids pumps,
 9.374, 9.376
 surge protection, piping, 10.31
 surge suppressors,
 waterhammer, 8.100
 surge tanks
 pumped storage, 9.271
 waterhammer prevention,
 8.102–8.103
 suspended solids, 5.19
 swirl, 10.42
 synchronous motors, 6.6
 direct-connected exciters, 6.7
 motor-generated exciters, 6.7
 static excitation, 6.7
 system design, mining pumps, 9.205
 system-head curves
 pumping systems, 8.13
 water supply systems, 9.10

T

tandem seals, 2.209
 tank-cleaning marine pumps, 9.249
 tanks, water pressure booster
 systems, 9.456
 tare of water consumption, 9.5
 technical bid evaluations, 11.25
 technical purchase
 recommendations, 11.29
 technical specifications,
 RFQs, 11.9–11.10
 telemetry pump control systems, 7.9
 temper annealing, 5.6
 temperature issues
 fluids, rotary pumps, 3.135

packings, 2.192
 pumping system flow rates, 8.77
 rise, centrifugal pumps, 2.372
 solutions, 9.114
 test models, suction pits, 10.22
 testing checklists, RFQs, 11.17
 testing pumps, 13.2
 accuracy, 13.8
 cavitation, 13.10
 Cipoletti weirs, 13.19, 13.22
 current meters, 13.26
 data recording, 13.38
 differential pressure meters, 13.15
 discharge measurement, 13.14
 flow nozzles, 13.16
 flumes, 13.23–13.24
 head area meters, 13.18
 head measurements, 13.27–13.28
 bourdon gages, 13.35
 differential mercury gages, 13.34
 mercury gages, 13.34
 water gages, 13.33
 instrumentation, 13.8
 operating conditions, 13.8–13.9
 orifice meters, 13.17
 pitot tubes, 13.18
 pitot static tubes, 13.18
 power measurements, 13.35
 pressure transducers, 13.18
 quantity meters, 13.14
 rate of flow meters, 13.15
 recommended procedure,
 13.12–13.13
 seismic nuclear pumps, 9.309
 speed, 13.37–13.38
 speed measurements, 13.36
 tolerances, 13.8
 V notch weirs, 13.23
 venturi meters, 13.15
 volumetric meters, 13.14
 weighing meters, 13.14
 weirs, 13.19, 13.22
 TEWAC electric motors
 (totally enclosed
 water-to-air-cooled), 6.113
 thermal issues
 displacement pumps, 3.72
 low flow rates, 2.438

- thermoplastic composite pumps, 5.51
- thermoset composite pumps, 5.52
- thixotropic liquids, 8.33, 9.188
- thoma cavitation parameter,
 - centrifugal pumps, 2.352
- three-body wear, 5.16, 5.18
- throat bushings, axially split casings, 2.141
- throat inlets, L/JL pumps, 4.15
- throttle bushings, 2.191
- throttle control, direct-acting pumps, 3.75
- throttling orifices, head losses, 8.77
- through hardening gears, 6.149
- thrust balance, canned motor pumps, 2.319–2.321
- thrust bearings, 2.149–2.150
- tidal river water, salinity, 5.37
- tilted pad bearings, 2.256, 2.259
- time history analysis, seismic nuclear pumps, 9.307
- time history of acceleration, seismic nuclear pumps, 9.307
- timed rotary pumps, 3.124
- timed rotor screw pumps, 3.103, 3.106–3.107
- Tirastat II controllers, wound-rotor induction controllers, 6.116
- tolerance
 - testing pumps, 13.8
 - wearing rings, 2.123–2.124
- torque
 - centrifugal pumps, 2.359–2.360
 - high-energy pumps, 2.72–2.73
 - hydraulic turbines, 6.86
 - oil well pumps, 9.382
 - power pumps, 3.8
 - variable frequency drives, 3.9
- torsional stress, shafts, 6.186
- tortuous-path precipitators, gas turbines, 6.94
- total dynamic head, centrifugal pumps, 2.10
- total head, 13.4
 - branch-line pumping systems, 8.90
 - pumping systems, 8.6–8.9
- total suction head
 - drainage pumps, 9.52
 - irrigation pumps, 9.52
- total suction lift
 - drainage pumps, 9.52
 - irrigation pumps, 9.52
- totally enclosed enclosures, electric motors, 6.16
- touchdown bearings. *See* catcher bearings.
- transducers, pump control systems, 7.7
- transfer function, magnetic bearings, 2.283
- transfer systems, agriculture, 9.441–9.442
- transient loads, magnetic bearings, 2.283
- transient operation, centrifugal pumps, 2.379–2.381
- transient power failures, centrifugal pumps, 2.376
- transient speeds, pumped storage, 9.263–9.264
- transmission systems, 6.175–6.176, 6.191–6.192
- transmittal torque, sealless magnetic drive pumps, 2.303
- transmitters, control systems, 7.7
- trashracks, 10.14–10.16
- treatment sewage systems, 9.26–9.27
- tribology, 5.14
- troubleshooting
 - axial thrust, 2.401
 - cavitation, 2.397
 - centrifugal pumps,
 - 12.20, 12.22–12.23
 - displacement pumps, 3.63
 - gear units, 6.161–6.164
 - pressure pulsations, 2.403
 - radial thrust, 2.402
 - reciprocating pumps, 12.24
 - recirculation, 2.398
 - rotary pumps, 12.23
 - steam pumps, 12.25

TRS (test response spectrum),
 seismic nuclear pumps, 9.307
 true liquids, 8.33
 tube turbines, 6.80
 tubing shrink, oil well pumps, 9.385
 tubular diaphragm pumps, 3.91
 tuning magnetic bearings, 2.291
 turbine chemical pumps, 9.121
 turbine drainage pumps, 9.52
 turbine irrigation pumps, 9.52
 turbines
 adjustable blade propeller, 6.79
 affinity laws, 6.84
 cavitation, 6.83
 centrifugal pump applications,
 2.385–2.387
 choosing type, 6.86
 fixed blade propeller, 6.79
 Francis, 6.79
 power shafts, 6.80
 gas, 6.89
 Brayton cycle, 6.89
 Joule cycle, 6.89
 horizontal shafts, 6.80
 hydraulic, 6.78–6.79
 flow units, 6.80
 power shafts, 6.80
 torque, 6.86
 impulse, 6.79
 inclined shaft, 6.80
 inpulse, 6.78
 power recovery, 6.83
 runners, 6.79
 sigma, 6.83
 speed characteristic, 6.86
 steam turbines, 6.37
 tube, 6.80
 vertical propeller, 6.80
 turbopumps, space shuttle booster
 pumps, 9.434
 turbulence, journal bearings, 2.252
 turbulent flow, 8.32, 9.327
 turndown, fluid couplings, 6.136
 turning vanes, suction pits, 10.13
 twin volute pumps, 2.101

two-body wear, 5.16
 two-chamber primers, 2.457
 types of wear, 5.13

U

unbalanced impellers, 2.432–2.433
 unbalanced power pumps, 3.18–3.19
 unbalanced seals, 2.201, 2.211
 unbalanced valves, duplex steam
 pumps, 3.43
 underfiling vanes, centrifugal
 pumps, 2.343
 underwater vortexing, 10.22
 uniform corrosion, chemical
 pumps, 9.118
 unit load capabilities, magnetic
 bearings, 2.284
 units of measure
 discharge head, 13.4
 efficiencies, 13.7
 flooded suction, 13.3
 head, 13.3
 NPSH, 13.5
 suction head, 13.3
 total head, 13.4
 total suction lift, 13.3
 velocity head, 13.3
 volume, 13.3
 water power, 13.6
 unloader mechanisms, displacement
 pump suction valves, 3.77
 unstable characteristic, 2.334
 untimed arrangement, rotary
 pumps, 3.124
 untimed rotor screw pumps, 3.103,
 3.107–3.108
 USCS (U.S. Customary
 System), 2.327
 user interfaces, magnetic
 bearings, 2.292
 UV exposure, composite pumps, 5.50

V

- V belts, adjustable-speed belt drives, 6.170
- V notch weirs, 13.23
- vacuum primers, 2.458
- valve covers, power pumps, 3.28
- valve dynamics, power pumps, 3.14
- valve friction, power pumps, 3.14
- valve springs, power pumps, 3.16
- valve-throttling constant speed control systems, 7.10
- valves
 - control systems, 7.14–7.15
 - control valves, 7.15
 - controlled closure, waterhammer prevention, 8.100
 - drainage pumps, 9.48
 - duplex steam pumps, 3.42–3.44
 - flow coefficients, 8.56–8.58, 8.62–8.63
 - frictional losses, 8.54
 - irrigation pumps, 9.48
 - liquid ends, steam pumps, 3.52
 - power pumps, 3.12–3.13, 3.15, 3.27
 - sewage systems, 9.41
 - simplex steam pumps, 3.45
 - solids pumps, 9.371–9.372
- vane pumps, 3.123
 - capacity, 3.140
 - rigid, 3.126
- vane tips
 - centrifugal pumps
 - clearance, 2.337
 - reducing size, 2.342
 - erosion, 5.12
- vaned diffusers, centrifugal pumps, 2.43–2.44
- vanes
 - high-energy pumps, blade combinations, 2.76–2.77
 - impellers, single-curvature, 2.113
- vapor lock, aircraft fuel pumps, 9.419
- vapor phase cooling systems, engines, 6.68
- vapor pressure
 - rotary pumps, 3.138
 - screw pumps, 3.110
- variable frequency drives, torque, 3.9
- variable orifices, bypass systems, 2.448
- variable speed drive water pressure booster systems, 9.449–9.452
- variable speed water supply systems, 9.14
- variable static head, pumping systems, 8.15
- variable system resistance, pumping systems, 8.16
- variable-displacement piston hydraulic pumps, variable water flow, 6.196
- variable-speed drivers, sewage systems, 9.40
- variable-torque loads, eddy current couplings, 6.101
- velocity caps, intakes, 10.18
- velocity diagrams, centrifugal pumps, 2.13, 2.19
- velocity head
 - centrifugal pumps, 2.10
 - pumping systems, 8.5
 - units of measure, 13.3
- velocity sensors, 2.421–2.424
- velocity-compounded single-stage steam turbines, 6.46
- Vena Contracta, 7.23, 2.448
- vendor clarification meetings, 11.25
- vendor data requirement forms, RFQs, 11.17
- vents
 - pipng systems, 12.11
 - valves, 2.460
- Venturi meters, 13.15
- Venturi tubes, 2.449
- vertical condensate pumps, 9.96
- vertical dry-pit pumps, 2.158–2.160
- vertical eddy current couplings, 6.104
- vertical flows, slurries, 9.341
- vertical operations, couplings, 6.182
- vertical propeller pumps, 2.166–2.167
- vertical propeller turbines, 6.80

- vertical pumps
 - axial thrust, 2.171, 2.172
 - foundation loads, 2.175
 - shaft elongation, 2.175
 - support systems, 2.163
 - vertical sewage pumps, 2.158
 - vertical shaft pumps, 2.99, 2.328
 - vertical single-suction pumps, 2.160–2.162
 - vertical turbine pumps, 2.97, 2.163
 - impellers, 2.165
 - suction case, 2.164
 - vertical wet pit pumps, 2.163, 2.170, 12.3
 - vertically split casings, 2.102
 - vibration
 - centrifugal pumps, 2.382
 - piping, 10.31
 - vibration analysis, 2.419–2.424
 - antifriction bearings, 2.434
 - baseplates, 2.435
 - impellers, 2.432
 - symptom diagnosis, 2.425, 2.430–2.431
 - vibration isolation, engines, 6.74
 - viscosity
 - bearing performance, 2.258
 - centrifugal pumps, 2.25
 - drag losses, journal bearings, 2.253
 - food/beverage pump liquids, 9.188
 - heat generation, cylindrical bearings, 2.254
 - petroleum pump liquids, 9.150–9.154
 - rotary pumps, 3.132, 3.135
 - power losses, 3.145
 - screw pumps, 3.113
 - voltage ratings, electric motors, 6.22
 - volume
 - displacement flow control, 3.76
 - flow rate. *See* flow rate.
 - units of measure, 13.3
 - volumetric efficiency
 - centrifugal pumps, 2.50, 2.334
 - power pumps, 3.6–3.7
 - rotary pumps, 3.146, 3.149
 - volumetric meters, 13.14
 - volute pumps, 2.97, 2.168
 - cellar drainers, 2.169
 - drainage pumps, 9.46, 9.52
 - irrigation pumps, 9.46, 9.52
 - volute-casing pumps, 2.99
 - volutes, centrifugal pumps, 2.41–2.43, 2.67
 - vortex pumps, 2.389
 - vortices
 - correcting, 10.52
 - free surface, 10.39
 - subsurface, 10.40
 - suction pits, 10.22–10.23
- ## W
- walking beams, mechanically driven
 - diaphragm pumps, 3.87
 - warm-up flow piping, 12.11
 - wash liquors, paper mill pumps, 9.165
 - wash water pumps, water treatment plants, 9.18
 - waste heat marine pumps, 9.231
 - waste pumps, 9.321
 - waste treatment. *See* sewage systems.
 - water as bearing lubricant, 2.152
 - water column separation,
 - waterhammer, 8.100
 - water consumption rates, water supply systems, 9.6
 - water distillation marine pumps, 9.234
 - water flooding of oil fields, gas turbines, 6.95
 - water flushed wearing rings, 2.119
 - water gages, measuring head, 13.33
 - water horsepower, steam pumps, 3.59
 - water injection pumps, 9.148, 9.150
 - water power, units of measure, 13.6
 - water pressure booster systems, 9.447

- constant speed multipump, 9.454
- control panels, 9.455
- demand profiles, 9.457–9.460
- limited storage constant speed
 - multipump, 9.456
- materials of construction, 9.461
- sizing tanks, 9.456
- variable speed drives, 9.449–9.452
- water supply systems
 - abrasiveness, 9.9
 - alkalinity, 9.9
 - capacities, 9.6
 - consumption rates, 9.6
 - demand fluctuations, 9.5
 - drivers, 9.10
 - frictional losses, 9.12
 - NPSH, 9.12
 - parallel/series operation, 9.13–9.14
 - pressure differential, 9.12
 - pumping time variations, 9.6
 - static head, 9.12
 - suction/discharge piping, 9.9
 - system-head curves, 9.10
 - variable speed units, 9.14
- water treatment plants, 9.15
 - booster pumps, 9.19
 - carbon slurry pumps, 9.17
 - coagulant feed pumps, 9.16
 - fluoride pumps, 9.17
 - high-service pumps, 9.19
 - low lift pumps, 9.16
 - plant water pumps, 9.18
 - sampling pumps, 9.18
 - surface wash pumps, 9.19
 - wash water pumps, 9.18
- water-cooled eddy current couplings,
 - enclosures, 6.105
- water-cooled stuffing boxes, 2.145
- water-jet exhausters, 4.41
- water-sealing tanks, sewage
 - pumps, 2.144
- waterhammer, 8.91
 - air chambers, 8.101, 8.103
 - basic assumptions, 8.92
 - check valves, 8.98, 8.102
 - control devices, 8.103, 8.105
 - controlled valve closure, 8.100
 - controlled valve opening, 8.102
 - discharge line profiles, 8.93
 - flywheel effect, 8.94
 - high head systems, 8.93
 - low head systems, 8.93
 - mining pumps, 9.208
 - nonreverse ratchets, 8.102
 - pipeline sizes, 8.94
 - pump motor failure, 8.95–8.96
 - quick opening slow closing
 - valves, 8.101
 - reducing effects, 8.93, 8.95
 - rigid water column theory, 8.93
 - solving problem, 8.95
 - specific pump speed, 8.94
 - surge suppressors, 8.100
 - surge tanks, 8.102–8.103
 - water column separation, 8.100
 - wave velocity, 8.93
- waterwheels, 1.2
- wave velocity, waterhammer, 8.93
- wear, 5.13
 - abrasive wear, 5.16, 5.18
 - adhesive wear, 5.14
 - slurry pumps, 9.353, 9.363, 9.365
- wearing rings, 2.118, 5.30
 - axial clearance, 2.121
 - axial thrust, 2.125
 - clearances, 2.123–2.124, 2.336
 - dam-type, 2.120
 - flat, 2.119
 - inspection ports, 2.120
 - L-type, 2.119
 - labyrinth, 2.119
 - mounting, 2.122
 - stationary, 2.122
 - step, 2.119
 - tolerance, 2.123–2.124
 - water flushed, 2.119
- wearing-ring hubs, 2.118
- weather protected enclosures,
 - electric motors, 6.16

weather-protected eddy current
couplings, 6.105
weighing meters, 13.14
weirs, 13.19, 13.22
weldments, chemical pumps, 9.121
well pumps, 9.21–9.22
well water pumps, 9.259
wet pit once through intakes, 10.5
wet pit raw sewage pumps, 9.29
wet vacuum pumps, 2.458
wet-pit pumps, 2.99
whirl, bearings, 2.266
whirl instability, cylindrical
bearings, 2.254
white liquor, paper mill
pumps, 9.162
wire mesh screens, head losses, 8.71
wire-to-liquid efficiency, 2.329
wire-to-water efficiency, 2.329
wood-block transmissions, 6.171
working barrel, power pumps, 3.22

worm gears, 6.148
wound-rotor induction motors,
6.5–6.6
contact secondary controls, 6.116
FVNR starters (full voltage
nonreversing), 6.111
liquid rheostat controls,
6.112–6.113
Tirastat II controllers, 6.116
wrist pin bearings, power
pumps, 3.33
wrist pins, power pumps, 3.31

Z

zero-bevel gears, 6.147
ZPA (zero period acceleration),
seismic nuclear pumps, 9.307