

# Coolselector2

Coolselector2	1.1.1.44.	4.5.1.1.2
	8	2016

## 1

R404A	50.00 kW
2094 kg/h	94.04 kW
-32.0 °C	45.0 °C
1.882 bar	20.63 bar
7.0 K	0.5 K
5.0 K	0 K
82.0 °C	Без переохлаждения
DX-	
: DIN-EN, /DIN-EN 22 (6/7")	

18.75 bar
77.7 K

1. T : TE 55 - 13	
	55.92 kW
	13.98 kW
	89 %
	18.75 bar
	77.7 K
	1.26 m/s

# Coolselector2

2

:	R404A	:	50.00 kW
:	1258 kg/h	:	56.50 kW
:	-32.0 °C	:	45.0 °C
:	1.882 bar	:	20.63 bar
:	7.0 K	:	0.5 K
:	5.0 K	:	37.0 K
:	82.0 °C		
:	DX-		
:	: DIN-EN, /DIN-EN 18 (23")		

Переохлаждение в ЭКО

18.75 bar
77.7 K

<b>1. T : TE 12 - 7 NS 16</b>	
	50.89 kW
	12.72 kW
	98 %
	18.75 bar
	77.7 K
	0.99 m/s

# Coolselector2

3

:	R404A	:	50.00 kW
:	1258 kg/h	:	56.50 kW
:	-32.0 °C	:	45.0 °C
:	1.882 bar	:	20.63 bar
:	7.0 K	:	0.5 K
:	5.0 K	:	37.0 K
:	82.0 °C		
:	DX-		
:	: DIN-EN, /DIN-EN 22 (6/7")		

  

18.75 bar
77.7 K

<b>1. T : TE 55 - 13</b>		
	104.7 kW	<b>Работа ТРВ без учета переохлаждения!</b>
	26.17 kW	
	48 %	
	18.75 bar	
	77.7 K	
	0.63 m/s	

# Coolselector2

