



QUOTATION TABLE

Guangzhou Jinlun Electric Equipment Co.,Ltd
28,Tuanjie Rd.,Tuanjie village,Xinhua town,Huadu
district,Guangzhou,Guangdong province,China 510800
Tel: 86-20-23354278
Fax:86-20-61824683
Email: meeting9@heatpumpchina.com
Web:www.heatpumpchina.com

Date :
7/May/13

To Buyer	Phone	Email	Seller:
			GUANGZHOU JINLUN ELECTRIC EQUIPMENT CO.,LTD
Contact	Fax	Messenger	Contact :
			Sam Huang

Subject :	Quotation for Air Source Heat Pumps	P/N :
-----------	-------------------------------------	-------

Payment Term: By T/T,30% total amount paid before production,the balance paid before delivery.

Shipment Term: FOB / Guangzhou

Shipment Way: By sea


Leadtime: 10 days upon the receipt of the advance payment(actually according to your order quantity).


Packaging: Export standard plywooden case with water-proof film inside.


Validity of Quotation: 3 months

Note: MOQ is 5pcs in total.

AIR SOURCE HEAT PUMP

DISCRPTION	PARAMETER	TTL QTY (CASES)	TTL QTY (PCS)	Unit price (USD/PC)	MOQ (PCS)	Packaging
Model No.	MD10D	1	1	\$533.00	5	Export standard plywooden case with water-proof film inside. 75pcs for 20' container. 141pcs for 40' container 
Installation	Freestanding					
Housing material	Spray coating					
Rated heating capacity	3.2kw					
Hot water supply	80L/h					
Average heating input power	0.8kw					
Rated heating input current	4A					
Max outlet water temp	60℃					
COP	4.0					
Power	220V/50HZ/1PHASE					
Noise	≤40Db(a)					
Dimension(W*D*H) in mm	1140*360*550					
Packing size(W*D*H) in mm	1200*400*700					
Net weight & Gross weight(kg)	62/75					
Refrigerant	R417A					
Working ambient Temp.	(-15)℃~45℃					
Controller	LCD intelligence					
Compressor	Panasonic					
Air source heat exchanger (Evaporator)	Type					
	Fan type					
Hot water side heat exchanger (Condenser)	Type					
	Water flow					
	Pipe size					

DISCRPTION	PARAMETER	TTL QTY (CASES)	TTL QTY (PCS)	Unit price (USD/PC)	MOQ (PCS)	Packaging
Model No.	MD15D	1	1	\$584.00	5	Export standard plywooden case with water-proof film inside. 75pcs for 20' container. 141pcs for 40' container 
Installation	Freestanding					
Housing material	Spray coating					
Rated heating capacity	5kw					
Hot water supply	120L/h					
Average heating input power	1.2kw					
Rated heating input current	6A					
Max outlet water temp	60℃					
COP	4.0					
Power	220V/50HZ/1PHASE					
Noise	≤40Db(a)					
Dimension(W*D*H) in mm	1140*360*550					
Packing size(W*D*H) in mm	1200*400*700					
Net weight & Gross weight(kg)	62/75					
Refrigerant	R417A					
Working ambient Temp.	(-15)℃~45℃					
Controller	LCD intelligence					
Compressor	Panasonic					
Air source heat exchanger (Evaporator)	Type					
	Fan type					
Hot water side heat exchanger (Condenser)	Type					
	Water flow					
	Pipe size					

DISCRPTION	PARAMETER	TTL QTY (CASES)	TTL QTY (PCS)	Unit price (USD/PC)	MOQ (PCS)	Packaging
Model No.	MD20D	1	1	\$642.00	5	Export standard plywooden case with water-proof film inside. 75pcs for 20' container. 141pcs for 40' container 
Installation	Freestanding					
Housing material	Spray coating					
Rated heating capacity	7kw					
Hot water supply	160L/h					
Average heating input power	1.84kw					
Rated heating input current	8A					
Max outlet water temp	60℃					
COP	4.0					
Power	220V/50HZ/1PHASE					
Noise	≤40Db(a)					
Dimension(W*D*H) in mm	1140*360*550					
Packing size(W*D*H) in mm	1200*400*700					
Net weight & Gross weight(kg)	77/90					
Refrigerant	R417A					
Working ambient Temp.	(-15)℃~45℃					
Controller	LCD intelligence					
Compressor	Panasonic					
Air source heat exchanger (Evaporator)	Type					
	Fan type					
Hot water side heat exchanger (Condenser)	Type					
	Water flow					
	Pipe size					







QUOTATION TABLE

Guangzhou Jinlun Electric Equipment Co.,Ltd
28,Tuanjie Rd.,Tuanjie village,Xinhua town,Huadu
district,Guangzhou,Guangdong province,China 510800
Tel: 86-20-23354278
Fax: 86-20-61824683
Email: meeting9@heatpumpchina.com
Web:www.heatpumpchina.com

Date :

7/May/13

DISCRIPTION		PARAMETER	TTL QTY (CASES)	TTL QTY (PCS)	Unit price (USD/PC)	MOQ (PCS)	Packaging
Model No.		MD30D-1	1	1	\$935.00	5	Export standard plywooden case with water-proof film inside. 40pcs for 20' container. 82pcs for 40' container 
Installation		Freestanding					
Housing material		Spray coating					
Rated heating capacity		12kw					
Hot water supply		280L/h					
Average heating input power		2.98kw					
Rated heating input current		13A					
Max outlet water temp		60℃					
COP		4.0					
Power		220V/50HZ/1PHASE					
Noise		≤40Db(a)					
Dimension(W*D*H) in mm		1120*490*710					
Packing size(W*D*H) in mm		1190*520*865					
Net weight & Gross weight(kg)		102/120					
Refrigerant		R417A					
Working ambient Temp.		(-15)℃~45℃					
Controller		LCD intelligence					
Compressor		Panasonic					
Air source heat exchanger (Evaporator)	Type	Finned heat exchanger	1	1	\$1,073.00	5	Export standard plywooden case with water-proof film inside. 40pcs for 20' container. 82pcs for 40' container 
	Fan type	Axial flow fan					
Hot water side heat exchanger (Condenser)	Type	Double pipe heat exchanger					
	Water flow	3000L/h					
	Pipe size	25DN					
Model No.		MD30D-2					
Installation		Freestanding					
Housing material		Spray coating					
Rated heating capacity		12kw					
Hot water supply		280L/h					
Average heating input power		2.98kw					
Rated heating input current		13A/6A					
Max outlet water temp		60℃					
COP		4.0					
Power		220V/380V/50HZ,1/3ph					
Noise		≤45Db(a)					
Dimension(W*D*H) in mm		1120*490*710					
Packing size(W*D*H) in mm		1190*520*865					
Net weight & Gross weight(kg)		102/120					
Refrigerant		R417A					
Working ambient Temp.		(-19)℃~45℃					
Controller		LCD intelligence					
Compressor		Copeland					
Air source heat exchanger (Evaporator)	Type	Finned heat exchanger	1	1	\$1,363.00	5	Export standard plywooden case with water-proof film inside. 20pcs for 20' container. 42pcs for 40' container. Note:Must be fulfilled with a few MD20D and MD30D. 
	Fan type	Axial flow fan					
Hot water side heat exchanger (Condenser)	Type	Double pipe heat exchanger					
	Water flow	5000L/h					
	Pipe size	25DN					
Model No.		MD40D					
Installation		Freestanding					
Housing material		Spray coating					
Rated heating capacity		15kw					
Hot water supply		350L/h					
Average heating input power		3.78kw					
Rated heating input current		15A/7A					
Max outlet water temp		60℃					
COP		4.2					
Power		220V/380V/50HZ,1/3ph					
Noise		≤55Db(a)					
Dimension(W*D*H) in mm		1120*490*1260					
Packing size(W*D*H) in mm		1190*520*1425					
Net weight & Gross weight(kg)		142/160					
Refrigerant		R417A					
Working ambient Temp.		(-19)℃~45℃					
Controller		LCD intelligence					
Compressor		Copeland					
Air source heat exchanger (Evaporator)	Type	Finned heat exchanger	1	1	\$1,333.00	5	Export standard plywooden case with water-proof film inside. 20pcs for 20' container. 42pcs for 40' container. Note:Must be fulfilled with a few MD20D and MD30D. 
	Fan type	Axial flow fan					
Hot water side heat exchanger (Condenser)	Type	Double pipe heat exchanger					
	Water flow	5000L/h					
	Pipe size	25DN					
Model No.		MD50D					
Installation		Freestanding					
Housing material		Spray coating					
Rated heating capacity		18.6kw					
Hot water supply		400L/h					
Average heating input power		4.6kw					
Rated heating input current		8A					
Max outlet water temp		60℃					
COP		4.2					
Power		380V/50HZ/3PHASE					
Noise		≤55Db(a)					
Dimension(W*D*H) in mm		1120*490*1260					
Packing size(W*D*H) in mm		1190*520*1425					
Net weight & Gross weight(kg)		152/170					
Refrigerant		R417A					
Working ambient Temp.		(-19)℃~45℃					
Controller		LCD intelligence					
Compressor		Copeland					
Air source heat exchanger (Evaporator)	Type	Finned heat exchanger					
	Fan type	Axial flow fan					
Hot water side heat exchanger (Condenser)	Type	Double pipe heat exchanger					
	Water flow	5000L/h					
	Pipe size	25DN					



QUOTATION TABLE

Guangzhou Jinlun Electric Equipment Co.,Ltd
28,Tuanjie Rd.,Tuanjie village,Xinhua town,Huadu
district,Guangzhou,Guangdong province,China 510800
Tel: 86-20-23354278
Fax:86-20-61824683
Email: meeting9@heatpumpchina.com
Web:www.heatpumpchina.com

Date :

7/May/13

DISCRIPTION		PARAMETER	TTL QTY (CASES)	TTL QTY (PCS)	Unit price (USD/PC)	MOQ (PCS)	Packaging
Model No.		MD60D-1	1	1	\$1,600.00	5	Export standard plywooden case with water-proof film inside. 20pcs for 20' container. 42pcs for 40' container. Note:Must be fulfilled with a few MD20D and MD30D.
Installation		Freestanding					
Housing material		Spray coating					
Rated heating capacity		21kw					
Hot water supply		500L/h					
Average heating input power		5.2kw					
Rated heating input current		12A					
Max outlet water temp		60℃					
COP		4.2					
Power		380V/50HZ/3PHASE					
Noise		≤55Db(a)					
Dimension(W*D*H) in mm		1120*490*1260					
Packing size(W*D*H) in mm		1190*520*1425					
Net weight & Gross weight(kg)		172/190					
Refrigerant		R417A					
Working ambient Temp.		(-19)℃~45℃					
Controller		LCD intelligence					
Compressor		Copeland					
Air source heat exchanger (Evaporator)	Type	Finned heat exchanger					
	Fan type	Axial flow fan					
Hot water side heat exchanger (Condenser)	Type	Double pipe heat exchanger					
	Water flow	6000L/h					
	Pipe size	25DN					
DISCRIPTION		PARAMETER	TTL QTY (CASES)	TTL QTY (PCS)	Unit price (USD/PC)	MOQ (PCS)	Packaging
Model No.		MD60D-2	1	1	\$2,116.00	5	Export standard plywooden case with water-proof film inside. 22pcs for 20' container. 46pcs for 40' container. Note:Must be fulfilled with a few MD20D and MD30D.
Installation		Freestanding					
Housing material		Spray coating					
Rated heating capacity		25kw					
Hot water supply		600L/h					
Average heating input power		6kw					
Rated heating input current		18A					
Max outlet water temp		60℃					
COP		4.2					
Power		380V/50HZ/3PHASE					
Noise		≤60Db(a)					
Dimension(W*D*H) in mm		1390*760*750					
Packing size(W*D*H) in mm		1460*790*910					
Net weight & Gross weight(kg)		220/240					
Refrigerant		R417A					
Working ambient Temp.		(-19)℃~45℃					
Controller		LCD intelligence					
Compressor		Copeland					
Air source heat exchanger (Evaporator)	Type	Finned heat exchanger					
	Fan type	Axial flow fan					
Hot water side heat exchanger (Condenser)	Type	Double pipe heat exchanger					
	Water flow	7000L/h					
	Pipe size	32DN					
DISCRIPTION		PARAMETER	TTL QTY (CASES)	TTL QTY (PCS)	Unit price (USD/PC)	MOQ (PCS)	Packaging
Model No.		MD100D	1	1	\$2,667.00	5	Export standard plywooden case with water-proof film inside. 11pcs for 20' container. 23pcs for 40' container. Note:Must be fulfilled with a few MD20D and MD30D.
Installation		Freestanding					
Housing material		Spray coating					
Rated heating capacity		36.8kw					
Hot water supply		800L/h					
Average heating input power		9.2kw					
Rated heating input current		18A					
Max outlet water temp		60℃					
COP		4.2					
Power		380V/50HZ/3PHASE					
Noise		≤70Db(a)					
Dimension(W*D*H) in mm		1440*760*1060					
Packing size(W*D*H) in mm		1500*800*1200					
Net weight & Gross weight(kg)		310/360					
Refrigerant		R417A					
Working ambient Temp.		(-19)℃~45℃					
Controller		LCD intelligence					
Compressor		Copeland					
Air source heat exchanger (Evaporator)	Type	Finned heat exchanger					
	Fan type	Axial flow fan					
Hot water side heat exchanger (Condenser)	Type	Double pipe heat exchanger					
	Water flow	12000L/h					
	Pipe size	32DN					
DISCRIPTION		PARAMETER	TTL QTY (CASES)	TTL QTY (PCS)	Unit price (USD/PC)	MOQ (PCS)	Packaging
Model No.		MD150D	1	1	\$3,200.00	5	Export standard plywooden case with water-proof film inside. 11pcs for 20' container. 23pcs for 40' container. Note:Must be fulfilled with a few MD20D and MD30D.
Installation		Freestanding					
Housing material		Spray coating					
Rated heating capacity		42kw					
Hot water supply		1000L/h					
Average heating input power		10.5kw					
Rated heating input current		24A					
Max outlet water temp		60℃					
COP		4.2					
Power		380V/50HZ/3PHASE					
Noise		≤70Db(a)					
Dimension(W*D*H) in mm		1440*760*1060					
Packing size(W*D*H) in mm		1500*800*1200					
Net weight & Gross weight(kg)		340/390					
Refrigerant		R417A					
Working ambient Temp.		(-19)℃~45℃					
Controller		LCD intelligence					
Compressor		Copeland					
Air source heat exchanger (Evaporator)	Type	Finned heat exchanger					
	Fan type	Axial flow fan					
Hot water side heat exchanger (Condenser)	Type	Double pipe heat exchanger					
	Water flow	12000L/h					
	Pipe size	32DN					



QUOTATION TABLE

Guangzhou Jinlun Electric Equipment Co.,Ltd
28,Tuanjie Rd.,Tuanjie village,Xinhua town,Huadu
district,Guangzhou,Guangdong province,China 510800
Tel: 86-20-23354278
Fax:86-20-61824683
Email: meeting9@heatpumpchina.com
Web:www.heatpumpchina.com

Date :

7/May/13

DISCRIPTION	PARAMETER	TTL QTY (CASES)	TTL QTY (PCS)	Unit price (USD/PC)	MOQ (PCS)	Packaging
Model No.	MD200D	1	1	\$5,333.00	5	Export standard plywooden case with water-proof film inside. 5pcs for 20' container. 11pcs for 40' container.
Installation	Freestanding					
Housing material	Spray coating					
Rated heating capacity	72kw					
Hot water supply	1600L/h					
Average heating input power	19kw					
Rated heating input current	35A					
Max outlet water temp	60℃					
COP	4.5					
Power	380V/50HZ/3PHASE					
Noise	≤70Db(a)					
Dimension(W*D*H) in mm	1990*980*2080					
Packing size(W*D*H) in mm	2120*1110*2210					
Net weight & Gross weight(kg)	600/680					
Refrigerant	R417A					
Working ambient Temp.	(-19)℃~45℃					
Controller	LCD intelligence					
Compressor	Copeland					
Air source heat exchanger (Evaporator)	Type	Finned heat exchanger	Axial flow fan			
	Fan type					
Hot water side heat exchanger (Condenser)	Type	Double pipe heat exchanger				
	Water flow					
	Pipe size					
Model No.	MD300D	1	1	\$6,400.00	5	Export standard plywooden case with water-proof film inside. 5pcs for 20' container. 11pcs for 40' container.
Installation	Freestanding					
Housing material	Spray coating					
Rated heating capacity	100kw					
Hot water supply	2000L/h					
Average heating input power	25kw					
Rated heating input current	40A					
Max outlet water temp	60℃					
COP	4.5					
Power	380V/50HZ/3PHASE					
Noise	≤70Db(a)					
Dimension(W*D*H) in mm	1990*980*2080					
Packing size(W*D*H) in mm	2120*1110*2210					
Net weight & Gross weight(kg)	670/750					
Refrigerant	R417A					
Working ambient Temp.	(-19)℃~45℃					
Controller	LCD intelligence					
Compressor	Copeland					
Air source heat exchanger (Evaporator)	Type	Finned heat exchanger	Axial flow fan			
	Fan type					
Hot water side heat exchanger (Condenser)	Type	Double pipe heat exchanger				
	Water flow					
	Pipe size					



RECEIVER BANK INFORMATION:

CONSIGNEE: GUANGZHOU WANSHIHONG TRADE CO., LTD
ADD: ROOM B707, NEW WORLD BUILDING, SHUGUANG WEST RD., HUADU DISTRICT, GUANGZHOU CITY, GUANGDONG PROVINCE, P.R. CHINA
TEL: 0086-20-36900768 FAX: 0086-20-36816103
BANK NAME: CHINA CITIC BANK, GUANGZHOU HUADU SUB-BRANCH
ACCOUNT NO.: 744491018260006531 SWIFT CODE: CIBKCNBJ510
ADD: NO.68, YINGBIN RD., XINHUA STREET, HUADU DISTRICT, GUANGZHOU CITY, GUANGDONG PROVINCE, P.R. CHINA