L-22302	Silver Brazing Flux Paste Use with torch, furnace, resistance or induction heating. Meets Mil-F-4883 Spec. Contents: **57 gram**
L-32850	Fluorescent gas LEAK DETECTOR Spray Long-lasting bubbles Convenient spray bottle. Non corrosive. Non toxic Contents: **0,95 litre**
L-32849	Same as L32850 Contents: **0,071 litre**
L-36473	Aluminum Flux Paste and Solder Kit Solders aluminum easily. **For repairing aluminum evaporators and tubing, ducts and gutters. Also solders aluminum to copper. Complete repair kit** Contents: 2 x **28 gr** Flux and 2 x **15 gr** Solder 60
L-41600	Thread Sealing Compound, SLICK-TITE Stik High-performance "TEFLON" thread compound in handy stik form Contents: **35 gram**
L-44099	DUCT TAPE (all purposes). Cotton blend cloth backing for better laminating strength. Resists break down from heat and moisture. Tears straight, edges do not curl. Silver-gray blends with duct work Contents: **50m** x **50mm**
L-49050	Pipe thread Sealant. Contains Teflon. Temp. Range **-54°** to **+204°C** Pressure range **690 Bar liquid** to **206 Bar** gas. Contents: **50 mlitre**